

ACCESSORY FOR VL400 MOTORIZED OPERATING MECH. 220-250 V AC/DC FOR ALL TMTU FOR ETU GREATER THAN,EQUAL TO *E03*01*



Figure similar

Model	
Product brand name	SETRON
Product designation	Motorized operating mechanism
Type of the driving mechanism	motorized operating mechanism
General technical data	
Break time / typical	1 s
Operating frequency / maximum	120 1/h
Voltage	
Fuse protection type / for external auxiliary power supply / required	NEOZED fuse (gL/gG): 2 A / miniature circuit breaker, C char.: 2 A
Operating range factor control supply voltage rated value	
<ul style="list-style-type: none"> • at AC / at 60 Hz / initial value • at AC / at 60 Hz / Full-scale value • at DC / initial value • at DC / Full-scale value 	<p>0.85</p> <p>1.1</p> <p>0.85</p> <p>1.1</p>

Protection class	
Protection class IP	IP30
Electricity	
Make time / typical	1 s
Control current	
Operating apparent output	100 V·A
Control supply voltage	
<ul style="list-style-type: none"> • at DC / rated value / minimum • at DC / rated value / maximum • at AC / at 50 Hz / rated value / minimum • at AC / at 50 Hz / rated value / maximum • at AC / at 60 Hz / rated value / minimum • at AC / at 60 Hz / rated value / maximum 	<ul style="list-style-type: none"> 250 V 220 V 220 V 250 V 220 V 250 V
Operating range factor control supply voltage rated value / at AC / at 50 Hz	
<ul style="list-style-type: none"> • initial value • Full-scale value 	<ul style="list-style-type: none"> 0.85 1.1
Accessories	
accessories	Accessories for VL400
Connections	
Connectable conductor cross-section / stranded	
<ul style="list-style-type: none"> • minimum • maximum 	<ul style="list-style-type: none"> 1.5 mm² 1.5 mm²
Wire stripping length	9 mm
Connectable conductor cross-section	
<ul style="list-style-type: none"> • solid <ul style="list-style-type: none"> — minimum — maximum • finely stranded / with core end processing <ul style="list-style-type: none"> — minimum — maximum 	<ul style="list-style-type: none"> 1.5 mm² 1.5 mm² 1.5 mm² 1.5 mm²
Mechanical Design	
Height	159.1 mm
Width	139.2 mm
Depth	186 mm
Net weight	2 325 g
Environmental conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation / minimum • during operation / maximum 	<ul style="list-style-type: none"> -25 °C 70 °C

- during storage / minimum
- during storage / maximum

-40 °C

80 °C

Certificates

Equipment marking

- acc. to DIN EN 61346-2
- acc. to DIN EN 81346-2

M

M

General Product Approval	EMC	Declaration of Conformity	Test Certificates	Shipping Approval
--------------------------	-----	---------------------------	-------------------	-------------------

[Miscellaneous](#)



C-Tick



EG-Konf.

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)



BUREAU VERITAS

Shipping Approval



DNV



GL



LRS



PRS



RINA



RMRS

other

[Confirmation](#)

[Environmental Confirmations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL9400-3ME10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL9400-3ME10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL9400-3ME10

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>