

Product type designation

SINAUT ST1/ST7, LTOP1

SINAUT ST7, LTOP1 SINGLE LINE TRANSFORMER WITH 1 OVERVOLTAGE PROTECTION MODULE OPM, FOR APPLICATION AT THE START OR AT THE END OF A 2-WIRE CABLE



Electrical data

Transmission frequency	300 Hz ... 35 kHz
------------------------	-------------------

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport 	<p>0 ... 60 °C</p> <p>-40 ... +70 °C</p> <p>-40 ... +70 °C</p>
Installation location	As near as possible to where the cable enters the building
Protection class IP	IP20

Design, dimensions and weight

Width	90 mm
Height	75 mm
Depth	110 mm
Net weight	300 g
Mounting type	DIN rail TS35 (35 mm, EN 50 022)

Standards, specifications, approvals

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL <http://www.siemens.com/snst>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Industry Mall <https://www.siemens.com/industrymall>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

08/15/2017