

### Product type designation

### MDS U524 transponder

MOBY U MOBILE DATA MEMORY MDS U524, 32 KBYTE RAM, IP 68, -25 TO +85 DEGR./C, 111 X 67 X 23.5 MM



Figure similar

### Wireless frequencies

Operating frequency	2400 ... 2435 MHz
---------------------	-------------------

### Electrical data

Range / maximum	3 m; Range adjustable in reader in steps of 0.5 m
Protocol / with radio transmission	ISO 18000-4
Transfer rate / with radio transmission / maximum	384 kbit/s
Product feature / multitag-capable	Yes
Polarization	Circular
Product component / Backup battery	Yes
Product feature / Replaceable battery	No
Battery life / typical	8 y

### Memory

Type of memory	RAM
Storage capacity / of the user memory	32768 byte
Type of memory organization	UID (fixed code) 4 bytes, OTP: 16 bytes, user memory 32768 bytes

Number of read cycles / at ambient temperature < 40 °C / maximum	1000000000000000
Number of write cycles / at ambient temperature < 40 °C / maximum	1000000000000000
Data retention time / at ambient temperature < 40 °C / not less than	8 y

### Mechanical data

Material	PA 12 GF 25
Color	anthracite
Tightening torque / of the screw for securing the equipment / maximum	0.8 N·m
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

### Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>during read/write access</li> </ul>	-25 ... +85 °C
<ul style="list-style-type: none"> <li>outside the read/write area</li> </ul>	-25 ... +85 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C
Protection class IP	IP68
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	500 m/s <sup>2</sup>
Vibrational acceleration	100 m/s <sup>2</sup>
Resistance to mechanical stress	Free fall 1 m

### Design, dimensions and weight

Width	67 mm
Height	23.5 mm
Depth	111 mm
Net weight	100 g
Mounting type	4 x M4 screws

### Product properties, functions, components / general

Product feature	
<ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes

### Standards, specifications, approvals

Certificate of suitability	RF: EN 300440-2, SAR: EN 50371, safety: EN 60950-1, EMC: EN 301489-01, EN 301489-03, ENV 50204, FCC Part 15C (USA), cULus, safe for heart pacemakers
MTBF	285 y

### Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> <li>to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/67384964">https://support.industry.siemens.com/cs/ww/en/view/67384964</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/ident/rfid">http://www.siemens.com/ident/rfid</a>

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

07/03/2017