



Figure similar

MLFB-Ordering data

6SL3224-0BE27-5AA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input

Number of phases	3 AC
Line voltage	380 ... 480 V \pm 10 %
Line frequency	47 ... 63 Hz
Rated current with line reactor	26.00 A
Rated current without line reactor	31.50 A

Output

Number of phases	3 AC
Rated voltage	400 V
Rated power (LO)	11.00 kW / 15.00 hp
Rated power (HO)	7.50 kW / 10.00 hp
Rated current (LO)	25.00 A
Rated current (HO)	19.00 A
Max. output current	38.00 A
Pulse frequency	4 kHz
Output frequency for vector control	0 ... 200 Hz
Output frequency for V/f control	0 ... 550 Hz

General tech. specifications

Power factor λ	0.85
Offset factor $\cos \phi$	0.95
Efficiency η	0.95
Sound pressure level (1m)	60 dB
Power loss	0.30 kW

Ambient conditions

Cooling	Internal air cooling
Cooling air requirement	0.055 m ³ /s
Installation altitude	1000 m
Ambient temperature	
Operation LO	0 ... 40 °C (32 ... 104 °F)
Operation HO	0 ... 50 °C (32 ... 122 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)

Relative humidity

Max. operation	95 % RH, condensation not permitted
----------------	-------------------------------------

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

MLFB-Ordering data

6SL3224-0BE27-5AA0



Figure similar

Mechanical data

Degree of protection	IP20
Size	FSC
Net weight	7.00 kg
Width	189.0 mm
Height	334.0 mm
Depth	185.0 mm

Connections

Line side

Version	screw-type terminal
Conductor cross-section	2.50 ... 10.00 mm ²

Motor end

Version	Screw-type terminals
Conductor cross-section	2.50 ... 10.00 mm ²

DC link (for braking resistor)

Version	Screw-type terminals
Conductor cross-section	2.50 ... 10.00 mm ²
PE connection	On housing with M5 screw

Max. motor cable length

Shielded	50 m
Unshielded	100 m

Standards

Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47
---------------------------	-------------------------------------

CE marking	Low-voltage directive 2006/95/EC
------------	----------------------------------