

SIMATIC DP, 5 ELECTRON. MODULES FOR ET 200S, 4 DI HIGH FEATURE 24V DC, 15 MM WIDTH WITH PARAM. F. INPUT DELAY DIAGNOSIS F. ENCODER SHORT- CIRCUIT W. LED SF (GROUP FAULT) 5 PIECES PER PACKAGING UNIT



Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> • 24 V DC 	Yes; From power module
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
from supply voltage L+, max.	Dependent on encoder
from backplane bus 3.3 V DC, max.	10 mA
Encoder supply	
Type of output voltage	min. L+ (-0.5 V), under load
Short-circuit protection	Yes; Electronic
Output current	
<ul style="list-style-type: none"> • Rated value • permissible range 	500 mA 0 to 500 mA
Power loss	
Power loss, typ.	0.7 W

Address area	
Address space per module	
• with packing	4 bit
• without packing	1 byte
Digital inputs	
Number of digital inputs	4
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	+11 to +30V
Input current	
• for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.5 / 3 / 15 ms
— at "0" to "1", min.	0.05 / 0.4 / 2.7 / 14.85
— at "0" to "1", max.	0,15 / 0,6 / 3,3 / 15,15
— at "1" to "0", min.	0.05 / 0.4 / 2.7 / 14.85
— at "1" to "0", max.	0,15 / 0,6 / 3,3 / 15,15
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostic functions	Yes
Diagnostic messages	
• Short-circuit	Yes; Short-circuit of outputs to ground; module by module
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes; per channel
Parameter	
Remark	3 byte
Diagnostics short-circuit	Disable / enable

Potential separation

Potential separation digital inputs

- | | |
|--|-----|
| • between the channels | No |
| • between the channels and backplane bus | Yes |

Permissible potential difference

between different circuits	75 V DC/60 V AC
----------------------------	-----------------

Isolation

Isolation tested with	500 V DC
-----------------------	----------

Dimensions

Width	15 mm
-------	-------

Height	81 mm
--------	-------

Depth	52 mm
-------	-------

Weights

Weight, approx.	35 g
-----------------	------

last modified:	03/07/2017
-----------------------	------------