



Figure similar

### MLFB-Ordering data

6SL3210-1PB13-0AL0

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Rated data		General tech. specifications	
<b>Input</b>		<b>Power factor <math>\lambda</math></b>	0.85
Number of phases	1 / 3 AC	<b>Offset factor <math>\cos \phi</math></b>	0.95
Line voltage	200 ... 240 V $\pm 10\%$	<b>Efficiency <math>\eta</math></b>	0.96
Line frequency	47 ... 63 Hz	<b>Sound pressure level (1m)</b>	50 dB
Rated current (LO)	7.50 / 4.30 A	<b>Power loss</b>	0.04 kW
Rated current (HO)	6.60 A	<b>Ambient conditions</b>	
<b>Output</b>		<b>Cooling</b>	Internal air cooling
Number of phases	3 AC	<b>Cooling air requirement</b>	0.005 m <sup>3</sup> /s
Rated voltage	230 V	<b>Installation altitude</b>	1000 m
Rated power (LO)	0.55 kW / 0.75 hp	<b>Ambient temperature</b>	
Rated power (HO)	0.37 kW / 0.50 hp	<b>Operation LO</b>	-5 ... 40 °C (23 ... 104 °F)
Rated current (LO)	3.20 A	<b>Operation HO</b>	-5 ... 50 °C (23 ... 122 °F)
Rated current (HO)	2.30 A	<b>Transport</b>	-40 ... 70 °C (-40 ... 158 °F)
Max. output current	4.80 A	<b>Storage</b>	-25 ... 55 °C (-13 ... 131 °F)
Pulse frequency	4 kHz	<b>Relative humidity</b>	
Output frequency for vector control	0 ... 200 Hz	<b>Max. operation</b>	95 % RH, condensation not permitted
Output frequency for V/f control	0 ... 550 Hz		

### Overload capability

#### Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

#### High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

MLFB-Ordering data

6SL3210-1PB13-0AL0



Figure similar

### Mechanical data

Degree of protection	IP20
Size	FSA
Net weight	1.60 kg
Width	73.0 mm
Height	196.0 mm
Depth	165.0 mm

### Connections

#### Line side

Version	Plug-in screw terminals
Conductor cross-section	1.00 ... 2.50 mm <sup>2</sup>

#### Motor end

Version	Plug-in screw terminals
Conductor cross-section	1.00 ... 2.50 mm <sup>2</sup>

#### Max. motor cable length

Shielded	50 m
Unshielded	100 m

### Standards

Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47
---------------------------	-------------------------------------

CE marking	Low-voltage directive 2006/95/EC
------------	----------------------------------