

Product type designation

Product description

Cable SINAUT ST7, CC 701-0A

Plug-in cable, preferred length, preassembled
SINAUT ST7, TEST CABLE FOR CONNECTING TWO TIMS VIA
THE RS232-INTERFACE WITHOUT INTERCONNECTION OF
MODEMS (NULL-MODEM); CABLE LENGTH 6 M



Figure similar

Suitability for use	For connecting two TIM modules via an RS232 interface without modems
Cable designation	LIYCY- 10x1x0,14
Wire length	6 m

Electrical data

Insulation resistance coefficient	20 GΩ·m
Capacity per length / at 1 kHz	160 pF/m
Inductance per length	0.65 μH/m
Operating voltage	
• RMS value	250 V
• maximum	350 V

Mechanical data

Number of electrical cores	10
Design of the shield	Braided shield made of tin-plated copper wires
Outer diameter	
• of inner conductor	0.14 mm

<ul style="list-style-type: none"> • of cable sheath 	6.1 mm
Material	
<ul style="list-style-type: none"> • of the wire insulation • of cable sheath 	PVC PVC
Color	
<ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	various colors according to DIN 47100 gray
Bending radius	
<ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible 	30.5 mm 61 mm
Weight per length	66 kg/km

Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	-5 ... +70 °C -5 ... +70 °C -5 ... +70 °C 70 °C
Burning behavior	flame resistant according to IEC 60332-1
Chemical resistance	
<ul style="list-style-type: none"> • to mineral oil • to grease 	conditional resistance Conditional resistance
Radiological resistance / to UV radiation	not resistant

Product properties, functions, components / general	
Product feature	
<ul style="list-style-type: none"> • halogen-free • silicon-free 	No Yes

Standards, specifications, approvals	
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • Bureau Veritas (BV) • Det Norske Veritas (DNV) • Germanische Lloyd (GL) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) 	No No No No No No No

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication 	http://www.siemens.com/snst http://www.siemens.com/simatic-net

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

08/10/2017