

Product type designation
Product description

IE FC M12 Plug PRO (PROFINET)
M12 connector with high protection, 4-pole, D-coded
IE FC M12 PLUG PRO 2X2 M12 PLUG CONNECTOR W. RUGGED METAL HOUSING AND FC CONNECTING METHOD, WITH AXIAL CABLE OUTLET (D CODED)1 PACKAGE = 8 PIECES FOR SCALANCE X208 PRO AND ET200 PRO PN



Suitability for use

For connecting electrical cables to SCALANCE X208PRO, ET200 PRO PN or ET200 eco PN for fast assembly with the FastConnect system

Transmission rate

Transfer rate / for Industrial Ethernet 10 Mbit/s, 100 Mbit/s

Interfaces

Number of electrical connections

- for Industrial Ethernet FC TP cables 4
- for network components or terminal equipment 1

Type of electrical connection

- for Industrial Ethernet FC TP cables integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22
- for network components or terminal equipment M12 connector (D-coded)

Type of electrical connection / FastConnect

Yes

Mechanical data

Material / of the enclosure metal

Number of reuses 10

Locking mechanism design	Screw
--------------------------	-------

Design, dimensions and weight

Type of cable outlet	180° cable outlet
Width	19 mm
Height	19 mm
Depth	73 mm
Net weight	40 g

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during operation 	-40 ... +85 °C
<ul style="list-style-type: none"> during storage 	-40 ... +85 °C
<ul style="list-style-type: none"> during transport 	-40 ... +85 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Chemical resistance / to water	resistant
Protection class IP	IP65/67

Product properties, functions, components / general

Product feature	
<ul style="list-style-type: none"> PoE capability 	Yes
<ul style="list-style-type: none"> PoE+capability 	Yes
<ul style="list-style-type: none"> silicon-free 	Yes
Product component	
<ul style="list-style-type: none"> strain relief 	Yes

Standards, specifications, approvals

Certificate of suitability	
<ul style="list-style-type: none"> RoHS conformity 	Yes
<ul style="list-style-type: none"> UL approval 	Yes
<ul style="list-style-type: none"> cULus approval 	Yes
<ul style="list-style-type: none"> Railway application in accordance with EN 50155 	No
Standard for structured cabling	Cat5

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> to website: Industry Online Support 	https://support.industry.siemens.com

last modified:

06/14/2017