



SOLID-STATE, TIME-DELAYED AUXILIARY SWITCH
BLOCK SETTING RANGE 0.5 S...10 S AC 200...240 V,
1NO + 1NC, ON-DELAY, FOR MOUNTING ONTO
CONTACTORS SIZE S0...S12

General technical data:

product brandname		SIRIUS
Product designation		auxiliary switch
Size of contactor can be combined company-specific		S0 ... S12
Product function		
• star-delta circuit		No
• at the relay outputs Switchover delayed/without delay		No
Product component semi-conductor output		No
Product extension		
• optional remote control		No
• required remote control		No
Adjustable time	s	0.5 ... 10
Ambient temperature during operation	°C	-25 ... +60
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750		K
Equipment marking acc. to DIN EN 61346-2		K

Switching Function:

Switching function		
--------------------	--	--

- ON-delay
- passing make contact
- fixed clock cycle beginning with pulse
- fixed clock cycle beginning with interval
- OFF delay
- variably clocked start with impulse
- variably clocked start with interval
- with control signal
 - additive ON delay
 - passing break contact
 - OFF delay

	Yes
	No
	No
	No
	No
	No
	No
	No
	No
	No
	No
	No

Auxiliary circuit:

Number of NC contacts		
• delayed switching		1
• instantaneous contact		0
Number of NO contacts		
• delayed switching		1
• instantaneous contact		0
Number of CO contacts		
• delayed switching		0
• instantaneous contact		0

Installation/ mounting/ dimensions:

Width	mm	33
Height	mm	46
Depth	mm	73

Connections/ Terminals:

Type of electrical connection		
• for auxiliary and control current circuit		screw-type terminals

Certificates/ approvals:

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity
--------------------------	---------------------------------------	---------------------------



[Type Examination Certificate](#)



Test Certificates	Shipping Approval
-------------------	-------------------

[Special Test Certificate](#)



Shipping Approval	other
-------------------	-------



[Environmental Confirmations](#)

[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1926-2ED21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1926-2ED21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1926-2ED21&lang=en



last modified:

07/01/2017