

SIMATIC S7-400, CONTROL MODULE FM 455 S, 16 CHANNELS,
STEP AND PULSE 8/16 AI + 16 DI + 32 DO



Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	400 mA; typ. 330 mA
Power loss	
Power loss, typ.	10.7 W
Digital inputs	
Number of digital inputs	16
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Input voltage	
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	13 to 30V
Input current	

• for signal "1", typ.	7 mA
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Digital outputs	
Number of digital outputs	32
Short-circuit protection	Yes; Electronic
Limitation of inductive shutdown voltage to	L+ (-1.5 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	240 Ω
• upper limit	4 kΩ
Output voltage	
• for signal "1", min.	L+ (-2.5 V)
Output current	
• for signal "1" rated value	0.1 A
• for signal "1" permissible range for 0 to 60 °C, min.	5 mA
• for signal "1" permissible range for 0 to 60 °C, max.	150 mA
• for signal "0" residual current, max.	0.5 mA
Parallel switching of two outputs	
• for logic links	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	100 Hz
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Analog inputs	
Number of analog inputs	16; With thermocouples or 2-wire connection; 8 with Pt 100 or 4-wire connection
permissible input voltage for voltage input (destruction limit), max.	20 V
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
• Voltage	Yes
• Current	Yes

• Thermocouple	Yes
• Resistance thermometer	Yes
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• Input resistance (0 to 10 V)	100 k Ω
• -1.75 V to +11.75 V	Yes
• Input resistance (-1.75 V to +11.75 V)	100 k Ω
• -80 mV to +80 mV	Yes
• Input resistance (-80 mV to +80 mV)	10 M Ω
Input ranges (rated values), currents	
• 0 to 20 mA	Yes
• Input resistance (0 to 20 mA)	50 Ω
• 0 to 23.5 mA	Yes
• Input resistance (0 to 23.5 mA)	50 Ω
• -3.5 mA to +23.5 mA	Yes
• Input resistance (-3.5 mA to +23.5 mA)	50 Ω
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 Ω
Input ranges (rated values), thermocouples	
• Type B	Yes
• Input resistance (Type B)	10 M Ω
• Type J	Yes
• Input resistance (type J)	10 M Ω
• Type K	Yes
• Input resistance (Type K)	10 M Ω
• Type R	Yes
• Input resistance (Type R)	10 M Ω
• Type S	Yes
• Input resistance (Type S)	10 M Ω
Input ranges (rated values), resistance thermometer	
• Pt 100	Yes
• Input resistance (Pt 100)	10 M Ω
Thermocouple (TC)	
Temperature compensation	
— internal temperature compensation	Yes; Parameterizable
— external temperature compensation with Pt100	Yes; Parameterizable
Characteristic linearization	
• parameterizable	Yes
— for thermocouples	Type B, J, K, R, S
— for resistance thermometer	Pt100 (standard)
Cable length	

- shielded, max.

200 m; 50 m at 80 mV and thermocouples

Analog value generation for the inputs

Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	14 bit; 12 bit or 14 bit, parameterizable
<ul style="list-style-type: none"> • Conversion time (per channel) 	16.67 ms; for 12 bit: 16 2/3 ms for 60 Hz, 20 ms for 50 Hz; for 14 bit: 100 ms for 50 Hz and 60 Hz

Encoder

Connection of signal encoders	
<ul style="list-style-type: none"> • for voltage measurement 	Yes
<ul style="list-style-type: none"> • for current measurement as 4-wire transducer 	Yes
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes
<ul style="list-style-type: none"> — permissible quiescent current (2-wire sensor), max. 	1.5 mA

Errors/accuracies

Linearity error (relative to input range), (+/-)	0.05 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	+/-0.6 to +/-1%
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	+/-0.6 to +/-1%
<ul style="list-style-type: none"> • Resistance thermometer, relative to input range, (+/-) 	+/-0.6 to +/-1%
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Voltage, relative to input range, (+/-) 	+/-0.4 to +/-0.6 %
<ul style="list-style-type: none"> • Current, relative to input range, (+/-) 	+/-0.4 to +/-0.6 %
<ul style="list-style-type: none"> • Resistance thermometer, relative to input range, (+/-) 	+/-0.4 to +/-0.6 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	
<ul style="list-style-type: none"> • Series mode interference (peak value of interference < rated value of input range), min. 	40 dB
<ul style="list-style-type: none"> • Common mode interference (USS < 2.5 V), min. 	70 dB

Interrupts/diagnostics/status information

Substitute values connectable	Yes; Parameterizable
-------------------------------	----------------------

Integrated Functions

Control technology	
<ul style="list-style-type: none"> • Number of closed-loop controllers 	16; With thermocouples or 2-wire connection; 8 with Pt 100 or 4-wire connection

Potential separation

Potential separation controller	
• between the channels	No
• between the channels and backplane bus	Yes; Optocoupler
Permissible potential difference	
Between the inputs and MANA (UCM)	2.5 V DC
between M internally and the inputs	75 V DC/60 V AC
Isolation	
Isolation tested with	500 V DC
Connection method	
required front connector	2x 48-pin
Dimensions	
Width	50 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	1 400 g
last modified:	03/30/2017