

SIMATIC S7-400, CP 441-2 COMMUNICATIONS MODULE FOR POINT TO POINT CONNECTIONS 2 CHANNELS INCL. CONFIG. PACKAGE ON CD



Figure similar

Supply voltage	
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes
Input current	
from backplane bus 5 V DC, max.	600 mA; Without interface module
Interface modules	
• 20 mA (TTY), power consumption from 5 V/24 V, max.	300 mA at 5 V, 45 mA at 24 V
• RS 422/485 (X.27), power consumption from 5 V, max.	300 mA
• RS 232C (V.24), power consumption from 5 V, max.	300 mA
Power loss	
Power loss, typ.	0.3 W
Memory	

Memory requirements per interface in memory card of S7-CPU	1 to 5 KB for parameters; 0 to 55 KB for message texts; 0 to 64 KB for loadable drivers
--	---

Interfaces

Number of interfaces	2; variable
Interface physics, 20 mA (TTY)	Yes
Interface physics, RS 232C (V.24)	Yes
Interface (physical) RS 422/485 (X.27)	Yes
20 mA (TTY), cable length shielded, max.	1 000 m
RS 232, cable length shielded, max.	10 m
RS 422/RS 485, cable length shielded, max.	1 200 m

Point-to-point

- Transmission rate, max. 115.2 kbit/s; distributed on both interfaces
- supported printers HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined

Integrated protocol driver

- 3964 (R) Yes
- ASCII Yes
- RK512 Yes
- Printer Yes
- customer-specific drivers reloadable Yes

Transmission rate, 20 mA (TTY)

- with 3964 (R) protocol, max. 19.2 kbit/s
- with ASCII protocol, max. 19.2 kbit/s
- with printer driver, max. 19.2 kbit/s
- with RK 512 protocol, max. 19.2 kbit/s

Transmission rate, RS 422/485

- with 3964 (R) protocol, max. 115.2 kbit/s
- with ASCII protocol, max. 115.2 kbit/s
- with printer driver, max. 115.2 kbit/s
- with RK 512 protocol, max. 115.2 kbit/s

Transmission speed, RS 232

- with 3964 (R) protocol, max. 115.2 kbit/s
- with ASCII protocol, max. 115.2 kbit/s
- with printer driver, max. 115.2 kbit/s
- with RK 512 protocol, max. 115.2 kbit/s

Configuration

Configuration software

- STEP 7 Yes; own parameter assignment forms

Dimensions

Width	25 mm
Height	290 mm
Depth	210 mm

Weights

Weight, approx.

720 g; Interface module: 100 g

last modified:

03/30/2017