

SURGE SUPPRESSOR RC ELEMENT AC 240V TO 400V FOR PLUGGING ONTO CONTACTORS WITHOUT/WITH AUX.CONTACT BLOCKS






General technical data:


Product designation	surge suppressor
Design of the surge suppressor	with RC elements

Control circuit/ Control:

Type of voltage of the control supply voltage	AC
Control supply voltage frequency	
• 1 rated value	Hz 50
• 2 rated value	Hz 60
Control supply voltage 1	
• at AC	
— at 50 Hz Initial rated value	V 240
— at 50 Hz Final rated value	V 400
— at 60 Hz Final rated value	V 400
— at 60 Hz Initial rated value	V 240

Certificates/ approvals:

General Product Approval	Test Certificates	Shipping Approval
 CSA  UR  EAC	Special Test Certificate	 DNV  PRS

Shipping Approval	other
 RINA	Environmental Confirmations Confirmation Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4490-3U>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX4490-3U>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4490-3U&lang=en

last modified:

07/28/2017