

### Product type designation

### SCALANCE X101-1AUI

SCALANCE X101-1AUI IE MEDIA CONVERTER UNMANAGED 1 X 10MBIT/S RJ45 PORT, 1 X 10MBIT/S AUI SEGMENT PORT, LED DIAGNOSIS, FAULT SIGNAL. CONTACT WITH SET BUTTON, REDUNDANT POWER SUPPLY, PROFINET COMPLIANT SLEEVE MANUAL AVAILABLE AS DOWNLOAD



### Transmission rate

Transfer rate	10 Mbit/s
---------------	-----------

### Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	2
Number of electrical connections	
<ul style="list-style-type: none"> <li>• for network components or terminal equipment</li> </ul>	2
<ul style="list-style-type: none"> <li>• for signaling contact</li> </ul>	1
<ul style="list-style-type: none"> <li>• for power supply</li> </ul>	1
<ul style="list-style-type: none"> <li>• for redundant voltage supply</li> </ul>	1
Type of electrical connection	
<ul style="list-style-type: none"> <li>• for network components or terminal equipment</li> </ul>	RJ45 port, 15-pin D-sub socket
<ul style="list-style-type: none"> <li>• for signaling contact</li> </ul>	2-pole terminal block
<ul style="list-style-type: none"> <li>• for power supply</li> </ul>	4-pole terminal block

### Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / Rated value</li> </ul>	24 V

Operating current / of the signaling contacts	
<ul style="list-style-type: none"> <li>• at DC / maximum</li> </ul>	0.1 A
<b>Supply voltage, current consumption, power loss</b>	
Supply voltage	
<ul style="list-style-type: none"> <li>• external</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• external</li> </ul>	18 ... 32 V
Type of voltage / of the supply voltage	DC
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	1 A / 33 V
Consumed current	
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	0.16 A
Power loss [W]	
<ul style="list-style-type: none"> <li>• at DC / at 24 V</li> </ul>	3 W
<b>Permitted ambient conditions</b>	
Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-10 ... +60 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +80 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +80 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP30
<b>Design, dimensions and weight</b>	
Design	Compact
Width	40 mm
Height	125 mm
Depth	124 mm
Net weight	0.56 kg
Mounting type	
<ul style="list-style-type: none"> <li>• 35 mm DIN rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• S7-300 rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	Yes
<b>Product functions / Redundancy</b>	
Product function	
<ul style="list-style-type: none"> <li>• Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	No
<ul style="list-style-type: none"> <li>• Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
<b>Standards, specifications, approvals</b>	
Standard	
<ul style="list-style-type: none"> <li>• for FM</li> </ul>	FM3611: Class 1, Divison 2, Group A, B, C, D / T.., Class 1, Zone 2, Group IIC, T..

<ul style="list-style-type: none"> <li>• for hazardous zone</li> <li>• for safety / from CSA and UL</li> <li>• for hazardous zone / from CSA and UL</li> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	EN 600079-15 II 3 G EEx nA II T.. KEMA 06 ATEX 0021 X UL 60950-1, CSA C22.2 No. 60950-1 UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T.., Class 1 / Zone 2 / Group IIC / T.. EN 61000-6-4:2001 EN 61000-6-4:2001
Certificate of suitability <ul style="list-style-type: none"> <li>• CE marking</li> <li>• C-Tick</li> <li>• KC approval</li> </ul>	EN 61000-6-2:2001, EN 61000-6-4:2001 Yes Yes Yes
Marine classification association <ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> <li>• Bureau Veritas (BV)</li> <li>• Det Norske Veritas (DNV)</li> <li>• Germanische Lloyd (GL)</li> <li>• Lloyds Register of Shipping (LRS)</li> <li>• Nippon Kaiji Kyokai (NK)</li> <li>• Polski Rejestr Statkow (PRS)</li> </ul>	Yes Yes Yes Yes Yes Yes No
MTBF / at 40 °C	136 y

#### Further Information / Internet Links

Internet-Link <ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> <li>• to website: Industrial communication</li> <li>• to website: Industry Mall</li> <li>• to website: Information and Download Center</li> <li>• to website: Image database</li> <li>• to website: CAx Download Manager</li> <li>• to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
--	---

#### Security information

---

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

06/14/2017