

Product type designation

RF382R reader

SIMATIC RF300 READER RF382R (ISO-SCANMODE) RS422/232-INTERFACE IP 67, -25 UP TO +70 DGR/C, 160 X 80 X 41 MM WITH INTEGRATED SPECIAL ANTENNA



Suitability for operation

RF300 and ISO 15693 Transponder (MDS Dxxx), lateral antenna field, for serial connection to control systems (Scan Mode)

Wireless frequencies

Operating frequency / Rated value 13.56 MHz

Electrical data

Range / maximum	75 mm; Range adjustable in reader via transmission power, range is dependent on transponder type: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	RF300-specific, ISO 15693, ISO 18000-3
Transfer rate / with radio transmission / maximum	106 kbit/s
Product feature / multitag-capable	No
Transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
Transmission time / for user data	
<ul style="list-style-type: none"> for read access / per byte / typical 	0.13 ms

Interfaces

Standard for interfaces / for communication	RS422/RS232
Type of electrical connection	M12, 8-pin

Mechanical data	
Material	PA 12
Color	anthracite
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

Supply voltage, current consumption, power loss	
Supply voltage	
<ul style="list-style-type: none"> • at DC / Rated value • at DC 	24 V 20.4 ... 28.8 V
Consumed current / at DC / at 24 V	
<ul style="list-style-type: none"> • typical 	0.16 A

Permitted ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport 	-25 ... +70 °C -40 ... +85 °C -40 ... +85 °C
Protection class IP	IP67
Shock resistance	EN 60721-3-7, Class 7 M2
Shock acceleration	500 m/s ²
Vibrational acceleration	200 m/s ²

Design, dimensions and weight	
Width	80 mm
Height	41 mm
Depth	160 mm
Net weight	0.6 kg
Mounting type	4 x M5 screws
Wire length	
<ul style="list-style-type: none"> • with RS 232 interface / maximum • for RS 422 interface / maximum 	30 m 1000 m

Product properties, functions, components / general	
Display version	3-color LED
Product feature / silicon-free	Yes

Standards, specifications, approvals	
Certificate of suitability	Wireless according to R&TTE guidelines EN 300 330, EN 301489, CE, FCC, UL/CSA
MTBF	109 y

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication 	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid

- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

07/03/2017