

numer artykułu	Producent	rodzina	opis	nowe	odnowione
1790L811A	SIEMENS	MICROMASTER	MICROMASTER 440 TERMINAL BLOCK MODULE	0	6
6SE9110-7BA53	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ12 120W CLASS A FILTER 230V 1 AC	6	1
6SE9111-5BA53	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ25 250W CLASS A FILTER 230V 1 AC	0	1
6SE9112-0BA53	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ37 370W CLASS A FILTER 230V 1 AC	0	2
6SE9112-0CA13	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ37/2 370W WITHOUT FILTER 230V 1 AC	0	4
6SE9112-6BA53	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ55 550W CLASS A FILTER 230V 1 AC	0	3
6SE9112-6CA13	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ55/2 550W WITHOUT FILTER 230V 1 AC	1	0
6SE9113-4BA53	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ75 750W CLASS A FILTER 230V 1 AC	0	2
6SE9113-7JA13	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ150/3 1.5KW WITHOUT FILTER 400-460V 3AC	0	1
6SE9210-7BA40	SIEMENS	MICROMASTER	MICROMASTER MM12 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.12 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE9210-7CA40	SIEMENS	MICROMASTER	MICROMASTER MM12/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.12 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	1
6SE9211-1DA40	SIEMENS	MICROMASTER	MICROMASTER MM37/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 0.37 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	5
6SE9211-5BA40	SIEMENS	MICROMASTER	MICROMASTER MM25 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.25 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	4
6SE9212-1BA40	SIEMENS	MICROMASTER	MICROMASTER MM37 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.37 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	+ 10
6SE9212-1CA40	SIEMENS	MICROMASTER	MICROMASTER MM37/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.37 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	+ 10	0
6SE9212-8BA40	SIEMENS	MICROMASTER	MICROMASTER MM55 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.55 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE9212-8CA40	SIEMENS	MICROMASTER	MICROMASTER MM55/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.55 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE9213-6BA40	SIEMENS	MICROMASTER	MICROMASTER MM75 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE	0	1
6SE9213-6CA40	SIEMENS	MICROMASTER	MICROMASTER MM75/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.75 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	2
6SE9215-2CB40	SIEMENS	MICROMASTER	MICROMASTER MM110/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 1.1 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	3

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE9215-8DB40	SIEMENS	MICROMASTER	MICROMASTER MM220/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 2.2 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	2	8
6SE9217-3DB40	SIEMENS	MICROMASTER	MICROMASTER MM300/3 UNFILTERED 3AC 380/500V +/-10% 50/60HZ CONSTANT TORQUE: 3.0 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE9221-0DC40	SIEMENS	MICROMASTER	MICROMASTER MM400/3 UNFILTERED 3AC 380-500V /-10% 50/60HZ CONSTANT TORQUE: 4.0 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM(H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE9221-5DC40	SIEMENS	MICROMASTER	MICROMASTER MM750/3 UNFILTERED 3AC 380-500V /-10% 50/60HZ CONSTANT TORQUE: 7.5 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM(H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE9221-8CC13	SIEMENS	MICROMASTER	MICROMASTER MM400/2 UNFILTERED 3AC 208-230V +/-10% 50/60HZ CONSTANT TORQUE: 4.0 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	1
6SE9514-0DA40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-150/3 UNFILTERED 3AC 380-500V +/-10% 47- 63HZ VARIABLE TORQUE:1.5KW 147 X 73 X 141 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	2
6SE9611-8DF10-Z	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI75/3 UNFILTERED 3AC 380-500V +/-10% 47- 63HZ CONSTANT TORQUE:0.75KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 0.75KW 105 X 120 X 160 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	1
6SE9612-7DF10-Z	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI110/3 UNFILTERED 3AC 380-500V +/-10% 47- 63HZ CONSTANT TORQUE:1.1KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 1.1KW 105 X 120 X 160 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	1	0
6SE9613-7DF10-Z	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI150/3 UNFILTERED 3AC 380-500V +/-10% 47- 63HZ CONSTANT TORQUE:1.5KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 1.5KW 105 X 120 X 160 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	3
6SE9613-7DF50-Z	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI150/3 WITH BUILT IN FILTER CLASS A 3AC 380-480V +/-10% 47-63HZ CONSTANT TORQUE:1.5KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 1.5KW 105 X 120 X 160 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	1
6SE9615-8DD10	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI220/3 UNFILTERED 3AC 380-500V +/-10% 47- 63HZ CONSTANT TORQUE:2.2KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 2.2KW 128 X 171 X 243 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	3
6SE9621-7DD10-Z	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI750/3 UNFILTERED 3AC 380-500V /-10% 47- 63HZ CONSTANT TORQUE:7.5KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 7.5KW 128 X 171 X 243 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO 50 C	1	0
6SE9621-7DD60	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI750/3 WITH BUILT IN FILTER CLASS B 3AC 380-480V +/-10% 47-63HZ CONSTANT TORQUE:7.5KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 7.5KW 128 X 171 X 243 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	1
6SE9621-7DD60-Z	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI750/3 WITH BUILT IN FILTER CLASS B 3AC 380-480V +/-10% 47-63HZ CONSTANT TORQUE:7.5KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 7.5KW 128 X 171 X 243 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	2
6SE9996-0XA17	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED AND COMBIMASTER OPTION CUSTOMER SPECIFIC COMMUNICATION OPTION	2	+ 10

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE3111-5CA40	SIEMENS	MICROMASTER	SIMOVERT P MICROMASTER 1/3-PH. 230V 50/60HZ, MM25/2 RATED OUTPUT 250W WEIGHT 1.8KG	0	2
6SE3114-0DC40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV150/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 1.5 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	3
6SE3190-0XX87-8BF0	SIEMENS	MICROMASTER	CLEAR TEXT DISPLAY FOR 6SE3111 TO 6SE3121 1PH AND 6SE3114 TO 6SE3121 3PH FOR 6SE3121 TO 6SE3127 UND 575V 6SE3121 TO 6SE3125 F. MICROMASTER AND MIDIMASTER	0	2
6SE3210-7BA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV12 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.12 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	6
6SE3211-1DA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV37/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 0.37 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	6	5
6SE3211-4DA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV55/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 0.55 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	2	+ 10
6SE3211-5BA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV25 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.25 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE3211-5CA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV25/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.25 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	4	0
6SE3212-0DA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV75/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 0.75 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	5
6SE3212-1CA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV37/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.37 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	0
6SE3212-7DA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV110/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 1.1 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	2
6SE3212-8CA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV55/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.55 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE , 0-50 DEG C	1	+ 10
6SE3213-6CA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV75/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.75 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE3214-0DA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV150/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 1.5 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	4	5
6SE3215-2BB40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV110 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 1.1 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	2

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE3215-2CB40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV 110/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 1.1 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	3
6SE3215-8DB40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV220/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 2.2 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	6
6SE3215-8DB50	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV220/3 WITH BUILT IN CLASS A FILTER 3AC 380-480V +/-10% 50/60HZ CONSTANT TORQUE: 2.2 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	9
6SE3216-8BB40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV150 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 1.5 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	2
6SE3216-8CB40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV150/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 1.5 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	3
6SE3217-3DB40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV300/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 3.0 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	+ 10
6SE3217-3DB50	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV300/3 WITH BUILT IN CLASS A FILTER 3AC 380-480V +/-10% 50/60HZ CONSTANT TORQUE: 3.0 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	2
6SE3221-0BC40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV220 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 2.2 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 185 X 215 X 195 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE3221-0CC40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV220/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 2.2 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 185 X 215 X 195 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE3221-0DC40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV400/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 4.0 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM(H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	2
6SE3221-0DC50	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV400/3 WITH BUILT IN CLASS A FILTER 3AC 380-480V +/-10% 50/60HZ CONSTANT TORQUE: 4.0 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM(H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE3221-3DC50	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV550/3 WITH BUILT IN CLASS A FILTER 3AC 380-480V +/-10% 50/60HZ CONSTANT TORQUE: 5.5 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM(H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG	0	1
6SE3221-5DC40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV750/3 UNFILTERED 3AC 380-500V +/-10% 50/60HZ CONSTANT TORQUE: 7.5 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM(H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	0
6SE6400-0BE00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 BASIC OPERATOR PANEL 2 (BOP-2)	2	9
6SE6400-0BE00-0AA1	SIEMENS	MICROMASTER	MICROMASTER 4 BASIC OPERATOR PANEL 2 (BOP-2)	0	+ 10
6SE6400-0BP00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 BASIC OPERATOR PANEL (BOP)	0	+ 10

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6400-0EN00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 ENCODER OPTION MODULE TTL DIFFERENTIAL / HTL INCREMENTAL 300 KHZ MAX., 5 V OR 24 V, 3W ENCA, ENCB, ENCZ /// ENC-REC	0	+ 10
6SE6400-0GP00-0BA0	SIEMENS	MICROMASTER	MICROMASTER 4 GLAND PLATE CABLE SCREENING KIT (FSB)	+ 10	0
6SE6400-0GP00-0CA0	SIEMENS	MICROMASTER	MICROMASTER 4 GLAND PLATE CABLE SCREENING KIT (FSC)	9	0
6SE6400-0PM00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 BOP/AOP SINGLE INVERTER DOOR MOUNTING KIT	3	6
6SE6400-1PB00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 PROFIBUS MODULE FOR MECHANICAL REASONS, USE CONNECTOR 6GK1500-0EA02 FOR MM4 FX/GX	0	+ 10
6SE6400-2FA00-6AD0	SIEMENS	MICROMASTER	MICROMASTER 4 EMC FILTER 200V-480V 3AC 6A FOOTPRINT FSA - CLASS A	9	+ 10
6SE6400-2FL01-0AB0	SIEMENS	MICROMASTER	MICROMASTER 4 LOW LEAKAGE EMC FILTER 200V-240V 1AC 10A FOOTPRINT FSA - CLASS B NOT FOOTPRINT FOR V20	0	1
6SE6400-2FS03-8CD0	SIEMENS	MICROMASTER	MICROMASTER 4 SUPPLEMENTARY EMC FILTER 200V-480V 3AC 38A FOOTPRINT FSC - CLASS B	0	2
6SE6400-3CC00-2AD3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 1,9A FOOTPRINT FSA - 3X5.2MH NOT FOOTPRINT FOR V20	0	+ 10
6SE6400-3CC00-4AB3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-240V 1AC 3,4A FOOTPRINT FSA - 9.5MH NOT FOOTPRINT FOR V20	1	3
6SE6400-3CC00-4AD3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 3,5A FOOTPRINT FSA - 3X3.9MH NOT FOOTPRINT FOR V20	7	7
6SE6400-3CC00-6AD3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 4,8A FOOTPRINT FSA - 3X1.53MH NOT FOOTPRINT FOR V20	2	4
6SE6400-3CC02-2CD3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 25A FOOTPRINT FSC - 1MH NOT FOOTPRINT FOR V20	3	10
6SE6400-3CC03-5CD3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 31,3A FOOTPRINT FSC - 0.53MH NOT FOOTPRINT FOR V20	0	3
6SE6400-3CC04-4DD0	SIEMENS	MICROMASTER	MICROMASTER 4 COMMUTATING CHOKE 380-600 V 3AC 45,8A FOOTPRINT FSD - 0.41 MH NOT FOOTPRINT FOR V20	3	1
6SE6400-3CC05-2DD0	SIEMENS	MICROMASTER	MICROMASTER 4 COMMUTATING CHOKE 200-480 V 3AC 53,6A FOOTPRINT FSD - 0.29 MH	1	3
6SE6400-3CC08-3ED0	SIEMENS	MICROMASTER	MICROMASTER 4 COMMUTATING CHOKE 380-600 V 3AC 86,9A FOOTPRINT FSE - 0.22 MH	0	3
6SE6400-3CC11-7FD0	SIEMENS	MICROMASTER	MICROMASTER 4 COMMUTATING CHOKE 200-480 V 3AC 186 A STAND ALONE FSF - 0.09 MH	0	1
6SE6400-3TC03-2CD3	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 200V-480V 3AC 26A FOOTPRINT FSC - 0.332 MH NOT FOOTPRINT FOR V20 400V: UP TO 200M CABLE LENGTH 480V: UP TO 100M CABLE LENGTH	1	4
6SE6400-3TC14-5FD0	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 380-480 V 3AC 145A (HO/CT)/178A (LO/VT) STAND ALONE FS F - 0.2 MH	0	4
6SE6400-4BC05-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 BRAKING RESISTOR 200-240 V 180R 1000 W PK 50 W CONT 230 X 72 X 43.5 MM H X W X D IP20	1	2
6SE6400-4BD12-0BA0	SIEMENS	MICROMASTER	MICROMASTER 4 BRAKING RESISTOR 380-480 V 160R 4000 W PK 200 W CONT 239 X 149 X 43.5 MM H X W X D IP20	5	2
6SE6400-4BD21-2DA0	SIEMENS	MICROMASTER	MICROMASTER 4 BRAKING RESISTOR 380-480 V 27R 24000 W PK 1200 W CONT 515 X 270 X 175 MM H X W X D IP20	2	0
6SE6400-4BD22-2EA0	SIEMENS	MICROMASTER	MICROMASTER 4 BRAKING RESISTOR 380-480 V 15R 44000 W PK 2200 W CONT 645 X 270 X 175 MM H X W X D IP20	0	1
6SE6401-1EM00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 EM MODULE (ELECTROMECHANICAL BRAKE CONTROL MODULE) FOR MM411 AND CM411 114.5 X 132 X 50 (H X W X D) IP66	0	1
6SE6401-1PB00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 PROFIBUS MODULE FOR MM411 AND CM411 114.5 X 132 X 50 (H X W X D) IP66	0	+ 10
6SE6401-1RB00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 REM MODULE (RESISTOR AND ELECTROMECHANICAL BRAKE CONTROL MODULE) FOR MM411 AND CM411 131 X 132 X 111 (H X W X D) IP66	0	+ 10
6SE6410-2BB13-7AA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITH BUILT-IN CLASS B FILTER 1AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.37 KW 150 X 69 X 118 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	0	1

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6410-2BB15-5BA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITH BUILT-IN CLASS B FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.55 KW 150 X 69 X 138 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT OP	0	1
6SE6410-2BB17-5BA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITH BUILT-IN CLASS B FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.75 KW 150 X 69 X 138 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT OP	0	1
6SE6410-2UA13-7AA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITHOUT FILTER 1AC 100-120 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.37 KW 150 X 69 X 118 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	5	6
6SE6410-2UB11-2AA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITHOUT FILTER 1AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.12 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.12 KW 150 X 69 X 118 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	1	3
6SE6410-2UB12-5AA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITHOUT FILTER 1AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.25 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.25 KW 150 X 69 X 118 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	0	1
6SE6410-2UB13-7AA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITHOUT FILTER 1AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.37 KW 150 X 69 X 118 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	0	4
6SE6410-2UB17-5BA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITHOUT FILTER 1AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.75 KW 150 X 69 X 138 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	0	4
6SE6411-6BD13-7BA1	SIEMENS	MICROMASTER	MICROMASTER 411 WITH BUILT IN CLASS B FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.37 KW 135 X 222 X 154 (H X L X W) PROTECTION IP66 AMBIENT TEMP -10 TO +40 DEG C	1	0
6SE6411-6BD17-5BA1	SIEMENS	MICROMASTER	MICROMASTER 411 WITH BUILT IN CLASS B FILTER 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.75 KW 135 X 222 X 154 (H X L X W) PROTECTION IP66 AMBIENT TEMP -10 TO 40 DEG C	0	+ 10
6SE6411-6BD22-2CA1	SIEMENS	MICROMASTER	MICROMASTER 411 WITH BUILT IN CLASS B FILTER 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 170 X 255 X 177 (H X L X W) PROTECTION IP66 AMBIENT TEMP -10 TO 40 DEG C	0	+ 10
6SE6420-2AB11-2AA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.12 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.12 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	1	6
6SE6420-2AB12-5AA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.25 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.25 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	1	5
6SE6420-2AB12-5AA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.25 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.25 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	+ 10
6SE6420-2AB13-7AA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	2

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6420-2AB13-7AA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	+ 10
6SE6420-2AB15-5AA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	2
6SE6420-2AB15-5AA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	+ 10	1
6SE6420-2AB17-5AA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.75 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	5
6SE6420-2AB17-5AA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.75 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	1
6SE6420-2AB21-1BA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 1.1 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.1 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	1
6SE6420-2AB21-5BA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.5 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2AB21-5BA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.5 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	2
6SE6420-2AB22-2BA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	1	6
6SE6420-2AB23-0CA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	5
6SE6420-2AC23-0CA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	1	0
6SE6420-2AC24-0CA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 4 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	2	0
6SE6420-2AC25-5CA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 5.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	1	1
6SE6420-2AD22-2BA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	+ 10	+ 10

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6420-2AD23-0BA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	3
6SE6420-2AD23-0BA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	2
6SE6420-2AD24-0BA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 4 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	3
6SE6420-2AD24-0BA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 4 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	4
6SE6420-2AD25-5CA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 5.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	3
6SE6420-2AD27-5CA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 7.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2AD27-5CA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 7.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	+ 10
6SE6420-2AD31-1CA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 11 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 11 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2AD31-1CA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 11 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 11 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	6
6SE6420-2UC12-5AA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.25 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.25 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	7
6SE6420-2UC13-7AA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	5
6SE6420-2UC13-7AA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	10
6SE6420-2UC21-5BA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.5 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2UC22-2BA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	5	3

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6420-2UC23-0CA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	2
6SE6420-2UC25-5CA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 5.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	1
6SE6420-2UD13-7AA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	2
6SE6420-2UD13-7AA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	+ 10
6SE6420-2UD15-5AA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	3
6SE6420-2UD15-5AA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	3	4
6SE6420-2UD17-5AA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.75 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	+ 10
6SE6420-2UD21-1AA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 1.1 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.1 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	7
6SE6420-2UD21-5AA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.5 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2UD21-5AA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.5 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	+ 10
6SE6420-2UD22-2BA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	6
6SE6420-2UD22-2BA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	3
6SE6420-2UD23-0BA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2UD23-0BA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	1	+ 10

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6420-2UD24-0BA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 4 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2UD25-5CA1	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 5.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	3
6SE6420-2UD27-5CA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 7.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	2
6SE6430-2AD27-5CA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 7.5 KW OVERLOAD 110% 60 S, 140% 3 S 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	1	0
6SE6430-2AD31-1CA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 11 KW OVERLOAD 110% 60 S, 140% 3 S 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	3
6SE6430-2AD31-5CA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 15 KW OVERLOAD 110% 60 S, 140% 3 S 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	6
6SE6430-2AD31-8DA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 18.5 KW OVERLOAD 110% 60 S, 140% 3 S 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	4
6SE6430-2AD32-2DA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 22 KW OVERLOAD 110% 60 S, 140% 3 S 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	7
6SE6430-2AD33-0DA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 30 KW OVERLOAD 110% 60 S, 140% 3 S 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	2
6SE6430-2AD33-7EA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 37 KW OVERLOAD 110% 60 S, 140% 3 S 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	1
6SE6430-2AD35-5FA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 55 KW OVERLOAD 110% 60 S, 140% 3 S 1150 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	4
6SE6430-2AD37-5FA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 75 KW OVERLOAD 110% 60 S, 140% 3 S 1150 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	3
6SE6430-2AD38-8FA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 90 KW OVERLOAD 110% 60 S, 140% 3 S 1150 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	5
6SE6430-2UD31-1CA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 11 KW OVERLOAD 110% 60 S, 140% 3 S 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	1

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6430-2UD31-5CA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 15 KW OVERLOAD 110% 60 S, 140% 3 S 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	1
6SE6430-2UD31-8DA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 18.5 KW OVERLOAD 110% 60 S, 140% 3 S 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	4
6SE6430-2UD33-0DA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 30 KW OVERLOAD 110% 60 S, 140% 3 S 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	2
6SE6430-2UD33-7EA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 37 KW OVERLOAD 110% 60 S, 140% 3 S 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	1
6SE6430-2UD35-5FA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 55 KW OVERLOAD 110% 60 S, 140% 3 S 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	1
6SE6430-2UD37-5FA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 75 KW OVERLOAD 110% 60 S, 140% 3 S 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	3	3
6SE6430-2UD38-8FA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 90 KW OVERLOAD 110% 60 S, 140% 3 S 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +40 DEG. C WITHOUT AOP/BOP	0	1
6SE6430-2UD41-3FA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 132 KW OVERLOAD 110% 59 S, 150% 1 S 1400 X 326 X 356 (H X W X D) PROTECTION IP20 AMBIENT TEMP. 0 TO +40 DEG. C WITHOUT AOP/BOP SERVICE BY SPARE PART	0	1
6SE6430-2UD42-0GA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 200 KW OVERLOAD 110% 59 S, 150% 1 S 1533 X 326 X 545 (H X W X D) PROTECTION IP20 AMBIENT TEMP. 0 TO +40 DEG. C WITHOUT AOP/BOP	0	1
6SE6430-2UD42-5GA0	SIEMENS	MICROMASTER	MICROMASTER 430 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ SQUARED TORQUE POWER 250 KW OVERLOAD 110% 59 S, 150% 1 S 1533 X 326 X 545 (H X W X D) PROTECTION IP20 AMBIENT TEMP. 0 TO +40 DEG. C WITHOUT AOP/BOP	0	1
6SE6436-2BD31-1CA0	SIEMENS	MICROMASTER	MICROMASTER 436,11KW,CLASS B,IP20	0	1
6SE6440-2AB12-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.25 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.25 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT A	0	9
6SE6440-2AB13-7AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT	0	+ 10
6SE6440-2AB15-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT	0	1
6SE6440-2AB17-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.75 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT	0	1

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6440-2AB21-1BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 1.1 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 1.1 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT A	0	1
6SE6440-2AB21-5BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 1.5 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT A	0	4
6SE6440-2AB22-2BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT A	5	6
6SE6440-2AB23-0CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 3 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BO	0	3
6SE6440-2AC23-0CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 4 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/B	0	2
6SE6440-2AD22-2BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	+ 10
6SE6440-2AD23-0BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 3 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/B	0	+ 10
6SE6440-2AD24-0BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 4 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	9
6SE6440-2AD25-5CA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	1
6SE6440-2AD25-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT A	0	6
6SE6440-2AD27-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 7.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 11 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/	0	3
6SE6440-2AD31-1CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 11 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 15 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	4
6SE6440-2AD31-5DA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 15 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 18.5 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	1
6SE6440-2AD31-5DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 15 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 18.5 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	5

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6440-2AD31-8DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 18.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 22 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	+ 10
6SE6440-2AD32-2DA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 22 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 30 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/B	0	7
6SE6440-2AD32-2DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 22 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 30 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/B	0	+ 10
6SE6440-2AD33-0EA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 30 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 37 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/B	0	7
6SE6440-2AD33-7EA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 37 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 45 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/B	0	6
6SE6440-2AD34-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 45 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 55 KW 1150 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/	0	2
6SE6440-2AD35-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 75 KW 1150 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	3
6SE6440-2AD37-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 75 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 90 KW 1150 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/	0	1
6SE6440-2UC11-2AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.12 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.12 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	5
6SE6440-2UC12-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.25 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.25 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	1	4
6SE6440-2UC15-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER .55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UC21-1BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 1.1 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 1.1 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UC24-0CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 5.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UC25-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	2

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6440-2UD13-7AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.37 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.37 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD15-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	+ 10
6SE6440-2UD17-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.75 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	+ 10
6SE6440-2UD21-1AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 1.1 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 1.1 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	4
6SE6440-2UD21-5AA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 1.5 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT AOP/BOP	0	4
6SE6440-2UD21-5AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 1.5 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	+ 10
6SE6440-2UD22-2BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	2
6SE6440-2UD23-0BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 3 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD24-0BA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 4 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	4
6SE6440-2UD25-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD27-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 7.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 11 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	6
6SE6440-2UD31-1CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 11 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 15 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	1	1
6SE6440-2UD31-5DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 15 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 18.5 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	2
6SE6440-2UD31-8DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 18.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 22 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6440-2UD32-2DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 22 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 30 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD33-0EA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 30 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 37 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	1	1
6SE6440-2UD33-7EA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 37 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 45 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD34-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 45 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 55 KW 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD35-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 75 KW 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	2	4
6SE6440-2UD37-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 75 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 90 KW 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	4
6SE6440-2UD38-8FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 90 KW OVERLOAD 136% 57 S, 160% 3 S SQUARED TORQUE POWER 110 KW 1400 X 326 X 356 (H X W X D) PROTECTION IP20 AMBIENT TEMP. 0 TO +40 DEG. C WITHOUT AOP/BOP	0	3
6SE6440-2UD41-1FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 110 KW OVERLOAD 136% 57 S, 160% 3 S SQUARED TORQUE POWER 132 KW 1400 X 326 X 356 (H X W X D) PROTECTION IP20 AMBIENT TEMP. 0 TO +40 DEG. C WITHOUT AOP/BOP	0	3
6SE6440-2UE17-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 1.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	3
6SE6440-2UE21-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 1.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 2.2 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	3
6SE6440-2UE22-2CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 4 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	3	1
6SE6440-2UE24-0CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 5.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UE27-5CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 7.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 11 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UE31-1CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 11 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 15 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	3

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6440-2UE31-5DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 15 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 18.5 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	4
6SE6440-2UE32-2DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 22 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 30 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UE33-7EA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 37 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 45 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	2
6SE6440-2UE37-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 75 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 90 KW 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	2
A5E00317637	SIEMENS	MICROMASTER	MICROMASTER INTERFACE	0	3
6SE3286-2AA00	SIEMENS	MICROMASTER	MULTI-LANGUAGE DOCUMENTATION AND SOFT-WARE TOOLS ON CD-ROM, FOR MICROMASTER VECTOR AND MIDIMASTER VECTOR	+ 10	0
6SE6400-3CC03-5CD0	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 35A FOOTPRINT FSC - 0.53MH	0	4
6SE6100-2FA00-6AD0	SIEMENS	MICROMASTER	MICROMASTER 4 EMC FILTER	0	1
6SE6411-6BD21-1VS3	SIEMENS	MICROMASTER	MICROMASTER 411 WITH BUILT IN CLASS B FILTER 3AC 380-480V +10/-10% 47-63HZ CONSTANT TORQUE POWER 1.1 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.1 KW 135 X 222 X 154 (H X L X W) PROTECTION IP66 AMBIENT TEMP -10 TO +40 DEG C	0	2
6SE9521-7DC50	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-750/3 WITH BUILT IN FILTER CLASS A 3AC , 380-480V +/-10% 47-63HZ VARIABLE TORQUE:7,5KW 215 X 185 X 195 MM (H X W X, D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE9521-8CC40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-400/2 UNFILTERED 3AC 208-240V +/-10% 47-63HZ VARIABLE TORQUE:4KW 215 X 185 X 195 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	2
6SE9590-0XX87-8BF0	SIEMENS	MICROMASTER	OPERATOR PANEL OPE FOR USE WITH MICROMASTER ECO AND MIDIMASTER ECO	+ 10	+ 10
6SE9996-0XA20	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED AND COMBIMASTER OPTION CM PROFIBUS CB155 WITH FCC CONNECTOR FOR ISSUE A CSB UNITS ONLY	0	1
6SE3200-3TC03-2CD0	SIEMENS	MICROMASTER	MICROMASTER 3 OUTPUT CHOKE 200V-480V 3AC +/-10% 26/32A FOOTPRINT FSC	1	0
6SE2008-2AA00	SIEMENS	MICROMASTER	MICROMASTER VECTOR 5,5KW	0	1
6SE3210-7CA40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV12/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 0.12 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 175 X 73 X 141 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	0
6SE3221-3CC40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV300/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 3.0 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 185 X 215 X 195 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	1	0
6SE3221-8CC40	SIEMENS	MICROMASTER	MICROMASTER VECTOR MMV400/2 UNFILTERED 3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 4 KW OVERLOAD 150% 60SEC, 200% 3SEC VARIABLE TORQUE: N/A 185 X 215 X 195 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	3
6SE6400-0GP00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 GLAND PLATE CABLE SCREENING KIT (FSA)	+ 10	0
6SE6400-0PA00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 PC - AOP MOUNTING KIT	+ 10	2
6SE6400-1CB00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 CANOPEN MODULE FOR MM420/MM430/MM440 161 X 73 X 43.5 (H X WX D) IP20	0	+ 10

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6400-2FA01-4BC0	SIEMENS	MICROMASTER	MICROMASTER 4 EMC FILTER 200V-240V 3AC 14A FOOTPRINT FSB - CLASS A	1	4
6SE6400-2FL02-6BB0	SIEMENS	MICROMASTER	MICROMASTER 4 LOW LEAKAGE EMC FILTER 200V-240V 1AC 26A FOOTPRINT FSB - CLASS B NOT FOOTPRINT FOR V20	+ 10	0
6SE6400-2FS02-6BB0	SIEMENS	MICROMASTER	MICROMASTER 4 SUPPLEMENTARY EMC FILTER 200V-240V 1AC 26A FOOTPRINT FSB - CLASS B	0	3
6SE6400-3CC00-4CE3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 380-600V 3AC 4,1A FOOTPRINT FSC - 5.68 MH	0	3
6SE6400-3CC01-0AB3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-240V 1AC 8,1A FOOTPRINT FSA - 3.6MH NOT FOOTPRINT FOR V20	1	0
6SE6400-3CC01-0BD0	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 10A FOOTPRINT FSB - 2.2MH	0	1
6SE6400-3CC01-0BD3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 9A FOOTPRINT FSB - 2.2MH NOT FOOTPRINT FOR V20	3	9
6SE6400-3CC01-4BD0	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 14A FOOTPRINT FSB - 1.3MH	0	2
6SE6400-3CC01-4BD3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 12,1A FOOTPRINT FSB - 1.3MH NOT FOOTPRINT FOR V20	3	1
6SE6400-3CC02-2CD0	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC 22A FOOTPRINT FSC - 1MH	0	1
6SE6400-3CC03-5CB3	SIEMENS	MICROMASTER	MICROMASTER 4 AC COMMUTATION CHOKE 200V-240V 1AC 29,5A FOOTPRINT FSC - 0.57MH NOT FOOTPRINT FOR V20	0	2
6SE6400-3CC11-2FD0	SIEMENS	MICROMASTER	MICROMASTER 4 COMMUTATING CHOKE 380-600 V 3AC 151 A STAND ALONE FSF - 0.15 MH	0	1
6SE6400-3TC00-4AD1	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 230V 3AC 4A FOOTPRINT FSA - 1.7MH ONLY UP TO 200M CABLE LENGTH	1	0
6SE6400-3TC00-4AD2	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 380-480V 3AC 4A FOOTPRINT FSA - 2.0MH NOT FOOTPRINT FOR V20 400V: UP TO 150M CABLE LENGTH 440V: UP TO 100M CABLE LENGTH	1	0
6SE6400-3TC01-0BD3	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 200V-480V 3AC 10A FOOTPRINT FSB - FSB - 1.243MH NOT FOOTPRINT FOR V20 230V: UP TO 200M CABLE LENGTH 400V: UP TO 150M CABLE LENGTH 480V: UP TO 100M CABLE LENGTH	0	4
6SE6400-3TC01-8CE3	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 500-600V 3AC 18A FOOTPRINT FSC - 0.75 MH 550V: UP TO 100M CABLE LENGTH	0	1
6SE6400-3TC03-8DD0	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 380-480 V 3AC 38A (HO/CT)/45A (LO/VT) STAND ALONE FS D - 0.82 MH	2	0
6SE6400-3TC05-4DD0	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 200-480 V 3AC 54A (HO/CT)/68A (LO/VT) STAND ALONE FS D - 0.232 MH	6	0
6SE6400-3TC08-0ED0	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT CHOKE 200-480 V 3AC 80A (HO/CT)/104A (LO/VT) STAND ALONE FS E - 0.111 MH	0	1
6SE6400-3TD01-0BD0	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT LC FILTER 380-480V 3AC 11.2 / 10.2 A (40 / 50 GRD C) FOOTPRINT FSB 340 X 150 X 100 (H X W X D)	0	1
6SE6400-3TD01-0CE0	SIEMENS	MICROMASTER	MICROMASTER 4 OUTPUT LC FILTER 500-600V 3AC 9.0 / 6.1 A (40 / 50 DEG C) FOOTPRINT FSC 382 X 185 X 140 (H X W X D)	4	2
6SE6400-4BC11-2BA0	SIEMENS	MICROMASTER	MICROMASTER 4 BRAKING RESISTOR 200-240 V 68R 2400 W PK 120 W CONT 239 X 149 X 43.5 MM H X W X D IP20	1	0
6SE6400-4BE14-5CA0	SIEMENS	MICROMASTER	MICROMASTER 4 BRAKING RESISTOR 500-600 V 120R 9000 W PK 450 W CONT 285 X 185 X 150 MM H X W X D IP20	1	0
6SE6400-4BE24-2FA0	SIEMENS	MICROMASTER	MICROMASTER 4 BRAKING RESISTOR 500-600 V 12R 84000 W PK 4200 W CONT 650 X 400 X 315 MM H X W X D IP20	0	1
6SE6401-0WM00-0AA0	SIEMENS	MICROMASTER	MICROMASTER 4 INVERTER WALL MOUNT KIT FOR MM411 75 X 182 X 140 (H X W X D) IP66	2	0
6SE6410-2UA11-2AA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITHOUT FILTER 1AC 100-120 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.12 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.12 KW 150 X 69 X 118 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	0	1

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6410-2UB15-5BA0	SIEMENS	MICROMASTER	MICROMASTER 410 WITHOUT FILTER 1AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% FOR 60 S SQUARED TORQUE POWER 0.55 KW 150 X 69 X 138 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT OP	1	5
6SE6411-6AD23-0WS8	SIEMENS	MICROMASTER	MICROMASTER 411 ECOFAST WITH BUILT IN FILTER CLASS A WITH PROFIBUS-MODULE LEFT AND REM MODULE RIGHT 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 247 X 279 X 360 (H X L X W) PROTECTION IP65	0	1
6SE6420-2AB11-2AA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.12 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.12 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	2
6SE6420-2AB23-0CA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 1AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	1	0
6SE6420-2AC23-0CA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 3 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	1	1
6SE6420-2AC24-0CA1	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 4 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	1	1
6SE6420-2AC25-5CA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 5.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	3	0
6SE6420-2AD22-2BA0	SIEMENS	MICROMASTER	MICROMASTER 420 WITH BUILT IN CLASS A FILTER 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2UC12-5AA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V 10/-10% 47-63HZ CONSTANT TORQUE POWER 0.25 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 0.25 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6420-2UC22-2BA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C W/O AOP/BOP	0	1
6SE6420-2UD21-1AA0	SIEMENS	MICROMASTER	MICROMASTER 420 UNFILTERED 3AC 380-480V 10/-10% 47-63HZ CONSTANT TORQUE POWER 1.1 KW OVERLOAD 150% FOR 60S VARIABLE TORQUE POWER 1.1 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C W/O AOP/BOP	0	1
6SE6440-2AB11-2AA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.12 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.12 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AO	0	1
6SE6440-2AB11-2AA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.12 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.12 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT	3	10
6SE6440-2AB17-5AA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 0.75 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.75 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT AOP/	0	1

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6440-2AB22-2BA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 1AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP	0	1
6SE6440-2AC23-0CA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 4 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT AOP/BOP,	1	0
6SE6440-2AC25-5CA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 200-240 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 5.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 7.5 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT AOP/B	1	0
6SE6440-2AD22-2BA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 2.2 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 2.2 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AO	0	2
6SE6440-2AD23-0BA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 3 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT AOP/BO	0	1
6SE6440-2AD24-0BA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 4 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BO	0	5
6SE6440-2AD31-8DA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 18.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 22 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AO	0	1
6SE6440-2AD33-7EA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITH BUILT-IN CLASS A FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 37 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 45 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/	0	2
6SE6440-2UC15-5AA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 0.55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 0.55 KW 173 X 73 X 149 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UC23-0CA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 1/3AC 200-240V +10/-10% 47-63HZ CONSTANT TORQUE POWER 3 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 3 KW 245 X 185 X 195 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UC31-1DA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 11 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 15 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UC31-8EA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 18.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 22 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UC31-8EA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 200-240 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 18.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 22 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD24-0BA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 4 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 4 KW 202 X 149 X 172 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT AOP/BOP	0	2

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6440-2UD31-5DA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 15 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 18.5 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD31-8DA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 18.5 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 22 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD32-2DA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V 10/-10% 47-63 HZ CONSTANT TORQUE POWER 22 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 30 KW 520 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO 50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD33-7EA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 37 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 45 KW 650 X 275 X 245 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UD35-5FA0	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 380-480 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 75 KW 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE6440-2UE35-5FA1	SIEMENS	MICROMASTER	MICROMASTER 440 WITHOUT FILTER 3AC 500-600 V +10/-10% 47-63 HZ CONSTANT TORQUE POWER 55 KW OVERLOAD 150% 60 S, 200% 3 S SQUARED TORQUE POWER 75 KW 850 X 350 X 320 (H X W X D) PROTECTION IP20 AMBIENT TEMP. -10 TO +50 DEG. C WITHOUT AOP/BOP	0	1
6SE9111-4JA13	SIEMENS	MICROMASTER	MICROMASTER JUNIOR MMJ55/3 550W WITHOUT FILTER 400-460V 3AC	1	0
6SE9216-8BB40	SIEMENS	MICROMASTER	MICROMASTER MM150 WITH BUILT IN CLASS A FILTER 1AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 1.5 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	9
6SE9221-3CC40	SIEMENS	MICROMASTER	MICROMASTER MM300/2 UNFILTERED 1AC/3AC 208-240V +/-10% 50/60HZ CONSTANT TORQUE: 3.0 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 215 X 185 X 195 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	2	0
6SE9515-5CB40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-110/2 UNFILTERED 3AC 208-240V +/-10% 47-63HZ VARIABLE TORQUE:1.1KW 184 X 149 X 172 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	1	1
6SE9517-7DB40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-300/3 UNFILTERED 3AC 380-500V +/-10% 47-63HZ VARIABLE TORQUE:3.0KW 184 X 149 X 172 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE9521-0CC40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-220/2 UNFILTERED 3AC 208-240V +/-10% 47-63HZ VARIABLE TORQUE:2.2KW 215 X 185 X 195 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE9611-8DF50	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI75/3 WITH BUILT IN FILTER CLASS A 3AC 380-480V +/-10% 47-63HZ CONSTANT TORQUE:0.75KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 0.75KW 105 X 120 X 160 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	1
6SE9613-7DD50	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI150/3 WITH BUILT IN FILTER CLASS A 3AC 380-480V +/-10% 47-63HZ CONSTANT TORQUE:1.5KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 1.5KW 128 X 171 X 243 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	1
6SE9615-8DD10ZC87	SIEMENS	MICROMASTER	MICROMASTER MI220/3 2,2KW	2	0
6SE9621-7DD50	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI750/3 WITH BUILT IN FILTER CLASS A 3AC 380-480V +/-10% 47-63HZ CONSTANT TORQUE:7.5KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 7.5KW 128 X 171 X 243 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	1
6SE9996-0XA51	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED AND COMBIMASTER OPTION MOTOR INTERFACE PLATE FOR CSA INVERTER WITH 1LA7 FRAME 56-71 MOTOR	1	0

numer artykułu	Producent	rodzina	opis	nowe	odnowione
6SE6436-5BD33-7EA0	SIEMENS	MICROMASTER	MICROMASTER 436,37KW,CLASS B,IP54	0	1
6SE9615-8DD10-Z	SIEMENS	MICROMASTER	MICROMASTER INTEGRATED MI220/3 UNFILTERED 3AC 380-500V +/-10% 47-63HZ CONSTANT TORQUE:2.2KW OVERLOAD 150% 60 SEC VARIABLE TORQUE: 2.2KW 128 X 171 X 243 MM PROTECTION DEGREE: IP65 OPERATING TEMPERATURE -10 TO +50 C	0	1
A5E00155591	SIEMENS	MICROMASTER	MICROMASTER 4 GWE:A5E00155591 FILTER_FUNKENT_B84143_480V_64A CLASS A 7.7 X 2.3 X 1.1	1	0
6SE9521-7DC40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-750/3 UNFILTERED 3AC 380-500V +/-10% 47-63HZ VARIABLE TORQUE:7.5KW 215 X 185 X 195 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE9516-0DB40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-220/3 UNFILTERED 3AC 380-500V +/-10% 47-63HZ VARIABLE TORQUE:2.2KW 184 X 149 X 172 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE9521-3DC40	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-550/3 UNFILTERED 3AC 380-500V +/-10% 47-63HZ VARIABLE TORQUE:5.5KW 215 X 185 X 195 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE6436-5BD23-0BA0	SIEMENS	MICROMASTER	MICROMASTER 436,3KW,CLASS B,IP54	2	1
A5E00684817	SIEMENS	MICROMASTER	DRIVE VARIABLE FREQUENCY I/O BOARD CONTROL	0	1
6SE6436-5BD27-5CA0	SIEMENS	MICROMASTER	MICROMASTER 436,7.5KW,CLASS B,IP54	0	2
6SE9217-3DB50	SIEMENS	MICROMASTER	MICROMASTER MM300/3F WITH BUILT IN CLASS A FILTER 3AC 380/480V +/-10% 50/60HZ CONSTANT TORQUE: 3.0 KW OVERLOAD 150% 60SEC VARIABLE TORQUE: N/A 184 X 149 X 172 MM (H X W X D) PROTECTION IP20 AMBIENT TEMPERATURE 0-50 DEG C	0	1
6SE9521-0DC50	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-400/3 WITH BUILT IN FILTER CLASS A 3AC 380-480V +/-10% 47-63HZ VARIABLE TORQUE:4,0KW 215 X 185 X 195 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE9517-7DB50	SIEMENS	MICROMASTER	MICROMASTER ECO IP20 ECO1-300/3 WITH BUILT IN FILTER CLASS A 3AC 380-480V +/-10% 47-63HZ VARIABLE TORQUE:3,0KW 184 X 149 X 172 MM (H X W X D) OPERATING TEMPERATURE 0 TO +50 C	0	1
6SE3114-0DC70-4AA0	SIEMENS	MICROMASTER	MICROMASTER INVERTER DRIVE	0	1
6SE6436-5BD21-1BA0	SIEMENS	MICROMASTER	MICROMASTER 436,1.1KW,CLASS B,IP54	8	0
6SE6436-2UD38-8FA0	SIEMENS	MICROMASTER	MICROMASTER 436,45KW,INDUSTRIAL,IP20	0	1