

SIMATIC S7, Y-COUPLER FOR BUILDING UP A Y-LINK FOR REDUNDANT CONTROLLERS



Figure similar

General information	
Requirements for DP master system	
• Length of parameter assignment telegram	244 byte
Supply voltage	
Design of the power supply	via bus module
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Interfaces	
PROFIBUS DP	
Properties of the lower-level DP master system	
— Transmission rate, max.	12 Mbit/s; 45.45 kbit/s to 12 Mbit/s
— Termination of lower-level DP master system	Active terminating resistor (Bus Terminator)
— Use of OLM/OBT	Yes
— Use of RS 485 repeaters, max.	9
— Number of DP slaves, max.	31; 64 when using RS 485 repeaters or OLM/OBT

Protocols

PROFIBUS DP	Yes
-------------	-----

Interrupts/diagnostics/status information

Status indicator	No
------------------	----

Alarms	No
--------	----

Diagnostic functions	Yes
----------------------	-----

Potential separation

to lower-level DP master system	Yes
---------------------------------	-----

Dimensions

Width	40 mm
-------	-------

Height	125 mm
--------	--------

Depth	130 mm
-------	--------

Weights

Weight, approx.	200 g
-----------------	-------

last modified:	03/17/2017
-----------------------	------------