

*** SPARE PART*** SIMATIC S7, DIGITAL INPUT SM 326, 8 DI; DC 24V, NAMUR, FAILSAFE NAMUR INPUTS FOR SIMATIC S7F SYSTEMS, UP TO CATEGORY 4 (EN954-1)/ SIL3 (IEC61508)/PLE (ISO13849), 1 X 40 PIN



Figure similar

Supply voltage	
Rated value (DC)	24 V
Input current	
from load voltage L+ (without load), max.	160 mA
from backplane bus 5 V DC, max.	90 mA
Encoder supply	
Number of outputs	8
Type of output voltage	8.2 V DC
Power loss	
Power loss, typ.	4.5 W
Digital inputs	
Number of digital inputs	8; 8 (one-channel); 4 (two-channel)
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8; vertical setup
— up to 60 °C, max.	8; horizontal set up

Input voltage	
• Type of input voltage	DC
• Rated value (DC)	in accordance with DIN 19234 or NAMUR
Input current	
• for signal "0", max. (permissible quiescent current)	0.35 to 1.2 mA
• for signal "1", typ.	2.1 to 7 mA
Input delay (for rated value of input voltage)	
for NAMUR inputs	
— at "0" to "1", max.	1.2 to 3 ms
— at "1" to "0", max.	1.2 to 3 ms
Cable length	
• shielded, max.	200 m
• unshielded, max.	100 m
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Fail-safe operation	Yes
• Group error SF (red)	Yes
Ex(i) characteristics	
Module for Ex(i) protection	Yes
Maximum values of input circuits (per channel)	
• Co (permissible external capacity), max.	3 µF
• Io (short-circuit current), max.	13.9 mA
• Lo (permissible external inductivity), max.	80 mH
• Po (power of load), max.	33.1 mW
• Uo (output no-load voltage), max.	10 V
• Um (fault voltage), max.	60 V DC/30 V AC
• Ta (permissible ambient temperature), max.	60 °C
Potential separation	
Potential separation digital inputs	
• between the channels	Yes
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	500 V DC
tested with	

- Channels against backplane bus and load voltage L+
- Channels among one another
- Load voltage L+ against backplane bus

1500 V AC
 1500 V AC
 500 V DC/350 V AC

Standards, approvals, certificates

Highest safety class achievable in safety mode

- acc. to DIN VDE 0801 AK 4 (one channel), AK 5 und 6 (two channel)
- acc. to EN 954 4
- SIL acc. to IEC 61508 SIL 2 (single-channel), SIL 3 (two-channel)

Use in hazardous areas

- Test number KEMA 99 ATEX 2671 X

Connection method

required front connector 40-pin

Dimensions

Width 80 mm
 Height 125 mm
 Depth 120 mm

Weights

Weight, approx. 482 g

last modified: 03/24/2017