

SIMATIC S7-300, CP 340 COMMUNICATION PROCESSOR WITH  
RS232C INTERFACE (V.24) INCL. CONFIG. PACKAGE ON CD

### Input current

from backplane bus 5 V DC, max.	165 mA
---------------------------------	--------

### Power loss

Power loss, max.	0.85 W
------------------	--------

### Interfaces

Interfaces/bus type	RS 232C (V.24)
---------------------	----------------

Number of interfaces	1; Isolated
----------------------	-------------

Transmission rate, min.	2.4 kbit/s
-------------------------	------------

Transmission rate, max.	19.2 kbit/s
-------------------------	-------------

### Point-to-point connection

- |                      |   |
|----------------------|---|
| • Cable length, max. | 15 m  |
| • supported printers | HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined |

### Telegram length, max.

- |            |            |
|------------|------------|
| — 3964 (R) | 1 024 byte |
| — ASCII    | 1 024 byte |

### Transmission speed, RS 232

- |                                |             |
|--------------------------------|-------------|
| — with 3964 (R) protocol, max. | 19.2 kbit/s |
| — with ASCII protocol, max.    | 9.6 kbit/s  |
| — with printer driver, max.    | 9.6 kbit/s  |

### Software

#### Block

- |                          |   |
|--------------------------|---|
| • FB length in RAM, max. | 2 700 byte; Data communication, sending and receiving |
|--------------------------|---|

### Dimensions

Width	40 mm
-------	-------

Height	125 mm
--------	--------

Depth	120 mm
-------	--------

### Weights

Weight, approx.	300 g
-----------------	-------

<b>last modified:</b>	02/24/2020
-----------------------	------------