

SITOP MODULAR 24 V/20 A, VARNISHED PCB  
 SITOP modular plus 20 A stabilized power supply input: 400-500 V  
 3AC output: 24 V DC/20 A version with coated PCB



Figure similar

| Input  |                                   |
|--|-----------------------------------|
| Input  | 3-phase AC                        |
| Rated voltage value $V_{in}$ rated   | 400 ... 500 V                     |
| Voltage range AC   | 320 ... 550 V                     |
| <ul style="list-style-type: none"> <li>Note</li> </ul>   | Starting from $V_{in} > 340$ V    |
| Wide-range input   | Yes                               |
| Oversvoltage resistance  | $2.3 \times V_{in}$ rated, 1.3 ms |
| Mains buffering at $I_{out}$ rated, min.   | 6 ms; at $V_{in} = 400$ V         |
| Rated line frequency 1   | 50 Hz                             |
| Rated line frequency 2   | 60 Hz                             |
| Rated line range   | 47 ... 63 Hz                      |
| Input current  |                                   |
| <ul style="list-style-type: none"> <li>at rated input voltage 400 V</li> <li>at rated input voltage 500 V</li> </ul> | 1.1 A<br>0.9 A                    |
| Switch-on current limiting (+25 °C), max.  | 35 A                              |
| $I^2t$ , max.  | 0.7 A <sup>2</sup> ·s             |
| Built-in incoming fuse   | none                              |

|   |   |
|---|---|
| Protection in the mains power input (IEC 898) | Required: 3-pole connected miniature circuit breaker 6 ... 16 A characteristic C or circuit breaker 3RV2011-1DA10 (setting 3 A) or 3RV2711-1DD10 (UL 489) |
|---|---|

## Output

|   |                                      |
|---|--------------------------------------|
| Output  | Controlled, isolated DC voltage      |
| Rated voltage Vout DC   | 24 V                                 |
| Total tolerance, static ±                                     | 3 %                                  |
| Static mains compensation, approx.                            | 0.1 %                                |
| Static load balancing, approx.                                | 0.2 %                                |
| Residual ripple peak-peak, max.                               | 100 mV                               |
| Spikes peak-peak, max. (bandwidth: 20 MHz)                    | 200 mV                               |
| Adjustment range  | 24 ... 28.8 V                        |
| Product function Output voltage adjustable                    | Yes                                  |
| Output voltage setting  | via potentiometer; max. 480 W        |
| Status display  | Green LED for 24 V OK                |
| Signaling   | via signaling module (6EP1961-3BA10) |
| On/off behavior   | No overshoot of Vout (soft start)    |
| Startup delay, max.   | 2.5 s                                |
| Voltage increase time of the output voltage maximum           | 500 ms                               |
| Rated current value Iout rated                                | 20 A                                 |
| Current range   | 0 ... 20 A                           |
| • Note  | +60 ... +70 °C: Derating 2%/K        |
| Supplied active power typical                                 | 480 W                                |
| Short-term overload current                                   |                                      |
| • at short-circuit during operation typical                   | 60 A                                 |
| Duration of overloading capability for excess current         |                                      |
| • at short-circuit during operation                           | 25 ms                                |
| Constant overload current                                     |                                      |
| • on short-circuiting during the start-up typical             | 23 A                                 |
| Parallel switching for enhanced performance                   | Yes; switchable characteristic       |
| Numbers of parallel switchable units for enhanced performance | 2                                    |

## Efficiency

|   |      |
|---|------|
| Efficiency at Vout rated, Iout rated, approx. | 90 % |
| Power loss at Vout rated, Iout rated, approx. | 53 W |

## Closed-loop control

|   |       |
|---|-------|
| Dynamic mains compensation (Vin rated ±15 %), max.      | 1 %   |
| Dynamic load smoothing (Iout: 50/100/50 %), Uout ± typ. | 2 %   |
| Load step setting time 50 to 100%, typ.                 | 4 ms  |
| Load step setting time 100 to 50%, typ.                 | 4 ms  |
| Setting time maximum                                    | 10 ms |

| Protection and monitoring  |  |
|--|--|
| Output overvoltage protection  | < 35 V   |
| Current limitation, typ.   | 23 A   |
| Property of the output Short-circuit proof   | Yes  |
| Short-circuit protection   | Alternatively, constant current characteristic approx. 23 A or latching shutdown |
| Enduring short circuit current RMS value <ul style="list-style-type: none"> <li>• typical</li> </ul> | 23 A   |
| Overload/short-circuit indicator   | LED yellow for "overload", LED red for "latching shutdown"                       |

| Safety  |  |
|---|--|
| Primary/secondary isolation   | Yes  |
| Galvanic isolation  | Safety extra-low output voltage U <sub>out</sub> acc. to EN 60950-1 and EN 50178 |
| Protection class  | Class I  |
| Leakage current <ul style="list-style-type: none"> <li>• maximum</li> </ul> | 3.5 mA   |
| CE mark   | Yes  |
| UL/cUL (CSA) approval   | UL-Listed (UL 508), File E197259, CSA (CSA C22.2 No. 14, CSA C22.2 No. 107.1)    |
| Explosion protection  | -  |
| FM approval   | -  |
| CB approval   | No   |
| Marine approval   | -  |
| Degree of protection (EN 60529)   | IP20   |

| EMC                         |                  |
|-----------------------------|------------------|
| Emitted interference        | EN 55022 Class B |
| Supply harmonics limitation | EN 61000-3-2     |
| Noise immunity              | EN 61000-6-2     |

| Operating data   |  |
|--|--|
| Ambient temperature <ul style="list-style-type: none"> <li>• during operation</li> <li>— Note</li> <li>• during transport</li> <li>• during storage</li> </ul> | 0 ... 70 °C<br>with natural convection<br>-40 ... +85 °C<br>-40 ... +85 °C |
| Humidity class according to EN 60721   | Climate class 3K3, no condensation   |

| Mechanics  |  |
|--|--|
| Connection technology  | screw-type terminals   |
| Connections <ul style="list-style-type: none"> <li>• Supply input</li> <li>• Output</li> </ul> | L1, L2, L3, PE: 1 screw terminal each for 0.2 ... 4 mm <sup>2</sup> single-core/finely stranded<br>+, -: 2 screw terminals each for 0.33 ... 4 mm <sup>2</sup> |

|  |   |
|--|---|
| • Auxiliary  | -   |
| Width of the enclosure   | 160 mm  |
| Height of the enclosure  | 125 mm  |
| Depth of the enclosure   | 125 mm  |
| Required spacing   |   |
| • top  | 50 mm   |
| • bottom   | 50 mm   |
| • left   | 0 mm  |
| • right  | 0 mm  |
| Weight, approx.  | 2 kg  |
| Product feature of the enclosure housing for side-by-side mounting | Yes   |
| Installation   | Snaps onto DIN rail EN 60715 35x7.5/15  |
| Electrical accessories   | Buffer module, signaling module   |
| MTBF at 40 °C  | 711 213 h   |
| Other information  | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |