

MICROMASTER 4 COMMUTATING CHOKE 380-600 V 3AC 86,9A
FOOTPRINT FSE - 0.22 MH



Figure similar

Order number	
Phase number / of the input voltage	3
Type of voltage / of the input voltage	AC
Input voltage	380 ... 600
Output current / rated value	86.9 A
Power loss [W]	
• at 50 Hz	Wert fehlt!
• at 60 Hz	Wert fehlt!
Type of electrical connection	
• for mains supply line	screw-type terminal
• for load-side outgoing feeder	Pigtail
Type of connectable conductor cross-section / for load-side outgoing feeder	Wert fehlt!
Connectable conductor cross-section	
• for mains supply line	Wert fehlt!
• for load-side outgoing feeder	35 mm ²
Wire length / of connecting cable / for load-side outgoing feeder	0.79 m

Type of electrical connection / for PE conductor	M8 stud
Protection class IP	IP20
Width	275 mm
Height	650 mm
Depth	93.5 mm
Net weight	19 kg
Certificate of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Catag/Product/6SE6400-3CC08-3ED0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE6400-3CC08-3ED0/all>