

MICROMASTER 4 COMMUTATING CHOKE 200-480 V 3AC 53,6A
FOOTPRINT FSD - 0.29 MH



Order number	6SE6400-3CC05-2DD0
Number of phases / of input voltage	3
Type of / input voltage	AC
Input voltage	200 ... 480
Output current / rated value	53.6 A
Effective power loss	92 W
<ul style="list-style-type: none"> • at 50 Hz • Design of electrical connection / for mains supply line • Design of the electrical connection / for motor outgoing line 	Screw-type terminals
Connectable conductor cross-section	Cable
<ul style="list-style-type: none"> • for line supply conductor 	16 mm ²
Design of electrical connection / for PE conductor	M8 stud bolt
Protection class IP	IP20
Width	275 mm
Height	520 mm
Depth	85 mm
Net weight	9.5 kg
Verification of suitability	cURus

Further information

Information und Download Center

https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx

Technical documentation

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

Industry Mall

<https://eb.automation.siemens.com/mall/en/WW/Cataog/Product/6SE64003CC052DD0/all>

Industry Online Support

<http://support.automation.siemens.com/WW/view/en/6SE64003CC052DD0/all>