

SPARE PART SIPLUS S7-200 CPU221 -25...+70 DGR C
 BASED ON 6ES7211-0AA23-0XB0 DC / 6DI / 4DO



Figure similar

Supply voltage	
Rated value (DC)	
<ul style="list-style-type: none"> • 24 V DC 	Yes
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V
<ul style="list-style-type: none"> • permissible range, lower limit (DC) 	20.4 V
<ul style="list-style-type: none"> • permissible range, upper limit (DC) 	28.8 V
Input current	
Inrush current, max.	10 A; at 28.8 V
from supply voltage L+, max.	450 mA; 80 to 450 mA
Encoder supply	
24 V encoder supply	
<ul style="list-style-type: none"> • 24 V 	Yes; permissible range: 15.4 to 28.8 V
<ul style="list-style-type: none"> • Short-circuit protection 	Yes; electronic at 600 mA
<ul style="list-style-type: none"> • Output current, max. 	180 mA
Memory	

Number of memory modules (optional)	1; pluggable memory module, content identical with integral EEPROM; can additionally store recipes, data logs and other files
Work memory	
• integrated (for program)	4 kbyte
• integrated (for data)	2 kbyte
Backup	
• present	Yes; Program: Entire program maintenance-free on integral EEPROM, programmable via CPU; data: Entire DB 1 loaded from PG/PC maintenance-free on integral EEPROM, current values of DB 1 in RAM, retentive memory bits, timers, counters, etc. maintenance-free via high-performance capacitor; optional battery for long-term buffering
Battery	
Backup battery	
• Backup time, max.	50 h; (min. 8 h at 40 °C); 200 days (typ.) with optional battery module
CPU processing times	
for bit operations, max.	0.22 µs
Counters, timers and their retentivity	
S7 counter	
• Number	256
of which retentive with battery	
— can be set	Yes; via high-performance capacitor or battery
— lower limit	1
— upper limit	256
Counting range	
— lower limit	0
— upper limit	32 767
S7 times	
• Number	256
of which retentive with battery	
— adjustable	Yes; via high-performance capacitor or battery
— upper limit	64
Time range	
— lower limit	1 ms
— upper limit	54 min; 4 timers: 1 ms to 30 s; 16 timers: 10 ms to 5 min; 236 timers: 100 ms to 54 min
Data areas and their retentivity	
Flag	
• Number, max.	32 byte
• Retentivity available	Yes; M 0.0 to M 31.7
• of which retentive with battery	0 to 255, via high-performance capacitor or battery, adjustable

- of which retentive without battery

0 to 112 in EEPROM, adjustable

Hardware configuration

connectable programming devices/PCs

SIMATIC PG/PC, standard PC

Digital inputs

Number of digital inputs

6; Integrated

Source/sink input

Yes; optionally, per group

Input voltage

- Rated value (DC)
- for signal "0"
- for signal "1"

24 V

0 to 5 V

min. 15 V

Input current

- for signal "1", typ.

2.5 mA

Input delay (for rated value of input voltage)

for standard inputs

- parameterizable
- at "0" to "1", min.
- at "0" to "1", max.

Yes; all

0.2 ms

12.8 ms

for interrupt inputs

- parameterizable

Yes; I 0.0 to I 0.3

for counter/technological functions

- parameterizable

Yes; (E 0.0 to E 0.5) 30 kHz

Cable length

- shielded, max.
- unshielded, max.

500 m; Standard input: 500 m, high-speed counters: 50 m

300 m; not for high-speed signals

Digital outputs

Number of digital outputs

4; Transistor

Short-circuit protection

No; to be provided externally

Limitation of inductive shutdown voltage to

1 W

Switching capacity of the outputs

- with resistive load, max.
- on lamp load, max.

0.75 A

5 W

Output voltage

- for signal "1", min.

20 V DC

Output current

- for signal "1" rated value
- for signal "0" residual current, max.

750 mA

0.1 mA

Output delay with resistive load

- "0" to "1", max.
- "1" to "0", max.

15 μ s; of the standard outputs, max. (Q0.2 to Q0.3) 15 μ s; of the pulse outputs, max. (Q0.0 to Q0.1) 2 μ s

130 μ s; of the standard outputs, max. (Q0.2 to Q0.3) 100 μ s; of the pulse outputs, max. (Q0.0 to Q0.1) 10 μ s

Parallel switching of two outputs	
• for uprating	Yes
Switching frequency	
• of the pulse outputs, with resistive load, max.	20 kHz; Q0.0 to Q0.1
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	3 A
horizontal installation	
— up to 55 °C, max.	3 A
Relay outputs	
• Number of relay outputs, integrated	0
Cable length	
• shielded, max.	500 m
• unshielded, max.	150 m
Analog inputs	
Number of analog potentiometers	1; Analog potentiometer; resolution 8 bit
Encoder	
Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
1. Interface	
Interface type	Integrated RS 485 interface
Physics	RS 485
Functionality	
• MPI	Yes; As MPI slave for data exchange with MPI masters (S7-300/S7-400 CPUs, OPs, TDs, Push Button Panels); S7-200-internal CPU/CPU communication is possible in the MPI network with restrictions; transmission rates: 19.2/187.5 kbit/s
• PPI	Yes; with PPI protocol for program functions, HMI functions (TD 200, OP), S7-200-internal CPU/CPU communication ; transmission rates 9.6/19.2/187.5 kbit/s
• serial data exchange	Yes; As freely programmable interface with interrupt facility for serial data exchange with third-party devices with ASCII protocol transfer rates: 1.2 / 2.4 / 4.8 / 9.6 / 19.2 / 38.4 / 57.6 / 115.2 kbps; the PC/PPI cable can also be used as RS 232/RS 485 converter
MPI	
• Transmission rate, min.	19.2 kbit/s
• Transmission rate, max.	187.5 kbit/s
Integrated Functions	

Number of counters	4; High-speed counters (30 kHz each), 32 bits (incl. sign), can be used as up/down counters or for connecting 2 incremental encoders with 2 pulse trains offset by 90° (max. 20 kHz (A/B counters)); parameterizable enable and reset input; interrupt facilities (incl. call of subroutine with any content) when the setpoint is reached; reversal in counting direction, etc.
Counting frequency (counter) max.	30 kHz
Number of alarm inputs	4; 4 rising edges and/or 4 falling edges
Number of pulse outputs	2; High-speed outputs, 20 kHz, with interrupt option; pulse-width and frequency modulation option
Limit frequency (pulse)	20 kHz

Potential separation

Potential separation digital inputs	
• between the channels	Yes
• between the channels, in groups of	2 and 4
Potential separation digital outputs	
• between the channels	Yes; Optocoupler
• between the channels, in groups of	4

Permissible potential difference

between different circuits	500 V DC between 24 V DC and 5 V DC
----------------------------	-------------------------------------

Degree and class of protection

Degree of protection acc. to EN 60529	
• IP20	Yes

Ambient conditions

Ambient temperature during operation	
• horizontal installation, min.	-25 °C; = Tmin
• horizontal installation, max.	70 °C; = Tmax
• vertical installation, min.	-25 °C; = Tmin
• vertical installation, max.	45 °C; = Tmax

Extended ambient conditions

• relative to ambient temperature-atmospheric pressure-installation altitude	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
--	---

Relative humidity

— With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
---	---

Resistance

— against biologically active substances / conformity with EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— against chemically active substances / conformity with EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!

— against mechanically active substances /
conformity with EN 60721-3-3

Yes; Class 3S4 incl. sand, dust. The supplied connector covers
must remain on the unused interfaces during operation!

Configuration

Programming

- | | |
|--|--|
| <ul style="list-style-type: none">• Command set
• Program processing
• Program organization
• Number of subroutines, max. | Bit logic instructions, compare instructions, timer instructions, counter instructions, clock instructions, transmissions instructions, table instructions, logic instructions, shift and rotate instructions, conversion instructions, program control instructions, interrupt and communications instructions, logic stack instructions, integer maths, floating-point math instructions, numerical functions

free cycle (OB 1), interrupt-controller, time-controlled (1 to 255 ms)

1 OB, 1 DB, 1 SDB subroutines with/without parameter transfer

64 |
|--|--|

Programming language

- | | |
|---|-------------------|
| <ul style="list-style-type: none">— LAD— FBD— STL | Yes
Yes
Yes |
|---|-------------------|

Know-how protection

- | | |
|---|----------------------------------|
| <ul style="list-style-type: none">• User program protection/password protection | Yes; 3-stage password protection |
|---|----------------------------------|

Connection method

- | | |
|-----------------------|----|
| Plug-in I/O terminals | No |
|-----------------------|----|

Dimensions

- | | |
|--------|-------|
| Width | 90 mm |
| Height | 80 mm |
| Depth | 62 mm |

Weights

- | | |
|-----------------|-------|
| Weight, approx. | 270 g |
|-----------------|-------|

last modified: 05/31/2017