

Product type designation

CP 343-1 Advanced

SIMATIC NET, CP 343-1 ADVANCED COMMUNICATION PROCESSOR FOR CONNECTING SIMATIC S7-300 TO IND. ETHERNET VIA PROFINET-IO CONTROLLER, PROFINET CBA,ISO, TCP/IP AND UDP, S7-KOMM., FETCH/WRITE, SEND/RECEIVE, WITH AND W/O RFC1006, HTTP W JAVA, MULTICAST, LOAD. COMM. BLOCKS, HTML DIAGN.,FTP CLIENT/SERVER E-MAIL, SNMP, DHCP, NTP-CPU SYNC, 10/100 MBIT, ONLY RJ45 PORT



Transmission rate

Transfer rate

- at the 1st interface

10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

1

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet
- for power supply

1

1

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet
- of Industrial Ethernet interface
- for power supply

RJ45 port

RJ45 port

2-pole plugable terminal block

design of the removable storage / C-PLUG

Yes

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage

24 V

Supply voltage / external	24 V
Supply voltage / external / at DC / Rated value	24 V
Relative positive tolerance / at DC / at 24 V	20 %
Relative negative tolerance / at DC / at 24 V	15 %
Consumed current	
• from backplane bus / at DC / at 5 V / typical	0.14 A
Power loss [W]	14.7 W

Permitted ambient conditions

Ambient temperature	
• for vertical installation / during operation	0 ... 40 °C
• for horizontally arranged busbars / during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 double width
Width	80 mm
Height	125 mm
Depth	120 mm
Net weight	0.8 kg
Mounting type	
• S7-300 rail mounting	Yes

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
Amount of data	
• as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
• as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	2 Kibyte
Number of Multicast stations	16

Performance data / S7 communication	
Number of possible connections / for S7 communication	
<ul style="list-style-type: none"> • maximum 	16
Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	48
Performance data / IT functions	
Number of possible connections	
<ul style="list-style-type: none"> • as client / by means of FTP / maximum 	10
<ul style="list-style-type: none"> • as server / by means of FTP / maximum 	2
<ul style="list-style-type: none"> • as server / by means of HTTP / maximum 	4
<ul style="list-style-type: none"> • as e-mail client / maximum 	1
Amount of data / as user data for email / maximum	8 Kibyte
Storage capacity / of the user memory	
<ul style="list-style-type: none"> • as flash memory file system 	28 Miabyte
<ul style="list-style-type: none"> • as RAM 	30 Miabyte
Number of possible write cycles / of the flash memory cells	100000
Performance data / PROFINET communication / as PN IO-Controller	
Number of PN IO devices / on PROFINET IO controller / usable / total	125
Number of external PN IO lines / with PROFINET / per rack	1
Amount of data	
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	4 Kibyte
<ul style="list-style-type: none"> • as user data for input variables / as PROFINET IO controller / maximum 	4 Kibyte
<ul style="list-style-type: none"> • as user data for input variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
<ul style="list-style-type: none"> • as user data for output variables per PN IO device / as PROFINET IO controller / maximum 	1433 byte
Performance data / PROFINET CBA	
Number of remote connection partners / with PROFINET CBA	64
Number of connections / with PROFINET CBA / total	1000
Amount of data	
<ul style="list-style-type: none"> • as user data for digital inputs / with PROFINET CBA / maximum 	8 Kibyte
<ul style="list-style-type: none"> • as user data for digital outputs / with PROFINET CBA / maximum 	8 Kibyte

- as user data for arrays and data types / in the case of acyclic transmission / with PROFINET CBA / maximum
- as user data for arrays and data types / with PROFINET CBA / with cyclical transfer / maximum
- as user data for arrays and data types / with PROFINET CBA / in the case of local interconnection / maximum

8 Kibyte

450 byte

2400 byte

Performance data / PROFINET CBA / remote connection / with acyclic transmission

Refresh time / of the remote interconnections / in the case of acyclic transmission / with PROFINET CBA	100 ms
Number of remote connections to input variables / in the case of acyclic transmission / with PROFINET CBA / maximum	128
Number of remote connections to output variables / in the case of acyclic transmission / with PROFINET CBA / maximum	128
Amount of data <ul style="list-style-type: none"> • as user data for remote interconnections with input variables / in the case of acyclic transmission / with PROFINET CBA • as user data for remote interconnections with output variables / in the case of acyclic transmission / with PROFINET CBA 	8 Kibyte 8 Kibyte

Performance data / PROFINET CBA / remote connection / with cyclic transmission

Refresh time / of the remote interconnections / with PROFINET CBA / with cyclical transfer	8 ms
Number of remote connections to input variables / with PROFINET CBA / with cyclical transfer / maximum	200
Number of remote connections to output variables / with PROFINET CBA / with cyclical transfer / maximum	200
Amount of data <ul style="list-style-type: none"> • as user data for remote interconnections with input variables / with PROFINET CBA / with cyclical transfer / maximum • as user data for remote interconnections with output variables / with PROFINET CBA / with cyclical transfer / maximum 	2000 byte 2000 byte

Performance data / PROFINET CBA / HMI variables via PROFINET / acyclic

Number of connectable HMI stations / for HMI variables / in the case of acyclic transmission / with PROFINET CBA	3
--	---

Refresh time / of the HMI variables / in the case of acyclic transmission / with PROFINET CBA	500 ms
Number of HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum	200
Amount of data / as user data for HMI variables / in the case of acyclic transmission / with PROFINET CBA / maximum	8 Kibyte

Performance data / PROFINET CBA / device-internal connections

Number of internal connections / with PROFINET CBA / maximum	256
Amount of data / of the internal connections / with PROFINET CBA / maximum	2400 byte

Performance data / PROFINET CBA / connections to constants

Number of connections with constants / with PROFINET CBA / maximum	200
Amount of data / as user data for interconnections with constants / with PROFINET CBA / maximum	4096 byte

Performance data / PROFINET CBA / PROFIBUS proxy functionality

Product function / with PROFINET CBA / PROFIBUS proxy functionality	No
---	----

Performance data / telecontrol

Protocol / is supported	
• TCP/IP	Yes
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	Yes
Configuration software	
• required	STEP 7 V5.3 SP2 or higher
• for PROFINET CBA / required	SIMATIC iMap V2.0 SP1 and higher
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes

Product functions / Diagnosis

Product function / Web-based diagnostics	Yes
--	-----

Product functions / switch

Product feature / Switch	No
--------------------------	----

Product functions / Redundancy

Product function	
------------------	--

- Ring redundancy

No

Product functions / Security

Product function

- ACL - IP-based
- ACL - IP-based for PLC/routing
- switch-off of non-required services
- Blocking of communication via physical ports
- log file for unauthorized access

Yes
No
No
No
No

Product functions / Time

Product function / SICLOCK support

Yes

Product function / pass on time synchronization

Yes

Protocol / is supported

- NTP

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

06/15/2017