

Product type designation

**PROFIBUS OLM/G12-EEC V4.0**

PB OLM/G12-EEC V4.0 OPTICAL LINK MODULE W. 1 RS485 AND 2 GLASS-FOC-INTERFACES (4 BFOC-SOCKETS) FOR EXTENDED TEMPERATURE RANGE -20..+60 DGR.



Transmission rate	
Transfer rate / with PROFIBUS	9.6 kbit/s ... 12 Mbit/s
Transfer rate / with PROFIBUS PA	45.45 kbit/s
Interfaces	
Number of electrical/optical connections / for network components or terminal equipment / maximum	3
Number of electrical connections	
<ul style="list-style-type: none"> <li>• for network components or terminal equipment</li> <li>• for measuring device</li> <li>• for signaling contact</li> <li>• for power supply</li> <li>• for redundant voltage supply</li> </ul>	<p>1</p> <p>1</p> <p>1</p> <p>1</p> <p>1</p>
Type of electrical connection	
<ul style="list-style-type: none"> <li>• for network components or terminal equipment</li> <li>• for measuring device</li> <li>• for power supply and signaling contact</li> </ul>	<p>9-pin Sub-D socket</p> <p>2-pole terminal block</p> <p>5-pole terminal block</p>
Number of optical interfaces / for fiber optic cable	2
Design of the optical interface / for fiber optic cable	BFOC port

## Optical data

Damping ratio / of the FOC transmission link	
<ul style="list-style-type: none"> <li>• for glass FOC with 50/125 <math>\mu\text{m}</math> / at 3 dB/km / maximum</li> </ul>	10 dB
<ul style="list-style-type: none"> <li>• for glass FOC with 62.5/125 <math>\mu\text{m}</math> / at 3.5 dB/km / maximum</li> </ul>	12 dB
propagation delay [bit]	6.5 bit
Connectable optical power relative to 1 mW	
<ul style="list-style-type: none"> <li>• for glass FOC with 50/125 <math>\mu\text{m}</math> / at 3 dB/km</li> </ul>	-16 dB
<ul style="list-style-type: none"> <li>• for glass FOC with 62.5/125 <math>\mu\text{m}</math> / at 3.5 dB/km</li> </ul>	-13 dB
Optical sensitivity relating to 1 mW	
<ul style="list-style-type: none"> <li>• for glass FOC with 50/125 <math>\mu\text{m}</math> / at 3 dB/km</li> </ul>	-28 dB
<ul style="list-style-type: none"> <li>• for glass FOC with 62.5/125 <math>\mu\text{m}</math> / at 3.5 dB/km</li> </ul>	-28 dB
Wavelength	
<ul style="list-style-type: none"> <li>• for glass FOC with 50/125 <math>\mu\text{m}</math> / compatible with interface / at 3 dB/km</li> </ul>	860 nm
<ul style="list-style-type: none"> <li>• for glass FOC with 62.5/125 <math>\mu\text{m}</math> / compatible with interface / at 3.5 dB/km</li> </ul>	860 nm
Wire length	
<ul style="list-style-type: none"> <li>• for glass FOC with 50/125 <math>\mu\text{m}</math> / at 3 dB/km / maximum</li> </ul>	3 km
<ul style="list-style-type: none"> <li>• for glass FOC with 62.5/125 <math>\mu\text{m}</math> / at 3.5 dB/km / maximum</li> </ul>	3 km

## Signal-Inputs/outputs

Operating voltage / of the signaling contacts / at DC / Rated value	24 V
Operating current / of the signaling contacts / at DC / maximum	0.1 A

## Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage / at DC / Rated value	24 V
Supply voltage / at DC	18.8 ... 28.8 V
Product component / fusing at power supply input	Yes
Consumed current / at DC / at 24 V / maximum	0.2 A

## Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-25 ... +60 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP40

Design, dimensions and weight	
Design	compact
Width	39.5 mm
Height	112 mm
Depth	74.5 mm
Net weight	340 g
Mounting type	
<ul style="list-style-type: none"> <li>• 35 mm DIN rail mounting</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• wall mounting</li> </ul>	Yes

Product functions / Redundancy	
Product function / Ring redundancy	Yes

Standards, specifications, approvals	
Standard	
<ul style="list-style-type: none"> <li>• for FM</li> </ul>	FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
<ul style="list-style-type: none"> <li>• for hazardous zone</li> </ul>	EN 60079-0: 2006, EN60079-15: 2005, EN60079-28: 2007, II 3 (2) G Ex nA [opis] IIC T4 KEMA 09 ATEX 0173X
<ul style="list-style-type: none"> <li>• for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 Nr. 60950-1
<ul style="list-style-type: none"> <li>• for hazardous zone / from CSA and UL</li> </ul>	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
<ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
<ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>	EN 61000-6-2
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• C-Tick</li> </ul>	Yes
Marine classification association	
<ul style="list-style-type: none"> <li>• American Bureau of Shipping Europe Ltd. (ABS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Bureau Veritas (BV)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Det Norske Veritas (DNV)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Germanische Lloyd (GL)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Lloyds Register of Shipping (LRS)</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Nippon Kaiji Kyokai (NK)</li> </ul>	Yes

Further Information / Internet Links	
Internet-Link	
<ul style="list-style-type: none"> <li>• to website: Selector SIMATIC NET SELECTION TOOL</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>

- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

## Security information

### Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

**last modified:**

06/15/2017