

Product type designation

Split Connect Terminator (non-Ex)
PROFIBUS PA SPLITCONNECT TERMINATOR, FOR
TERMINATING OF PROFIBUS PA SEGMENTS, NOT SUITABLE
FOR APPLICATION IN EX-AREA, PACK. UNIT: 5 PIECES PER
PACK



Electrical data

| | |
|----------------------------------|--------------|
| Transfer rate / with PROFIBUS PA | 31.25 kbit/s |
|----------------------------------|--------------|

Permitted ambient conditions

| | |
|---------------------|----------------|
| Ambient temperature | |
| • during operation | -40 ... +85 °C |
| • during storage | -40 ... +85 °C |
| • during transport | -40 ... +85 °C |
| Protection class IP | IP67 |

Further Information / Internet Links

Internet-Link

- | | |
|---|---|
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAx Download Manager | http://www.siemens.com/cax |

- to website: Industry Online Support

<https://support.industry.siemens.com>

last modified:

06/05/2017