

Product type designation

MDS U315 transponder

MOBY U MOBILE DATA MEMORY MDS U315, 2 KBYTE RAM,
REPLACEABLE BATTERY, IP 65, -25 TO +70 DGR/C, 111 X 67 X
23.5 MM



Wireless frequencies

Operating frequency	2400 ... 2435 MHz
---------------------	-------------------

Electrical data

Range / maximum	3 m; Range adjustable in reader in steps of 0.5 m
Protocol / with radio transmission	ISO 18000-4
Transfer rate / with radio transmission / maximum	384 kbit/s
Product feature / multitag-capable	Yes
Polarization	Circular
Product component / Backup battery	Yes
Product feature / Replaceable battery	Yes
Battery life / typical	5 y

Memory

Type of memory	RAM
Storage capacity / of the user memory	2048 byte
Type of memory organization	UID (fixed code) 4 bytes, OTP: 16 bytes, user memory 2048 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	100000000000000

Number of write cycles / at ambient temperature < 40 °C / maximum	1000000000000000
Data retention time / at ambient temperature < 40 °C / not less than	5 y

Mechanical data

Material	PA 12 GF 25
Color	anthracite
Tightening torque / of the screw for securing the equipment / maximum	0.8 N·m
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during read/write access outside the read/write area during storage 	<p>-25 ... +70 °C</p> <p>-25 ... +70 °C</p> <p>-40 ... +85 °C</p>
Protection class IP	IP65
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	500 m/s ²
Vibrational acceleration	100 m/s ²
Resistance to mechanical stress	Free fall 1 m

Design, dimensions and weight

Width	67 mm
Height	23.5 mm
Depth	111 mm
Net weight	100 g
Mounting type	4 x M4 screws

Product properties, functions, components / general

Product feature	
<ul style="list-style-type: none"> silicon-free 	Yes

Standards, specifications, approvals

Certificate of suitability	RF: EN 300440-2, SAR: EN 50371, safety: EN 60950-1, EMC: EN 301489-01, EN 301489-03, ENV 50204, FCC Part 15C (USA), cULus, safe for heart pacemakers
MTBF	285 y

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> to website: Selector SIMATIC NET SELECTION TOOL to website: Industrial communication to website: Industry Mall 	<p>https://support.industry.siemens.com/cs/ww/en/view/67384964</p> <p>http://www.siemens.com/ident/rfid</p> <p>https://mall.industry.siemens.com</p>

- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

07/03/2017