

Product type designation

Product description

Cable 24 V, M12 / M12

Sensor/actuator cable (4-core)

MOBY CONNECTING CABLE FOR WIDE RANGE POWER UNIT

6GT2494-0AA00, 6GT2898-0AA00, 6GT2898-0AA10, 6GT2898-

0AA20, 24 V DC; PUR, LENGTH: 5 M



Suitability for use	Plug-in cable for connecting a 24 V power supply to a load
Cable designation	Li9Y11Y-HF
Wire length	5 m

Electrical data

Number of electrical connections	2
Type of electrical connection	M12 (male 4 pin, straight) / M12 (female, 4 pin, straight)
Loop resistance per length / maximum	116 mΩ/m
Insulation resistance coefficient	1000 GΩ·m
Operating voltage	
• maximum	300 V

Mechanical data

Number of electrical cores	4
Design of the shield	unshielded
Outer diameter	
• of cable sheath	4.7 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.15 mm

Material	
<ul style="list-style-type: none"> • of the wire insulation • of cable sheath 	PP PUR
Color	
<ul style="list-style-type: none"> • of the insulation of data wires • of cable sheath 	brown, white, blue, black black-grey
Bending radius	
<ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible • with continuous bending 	23.5 mm 47 mm 47 mm
Number of bending cycles	4000000
Weight per length	30 kg/km

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	-25 ... +80 °C -40 ... +80 °C -40 ... +80 °C -25 ... +80 °C
Burning behavior	flame resistant according to UL-Style 20549, FT1 gem. UL 758
Chemical resistance	
<ul style="list-style-type: none"> • to mineral oil • to grease 	resistant according to DIN EN 60811-2-1 resistant according to DIN EN 60811-2-1
Radiological resistance / to UV radiation	conditional UV resistance according to DIN EN ISO 4892-2-A

Product properties, functions, components / general

Product feature	
<ul style="list-style-type: none"> • halogen-free • silicon-free 	Yes Yes

Standards, specifications, approvals

UL/ETL listing / 300 V Rating	Yes; FT1 gem. UL 758
-------------------------------	----------------------

Further Information / Internet Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support 	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified: 07/06/2017