

### Product type designation



### SIPLUS SCALANCE X204-2

SIPLUS NET SCALANCE X204-2 -40 ... +60 DEGREES C FOR MEDIAL STRESS BASED ON 6GK5204-2BB10-2AA3 . MANAGED IE SWITCH, 4 X 10/100MBIT/S RJ45 PORTS, 2 X 100MBIT/S MULTIMODE BFOC, LED DIAGNOSTICS, ERROR SIGNAL CONTACT WITH SET BUTTON, REDUNDANT POWER SUPPLY, PROFINET-IO DEVICE, NETWORK MANAGEMENT, INTEGRATED REDUNDANCY MANAGER, INCL. ELECTRONIC MANUAL ON CD, C-PLUG OPTIONAL

### Transmission rate

Transfer rate	10 Mbit/s, 100 Mbit/s
---------------	-----------------------

### Interfaces / for communication / integrated

Number of electrical connections	
• for network components or terminal equipment	4

### Interfaces / others

Number of electrical connections	
• for signaling contact	1
• for power supply	1
• for redundant voltage supply	1
Type of electrical connection	
• for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
design of the removable storage	
• C-PLUG	Yes

### Signal-Inputs/outputs

Operating voltage / of the signaling contacts	
---	--

• at DC / Rated value	24 V
Operating current / of the signaling contacts	
• at DC / maximum	0.1 A

#### Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage	DC
Supply voltage	
• external	24 V
• external	18 ... 32 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.215 A
Power loss [W]	
• at DC / at 24 V	6.36 W

#### Permitted ambient conditions

Ambient temperature	
• during operation	-40 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Relative humidity	
• at 25 °C / without condensation / during operation / maximum	100 %
• with condensation / maximum	100 %; r.F., incl. condensation/frost permitted (no commissioning in bedewed state)
Ambient condition / relating to ambient temperature - air pressure - installation altitude	-40 ... +60 °C at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // -40 ... +50 °C at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // -40 ... +40 °C at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Resistance to biologically active substances / conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, Class 3B2 mold, fungus, and sponge spores (except fauna). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to chemically active substances / conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, class 3C4 incl. salt spray according to EN 60068-2-52 (severity 3). The supplied plug covers must remain in place over the unused interfaces during operation!
Resistance to mechanically active substances / conformity acc. to EN 60721-3-3	Yes; Compliance with EN 60721-3-3, Class 3S4 including sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation!
Protection class IP	IP30

#### Design, dimensions and weight

Design	compact
Width	60 mm
Height	125 mm
Depth	124 mm
Net weight	0.78 kg

Mounting type	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	Yes

#### Product properties, functions, components / general

Cascading in the case of a redundant ring / at reconfiguration time of $\leq 0.3$ s	50
Cascading in cases of star topology	any (depending only on signal propagation time)

#### Product functions / management, configuration

Product function	
• CLI	Yes
• web-based management	Yes
• MIB support	Yes
• TRAPs via email	Yes
• Configuration with STEP 7	Yes
• SMTP server	Yes
• Port mirroring	Yes
• with IRT / PROFINET IO switch	No
• PROFINET IO diagnosis	Yes
• switch-managed	Yes
Protocol / is supported	
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• FTP	Yes
• BOOTP	No
• GMRP	No
• DCP	Yes
• LLDP	Yes
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
• IGMP (snooping/querier)	No

#### Product functions / Diagnosis

Product function	
• Port diagnostics	Yes
• Statistics Packet Size	Yes
• Statistics packet type	Yes
• Error statistics	Yes

## Product functions / DHCP

### Product function

- DHCP client

Yes

## Product functions / Redundancy

### Product function

- Ring redundancy
- High Speed Redundancy Protocol (HRP)
- high speed redundancy protocol (HRP) with redundancy manager
- high speed redundancy protocol (HRP) with standby redundancy

Yes

Yes

Yes

No

### Protocol / is supported / Media Redundancy Protocol (MRP)

Yes

### Product function

- media redundancy protocol (MRP) with redundancy manager
- Passive listening

Yes

Yes

## Product functions / Security

### Protocol / is supported

- SSH

Yes

## Product functions / Time

### Product function

- SICLOCK support

Yes

### Protocol / is supported

- NTP
- SNTP

No

Yes

## Standards, specifications, approvals

### Standard

- for hazardous zone
- for emitted interference
- for interference immunity

EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X

EN 61000-6-4 (Class A)

EN 61000-6-2

### Certificate of suitability / CE marking

Yes

### Certificate of suitability

EN 61000-6-2, EN 61000-6-4

- Railway application in accordance with EN 50155
- Railway application in accordance with EN 50124-1
- KC approval

No

No

Yes

### Marine classification association

- American Bureau of Shipping Europe Ltd. (ABS)

No

- Bureau Veritas (BV)
- Det Norske Veritas (DNV)
- Germanische Lloyd (GL)
- Lloyds Register of Shipping (LRS)
- Nippon Kaiji Kyokai (NK)
- Polski Rejestr Statkow (PRS)

No  
No  
No  
No  
No  
No

## Further Information / Internet Links

### Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>  
  
<http://www.siemens.com/simatic-net>  
<https://mall.industry.siemens.com>  
<http://www.siemens.com/industry/infocenter>  
<http://automation.siemens.com/bilddb>  
<http://www.siemens.com/cax>  
<https://support.industry.siemens.com>

## Security information

### Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

04/05/2017