

SIMATIC S7-400, CPU 414-3 768 KB WORKING MEMORY (384 KB CODE, 384 KB DATA) 1. INTERFACE MPI/DP 12 MBIT/S 2.IF PROFIBUS DP, 3.IF FOR IFM ONLY REMAINING QUANTITY AVAIL.

CiR – Configuration in RUN

CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	120 µs

Supply voltage

Rated value (DC)	
<ul style="list-style-type: none"> • 24 V DC 	Yes

Input current

from backplane bus 5 V DC, typ.	1.5 A
from backplane bus 5 V DC, max.	1.6 A; typ. 1.5 A
from backplane bus 24 V DC, max.	450 mA; Total current consumption of the components connected to the MPI/DP interfaces, but no more than 150 mA per interface

Power loss

Power loss, typ.	7.5 W
------------------	-------

Memory

Work memory	
<ul style="list-style-type: none"> • integrated 	768 kbyte
<ul style="list-style-type: none"> • integrated (for program) 	384 kbyte
<ul style="list-style-type: none"> • integrated (for data) 	384 kbyte
<ul style="list-style-type: none"> • expandable 	No
Load memory	
<ul style="list-style-type: none"> • expandable FEPRM 	Yes; with Memory Card (FLASH)
<ul style="list-style-type: none"> • expandable FEPRM, max. 	64 Mbyte
<ul style="list-style-type: none"> • integrated RAM, max. 	256 kbyte
<ul style="list-style-type: none"> • expandable RAM 	Yes; with Memory Card (RAM)
<ul style="list-style-type: none"> • expandable RAM, max. 	64 Mbyte
Backup	
<ul style="list-style-type: none"> • present 	Yes
<ul style="list-style-type: none"> • with battery 	Yes; all data
<ul style="list-style-type: none"> • without battery 	No

Battery

Backup battery	
<ul style="list-style-type: none"> • Backup current, typ. 	40 µA

- Backup current, max. 420 μ A
- Feeding of external backup voltage to CPU 5 V DC to 15 V DC

CPU processing times

for bit operations, typ.	0.1 μ s
for word operations, typ.	0.1 μ s
for fixed point arithmetic, typ.	0.1 μ s
for floating point arithmetic, typ.	0.6 μ s

CPU-blocks

DB

- Number, max. 4 095; DB 0 reserved
- Size, max. 64 kbyte

FB

- Number, max. 2 048
- Size, max. 64 kbyte

FC

- Number, max. 2 048
- Size, max. 64 kbyte

OB

- Number, max. see instruction list
- Size, max. 64 kbyte
- Number of time alarm OBs 4
- Number of delay alarm OBs 4
- Number of cyclic interrupt OBs 4
- Number of process alarm OBs 4

Nesting depth

- per priority class 24
- additional within an error OB 2

Counters, timers and their retentivity

S7 counter

- Number 256

Retentivity

- adjustable Yes
- lower limit 0
- upper limit 255
- preset Z 0 to Z 7

Counting range

- lower limit 1
- upper limit 999

IEC counter

- present Yes
- Type SFB

S7 times	
• Number	256
Retentivity	
— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	No retentivity
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
• present	Yes
• Type	SFB
Data areas and their retentivity	
retentive data area in total	Total working and load memory (with backup battery)
Flag	
• Number, max.	8 kbyte
• Retentivity available	Yes; from MB 0 to MB 8191
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Number, max.	4 096; DB 0 reserved
• Size, max.	64 kbyte
Address area	
I/O address area	
• Inputs	8 kbyte
• Outputs	8 kbyte
of which distributed	
— MPI/DP interface, inputs	2 kbyte
— MPI/DP interface, outputs	2 kbyte
— DP interface, inputs	6 kbyte
— DP interface, outputs	6 kbyte
Process image	
• Inputs, adjustable	8 kbyte; adjustable at the expense of the code area of the RAM
• Outputs, adjustable	8 kbyte; adjustable at the expense of the code area of the RAM
• Inputs, default	256 byte
• Outputs, default	256 byte
• consistent data, max.	244 byte
• Access to consistent data in process image	Yes
Subprocess images	
• Number of subprocess images, max.	8

Digital channels	
• Inputs	65 536
— of which central	65 536
• Outputs	65 536
— of which central	65 536
Analog channels	
• Inputs	4 096
— of which central	4 096
• Outputs	4 096
— of which central	4 096
Hardware configuration	
Number of expansion units, max.	21; of which 6 ER with K-bus
connectable OPs	31 without message processing, 8 with message processing
Multicomputing	Yes; 4 CPUs max. (with UR1 or UR2)
Interface modules	
• Number of connectable IMs (total), max.	6
• Number of connectable IM 460s, max.	6
• Number of connectable IM 463s, max.	4; IM 463-2
Number of DP masters	
• integrated	2
• via CP	10
• via IM 467	4
• Mixed mode IM + CP permitted	No; IM 467 cannot be used jointly with CP 443-5 Ext.
• via interface module	1
• Number of pluggable S5 modules (via adapter capsule in central device), max.	6
Number of operable FMs and CPs (recommended)	
• FM	32; Limited by number of slots and number of connections
• CP, PtP	32; limited by number of slots
• CP, LAN	32; limited by number of connections
• PROFIBUS and Ethernet CPs	14; incl. CP 443-5 Ext. and IM 467
Slots	
• required slots	2
Time of day	
Clock	
• Hardware clock (real-time)	Yes
• retentive and synchronizable	Yes
• Resolution	1 ms
Operating hours counter	
• Number	8
Clock synchronization	

• supported	Yes
• to MPI, master	Yes
• to MPI, slave	Yes
• to DP, master	Yes
• to DP, slave	Yes
• in AS, master	Yes
• in AS, slave	Yes
• to IF 964 DP	Yes; as Master or Slave

1. Interface

Physics	RS 485 / PROFIBUS
Isolated	Yes
Number of connection resources	MPI: 32, DP: 16
Functionality	
• MPI	Yes
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
MPI	
• Number of connections	32
• Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes
DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	

— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
DP slave	
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— PG/OP communication	Yes; with interface active
— Routing	Yes; with interface active
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte

2. Interface	
Physics	RS 485 / PROFIBUS
Isolated	Yes
Number of connection resources	16
Functionality	
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
DP master	
• Number of connections, max.	16
• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	96
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— Equidistance	Yes
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Direct data exchange (slave-to-slave communication)	Yes
Address area	

— Inputs, max.	6 kbyte
— Outputs, max.	6 kbyte
User data per DP slave	
— Inputs, max.	128 byte
— Outputs, max.	128 byte
DP slave	
• Transmission rate, max.	12 Mbit/s
• Address area, max.	32
• User data per address area, max.	32 byte
— of which consistent, max.	32 byte
Services	
— Routing	Yes; with interface active
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
3. Interface	
Interface type	Pluggable interface module (IF), technical data as for 2nd interface
Plug-in interface modules	IF 964-DP
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes
User data per isochronous slave, max.	128 byte
Equidistance	Yes
shortest clock pulse	5 ms; 2.5 ms without using the SFCs 126 / 127
Communication functions	
PG/OP communication	Yes
Global data communication	
• supported	Yes
• Number of GD packets, transmitter, max.	8
• Number of GD packets, receiver, max.	16
• Size of GD packets, max.	64 byte
S7 basic communication	
• supported	Yes
• User data per job, max.	76 byte
S7 communication	
• supported	Yes
• as server	Yes
• as client	Yes
• User data per job, max.	64 kbyte
S5 compatible communication	

<ul style="list-style-type: none"> supported 	Yes; via CP and FC AG_SEND and FC AG_RECV
<ul style="list-style-type: none"> User data per job, max. 	8 kbyte
Standard communication (FMS)	
<ul style="list-style-type: none"> supported 	Yes; Via CP and loadable FB
Number of connections	
<ul style="list-style-type: none"> overall 	32; of which one is reserved for PG and OP
<ul style="list-style-type: none"> usable for PG communication <ul style="list-style-type: none"> reserved for PG communication adjustable for PG communication, max. 	1 0
<ul style="list-style-type: none"> usable for OP communication <ul style="list-style-type: none"> reserved for OP communication adjustable for OP communication, max. 	1 0
<ul style="list-style-type: none"> usable for S7 basic communication <ul style="list-style-type: none"> reserved for S7 basic communication adjustable for S7 basic communication, max. 	0 0
<ul style="list-style-type: none"> usable for S7 communication <ul style="list-style-type: none"> reserved for S7 communication adjustable for S7 communication, max. 	0 0
<ul style="list-style-type: none"> usable for routing <ul style="list-style-type: none"> reserved for routing adjustable for routing, max. 	0 0

S7 message functions	
Number of login stations for message functions, max.	8
Symbol-related messages	Yes
Block related messages	Yes
Alarm 8-blocks	Yes
Process control messages	Yes

Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	4
Status/control	
<ul style="list-style-type: none"> Status/control variable 	Yes
Forcing	
<ul style="list-style-type: none"> Forcing 	Yes
Diagnostic buffer	
<ul style="list-style-type: none"> present 	Yes
<ul style="list-style-type: none"> Number of entries, max. <ul style="list-style-type: none"> adjustable 	3 200 Yes

Configuration

Configuration software	
• STEP 7	Yes
Programming	
• Nesting levels	8
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Know-how protection	
• User program protection/password protection	Yes
Dimensions	
Width	50 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	1 070 g
last modified:	03/24/2017