

SIMATIC DP, ET 200ECO PN, 16 DO 24V DC/1,3A; 8 X M12,
DOUBLE-ASSIGNMENT DEGREE OF PROTECTION IP67



Figure similar

General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Load voltage 2L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
Current consumption, typ.	100 mA
from supply voltage 1L+, max.	4 A
from load voltage 2L+, max.	4 A
Power loss	

Power loss, typ.	5.5 W
Digital outputs	
Number of digital outputs	16
• in groups of	8
Short-circuit protection	Yes
• Response threshold, typ.	1.8 A
Limitation of inductive shutdown voltage to	Typ. (L1+, L2+) -47 V
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Output current	
• for signal "1" rated value	1.3 A; Maximum
• for signal "0" residual current, max.	1.5 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 60 °C, max.	3.9 A
Cable length	
• unshielded, max.	30 m
Interfaces	
Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1
PROFINET IO	
• Autocrossing	Yes
• automatic detection of transmission rate	Yes
• Transmission rate, max.	100 Mbit/s
• integrated switch	Yes
PROFINET IO Device	
— IRT with the option "high flexibility"	Yes
— Prioritized startup	Yes
Protocols	
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
PROFIsafe	No
Protocols (Ethernet)	

• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes

Interrupts/diagnostics/status information

Status indicator	Yes; Green LED
Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes; Green "ON" LED
• Wire-break in actuator cable	Yes
• Short-circuit	Yes
• Group error	Yes; Red/yellow "SF/MT" LED

Potential separation

between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
Potential separation digital outputs	
• between the channels	No

Isolation

tested with	
• 24 V DC circuits	707 V DC (type test)
• Interface	1 500 V; According to IEEE 802.3

Degree and class of protection

IP degree of protection	IP67
-------------------------	------

Standards, approvals, certificates

Suitable for safety-oriented group deactivation	Yes
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	d
• SIL acc. to IEC 61508	2

Connection method

Design of electrical connection	4/5-pin M12 circular connectors
---------------------------------	---------------------------------

Dimensions

Width	60 mm
Height	175 mm

Depth	49 mm
Weights	
Weight (without packaging)	910 g
last modified:	03/09/2017