

SIMATIC S7-400, ANALOG INPUT SM 431, NON-ISOLATED 16 AI, RESOLUTION 13 BITS, +/-10V, +/-20MA, 4 - 20MA 20 MS MODULE UPDATE



Figure similar

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V; Only required for supplying 2-wire transmitters
<ul style="list-style-type: none"> <li>Reverse polarity protection</li> </ul>	Yes
Input current	
from load voltage L+ (without load), max.	400 mA; for 16 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	16
<ul style="list-style-type: none"> <li>For voltage/current measurement</li> </ul>	16
permissible input voltage for voltage input (destruction limit), max.	20 V; 20 V DC permanent, 75 V DC for max. 1 s (duty factor 1:20)
permissible input current for current input (destruction limit), max.	40 mA

Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No
Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
• Input resistance (1 V to 5 V)	100 k $\Omega$
• -1 V to +1 V	Yes
• Input resistance (-1 V to +1 V)	10 M $\Omega$
• -10 V to +10 V	Yes
• Input resistance (-10 V to +10 V)	100 k $\Omega$
Input ranges (rated values), currents	
• -20 mA to +20 mA	Yes
• Input resistance (-20 mA to +20 mA)	50 $\Omega$
• 4 mA to 20 mA	Yes
• Input resistance (4 mA to 20 mA)	50 $\Omega$
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	13 bit
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	55 / 65 ms
• Integration time (ms)	50 / 60 ms
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz
Encoder	
Connection of signal encoders	
• for voltage measurement	Yes; possible
• for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Voltage, relative to input range, (+/-)	0.65 %; 1.0% at 1 to 5 V; 0.65% at +/-1 V, +/-10 V
• Current, relative to input range, (+/-)	0.65 %
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.25 %; 0.5% at 1 to 5 V; 0.25% at +/-1 V, +/-10 V
• Current, relative to input range, (+/-)	0.25 %; at +/-20 mA, 4 to 20 mA

## Potential separation

### Potential separation analog inputs

- Potential separation analog inputs No
- between the channels No

## Isolation

Isolation tested with 500 V AC/707 V DC, type test

## Dimensions

Width 25 mm

Height 290 mm

Depth 210 mm

## Weights

Weight, approx. 500 g

**last modified:** 03/24/2017