

\*\*\* SPARE PART\*\*\* SIMATIC DP, ELECTRONIC MODULE  
DIGITAL, FOR ET 200B, W=235MM, 16 DO 24V DC, 2A, DEGR. OF  
PROTECT. IP20,STANDARD

### Supply voltage

Rated value (DC)	24 V; L1+, L2+, L3+, L4+, L5+; value at $t < 0.5$ s: 35 V
permissible range, lower limit (DC)	18.5 V
permissible range, upper limit (DC)	30.2 V

### Input current

Current consumption, typ.	100 mA; From L5+; logic
$I^2t$	0.05 A <sup>2</sup> ·s; with starting current inrush

### Power loss

Power loss, max.	7 W
------------------	-----

### Hardware configuration

Rack	
<ul style="list-style-type: none"> <li>required terminal block</li> </ul>	TB2/DC, TB2-4/DC, TB4/DC, TB4-4/DC

### Digital outputs

Number of digital outputs	16
Short-circuit protection	Yes; Electronic
Limitation of inductive shutdown voltage to	typ. (L1+ to L4+) -50 V
Controlling a digital input	Yes

### Switching capacity of the outputs

<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	10 W
--	------

### Output voltage

<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>for signal "0", max.</li> </ul>	2 V; idling
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	UE -3 V

### Output current

<ul style="list-style-type: none"> <li>for signal "1" permissible range, max.</li> </ul>	2 A; in groups of 4
<ul style="list-style-type: none"> <li>for signal "0" residual current, max.</li> </ul>	1 mA

### Switching frequency

<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>with inductive load, max.</li> </ul>	0.5 Hz
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	8 Hz

### Total current of the outputs (per group)

all mounting positions	
— up to 60 °C, max.	4 A

<b>Cable length</b>	
• unshielded, max.	100 m
<b>Interfaces</b>	
<b>PROFIBUS DP</b>	
• Transmission rate, max.	12 Mbit/s
• SYNC capability	Yes
<b>Protocols</b>	
Bus protocol/transmission protocol	PROFIBUS DP
<b>Interrupts/diagnostics/status information</b>	
<b>Diagnostics indication LED</b>	
• RUN LED	Yes
• Bus fault BF (red)	Yes
• Status indicator digital output (green)	Yes
<b>Potential separation</b>	
between electronic block and PROFIBUS DP	Yes
<b>Potential separation digital outputs</b>	
• Potential separation digital outputs	Yes
• between the channels, in groups of	4
<b>Degree and class of protection</b>	
Degree of protection acc. to EN 60529	IP20
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C; 40°C for other mountings
<b>Air pressure acc. to IEC 60068-2-13</b>	
• permissible range, lower limit	795 hPa
• permissible range, upper limit	1 080 hPa
<b>Relative humidity</b>	
• Operation, min.	15 %
• Operation, max.	95 %; RH class 2 in accordance with IEC 1131-2
<b>Vibrations</b>	
• Operation, tested according to IEC 60068-2-6	Yes; IEC 68, Part 2-6; 10 to 57 Hz; (constant amplitude 0.075 mm); 57 to 150 Hz; (constant acceleration 1 g)
<b>Shock test</b>	
• tested according to IEC 60068-2-27	Yes; IEC 68, Part 2-27; half-sine, 15 g, 11 ms
<b>Connection method</b>	
Design of electrical connection for the inputs and outputs	Screw-type and spring-loaded terminals, permanent wiring; 3 and 4-wire connection
<b>Dimensions</b>	

Width	235 mm; EB and TB
Height	130 mm; EB and TB
Depth	60 mm; EB and TB
<b>Weights</b>	
Weight, approx.	900 g; EB and TB
<b>last modified:</b>	03/07/2017