

SIMATIC S7-400, PS 405 POWER SUPPLY, WIDE RANGE 20A,  
24/48/60V DC, 5V/20A DC



Figure similar

Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
• 48 V DC	Yes
• 60 V DC	Yes
permissible range, lower limit (DC)	Static 19.2 V, dynamic 18.5 V
permissible range, upper limit (DC)	Static 72 V, dynamic 75.5 V
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
• Mains buffering according to NAMUR recommendation	Yes
Input current	
Rated value at 24 V DC	7.3 A
Rated value at 48 V DC	3.45 A
Rated value at 60 V DC	2.75 A
Inrush current, max.	56 A; Full width at half maximum 1.5 ms

Output voltage	
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes
Output current	
for backplane bus (5 V DC), max.	20 A; 200 mA base load required
for backplane bus (24 V DC), max.	1 A; idling-proof
Short-circuit protection	Yes
Power	
Active power input, typ.	175 W
Power loss	
Power loss, typ.	51 W
Battery	
Backup battery	
• Backup battery (optional)	Yes; 2x lithium AA; 3.6 V / 1.9 Ah
Hardware configuration	
Slots	
• required slots	3
Potential separation	
primary/secondary	Yes
Degree and class of protection	
Protection class	1; with protective conductor
Standards, approvals, certificates	
FM approval	Yes; up to 40 °C: T4
Connection method	
Connecting cables/cross-sections	3x 1.5 mm <sup>2</sup> , solid or stranded wire with end sleeve, external diameter 3 mm to 9 mm
Dimensions	
Width	75 mm
Height	290 mm
Depth	217 mm
Weights	
Weight, approx.	2 200 g
<b>last modified:</b>	03/24/2017