

CONNECTING CABLE FOR MOBILE PANELS (MPI/PROFIBUS),  
LENGTH 2 M



Figure similar

General information	
Product type designation	MPI/DP connecting cable
Supply voltage	
Rated value (DC)	24 V; DC
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP65
Standards, approvals, certificates	
CE mark	Yes
Suitable for safety functions	Yes; e.g. emergency stop, acknowledgment button
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C

• max.	70 °C
<b>Relative humidity</b>	
• Operation, max.	85 %

<b>Cables</b>	
Cable length	2 m
smallest bending radius	45 mm
Color of cable sheath	Red
Oil resistance of outer sheath	Yes; Hydrolysis-resistant and oil-resistant acc. to VDE 0472 Part 803/B, also resistant to commercially available lubricants and hydraulic oils
Resistance to MEK, xylene, toluene, isopropanol	Yes

<b>Mechanics/material</b>	
Material of cable sheath	Special PUR, flame-resistant acc. to VDE 0472 Part 804 Test Type B, Shore A 88 Flame-Retardant UR Style 20963

<b>Dimensions</b>	
Thickness	9 mm

<b>Scope of supply</b>	
Delivery quantity in pieces	1

<b>Other</b>	
Merchandise	Yes

<b>Usable in the following products</b>	
• Product 1	<a href="#">6AV6645-0AA01-0AX0</a>
• Product 2	<a href="#">6AV6645-0AB01-0AX0</a>
• Product 3	<a href="#">6AV6645-0AC01-0AX0</a>
• Product 4	6AV6645-0C*
• Product 5	<a href="#">6AV6645-0BE02-0AX0</a>

**last modified:** 08/29/2017