

Product type designation

RF680T transponder

SIMATIC RF680T HEAT RESISTANT TAG; 130X32X15 MM;ISO 18000-6C; EPC CLASS 1 GEN 2, FREQUENCY 860 UP TO 928 MHZ, CHIP TYPE NXP G2XM, EPC 240 BIT 64 BYTE ADD-ON MEMORY, MINIMAL ORDER QUANTITY 10 PCS



Wireless frequencies

Operating frequency	865 ... 928 MHz
---------------------	-----------------

Electrical data

Range / maximum	4 m; observe system manual RF600: overrange is possible, range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
Protocol / with radio transmission	EPCglobal Class 1 Gen 2 / ISO 18000-6C
Transfer rate / with radio transmission / maximum	320 kbit/s
Product feature / multitag-capable	Yes
Polarization	Linear
Product component / Backup battery	No

Memory

Type of memory	EEPROM
Storage capacity / of the user memory	64 byte
Type of memory organization	EPC memory 96/240 bits, user memory 64 bytes (512 bits), TID memory 8 bytes
Number of read cycles / at ambient temperature < 40 °C / maximum	10000000000000

Number of write cycles / at ambient temperature < 40 °C / maximum	100000
Data retention time / at ambient temperature < 40 °C / not less than	10 y
Property of memory	lock, unlock, write protection, password protection
Type of transponder chip used	NXP G2XM

Mechanical data

Material	PPS
Color	black
Tightening torque / of the screw for securing the equipment / maximum	1 N·m
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> during read/write access 	-25 ... +100 °C
<ul style="list-style-type: none"> outside the read/write area 	-40 ... +220 °C
<ul style="list-style-type: none"> during storage 	-40 ... +100 °C
Ambient condition / for operation	Operating temperature permanent up to 140 °C, for 5000 hours or 3000 cycles up to 200 °C, for 2000 hours or 1500 cycles up to 220 °C
Protection class IP	IP68 / IPx9K
Shock resistance	According to DIN EN 60721-3-7 Class 7 M3
Shock acceleration	1000 m/s ²
Vibrational acceleration	200 m/s ²
Resistance to mechanical stress	Torsion and bending stress not permissible

Design, dimensions and weight

Width	32 mm
Height	15 mm
Depth	130 mm
Net weight	50 g
Mounting type	2 x M6 screws

Product properties, functions, components / general

Product feature	
<ul style="list-style-type: none"> silicon-free 	Yes
<ul style="list-style-type: none"> printable 	No

Standards, specifications, approvals

Certificate of suitability	II 2G Ex ib IIB T6 to T2 Gb, II 2D Ex ib IIIB T135 °C Db
MTBF	1940 y

Accessories

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>

<http://www.siemens.com/ident/rfid>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

08/01/2017