

WITHDR. COIL FOR SIZE S12 FOR F. CONTACTOR
 3RT107/3RT147 AC/DC OPERATION 200-277V UC DRIVE:
 ELECTRONIC WITH SPS/SIMOCODE INTERFACE AND RESID.
 LIFETIME INDICATION



Figure similar

General technical data	
product brandname	SIRIUS
Product designation	Magnet coil
Control circuit	
Type of voltage of the control supply voltage	AC/DC
Control supply voltage	
<ul style="list-style-type: none"> • 1 at AC <ul style="list-style-type: none"> — at 50 Hz rated value — at 60 Hz rated value • 2 at AC <ul style="list-style-type: none"> — at 50 Hz rated value — at 60 Hz rated value 	200 V 200 V 277 V 277 V
Control supply voltage	
<ul style="list-style-type: none"> • 1 at DC rated value • 2 at DC rated value 	200 V 277 V
Certificates/approvals	

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	Test Certificates
--------------------------	---------------------------------------	---------------------------	-------------------



[Type Examination Certificate](#)



[Special Test Certificate](#)

Shipping Approval



Shipping Approval	other
-------------------	-------



[Environmental Confirmations](#)

[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT1975-5PP31>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT1975-5PP31>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT1975-5PP31>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT1975-5PP31&lang=en

last modified:

08/12/2017