

SIMATIC DP, ELECT. SUBMODULE FOR ET200ISP, 4 AI HART, 2DMU, FOR CONNECTION OF HART 2-WIRE TRANSDUCER



Figure similar

Input current	
from supply voltage L+, max.	320 mA
Output voltage	
Power supply to the transmitters	
<ul style="list-style-type: none"> • short-circuit proof • Supply current, max. 	Yes 23 mA; per channel
Power loss	
Power loss, typ.	2.7 W
Analog inputs	
Number of analog inputs	4
permissible input current for current input (destruction limit), max.	90 mA
Cycle time (all channels) max.	120 ms; 30 ms basic conversion time x 4 channels with 60 Hz, 50 Hz interference frequency suppression
Technical unit for temperature measurement adjustable	Yes
Input ranges	

• Voltage	No
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	No

Input ranges (rated values), currents

• 4 mA to 20 mA	Yes
-----------------	-----

Cable length

• shielded, max.	500 m
------------------	-------

Analog value generation for the inputs

Measurement principle	integrating (Sigma-Delta)
-----------------------	---------------------------

Integration and conversion time/resolution per channel

• Resolution with overrange (bit including sign), max.	13 bit
• Integration time, parameterizable	No
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz

Smoothing of measured values

• parameterizable	Yes; in 4 stages
• Step: None	Yes; 1 x cycle time
• Step: low	Yes; 4 x cycle time
• Step: Medium	Yes; 32 x cycle time
• Step: High	Yes; 64 x cycle time

Encoder

Connection of signal encoders

• for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	750 Ω

Errors/accuracies

Linearity error (relative to input range), (+/-)	0.015 %
Temperature error (relative to input range), (+/-)	0.005 %/K
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.01 %

Operational error limit in overall temperature range

• Current, relative to input range, (+/-)	0.15 %
---	--------

Basic error limit (operational limit at 25 °C)

• Current, relative to input range, (+/-)	0.1 %
---	-------

Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency

• Series mode interference (peak value of interference < rated value of input range), min.	70 dB
--	-------

Interrupts/diagnostics/status information

Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Limit value alarm	Yes; Parameterizable
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
• between the channels	No
• between the channels and backplane bus	Yes
Standards, approvals, certificates	
CE mark	Yes
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	none
• SIL acc. to IEC 61508	No
Use in hazardous areas	
• Type of protection acc. to EN 50020 (CENELEC)	II2 G (1) GD Ex ib[ia] IIC T4 and I M2 Ex ib[ia] I
• Type of protection acc. to KEMA	04 ATEX 1244
Dimensions	
Width	30 mm
Height	129 mm
Depth	136.5 mm
Weights	
Weight, approx.	230 g
last modified:	03/09/2017