

SIMATIC S7-400, POWER SUPPLY PS407;10A,120/230V  
UC,5V/10A DV FOR REDUNDANT USE

Supply voltage	
Rated value (DC)	
• 120 V DC	Yes
• 230 V DC	Yes
permissible range, lower limit (DC)	88 V
permissible range, upper limit (DC)	300 V
Rated value (AC)	
• 120 V AC	Yes
• 230 V AC	Yes
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Line frequency	
• Rated value 50 Hz	Yes
• Rated value 60 Hz	Yes
• permissible range, lower limit	47 Hz
• permissible range, upper limit	63 Hz
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
• Mains buffering according to NAMUR recommendation	Yes
Input current	
Rated value at 110 V DC	1.2 A
Rated value at 230 V DC	0.6 A
Rated value at 120 V AC	1.2 A
Rated value at 230 V AC	0.6 A
Inrush current, max.	18 A; 15 x rated value input current
Output voltage	
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes
Output current	
for backplane bus (5 V DC), max.	10 A; 200 mA base load required
for backplane bus (24 V DC), max.	1 A; idling-proof
Short-circuit protection	Yes

<b>Power</b>	
Active power input, typ.	97.5 W
<b>Power loss</b>	
Power loss, typ.	22.4 W
<b>Battery</b>	
Backup battery	
• Backup battery (optional)	Yes; 2x lithium AA; 3.6 V / 1.9 Ah
<b>Hardware configuration</b>	
Slots	
• required slots	2
<b>Potential separation</b>	
primary/secondary	Yes
<b>EMC</b>	
Compliance with line harmonic distortion limits	
• Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3	Yes
<b>Degree and class of protection</b>	
Protection class	1; with protective conductor
<b>Standards, approvals, certificates</b>	
FM approval	Yes; up to 40 °C: T4
<b>Connection method</b>	
Connecting cables/cross-sections	3x 1.5 mm <sup>2</sup> , solid or stranded wire with end sleeve, external diameter 3 mm to 9 mm
<b>Dimensions</b>	
Width	50 mm
Height	290 mm
Depth	217 mm
<b>Weights</b>	
Weight, approx.	1 360 g
<b>last modified:</b>	03/24/2017