

SIMATIC MOBILE PANEL 177 DP WITH INTEGRATED ENABLING BUTTON AND STOP BUTTON, CONFIGURABLE WITH WINCC FLEXIBLE COMPACT VERSION 2005 AND HIGHER OR TIA PORTAL V11 AND HIGHER



Figure similar

Display	
Design of display	STN
Screen diagonal	5.7 in
Number of colors	256
Color type	Colors
Resolution (pixels)	
• Horizontal image resolution	320 Pixel
• Vertical image resolution	240 Pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
• Backlight dimmable	No
Control elements	
Control elements	Keys and touch
Keyboard fonts	
• Membrane keyboard — user-definable label membrane keys	Yes
• Function keys	

— Number of function keys	14
— Number of function keys with LEDs	8
• Keys with LED	Yes; 8 with LED
• System keys	Yes
• Numeric/alphabetical input	Yes / Yes
— hexadecimal keyboard	Yes
• Multi-key operation	Yes
— Number of multi-key operations	2
<b>Touch operation</b>	
• Design as touch screen	Yes; analog, resistive
<b>Special operator controls</b>	
• Stop button	Yes
• Acknowledgement button	Yes
• Key-operated switch	No
• Illuminated pushbutton	No
• Handwheel	No
<b>Supply voltage</b>	
Design of the power supply	via connection box
Type of supply voltage	DC
<b>Processor</b>	
Processor type	RISC 32-bit, 200 MHz
<b>Drives</b>	
Diskette drive	No
CD-ROM	No
Hard disk	No
<b>Memory</b>	
Type of memory	Flash / RAM
Memory available for user data	2 048 kbyte
<b>Type of output</b>	
Info LED	No
Power LED	No
Error LED	No
<b>Interfaces</b>	
Interfaces/bus type	1 x RS422, 1 x RS485 (max. 12 Mbit/s)
Number of RS 485 interfaces	1
• Transmission rate, max.	12 Mbit/s
Number of USB interfaces	0
Number of parallel interfaces	0
USB port	No
PC card slot	No

CF card slot	No
Multimedia card/SD card slot	combined
Special interfaces	1 x special interfaces
<b>Industrial Ethernet</b>	
• Industrial Ethernet interface	No
• Industrial Ethernet status LED	0
<b>Protocols</b>	
PROFINET	No
Supports protocol for PROFINET IO	No
PROFIsafe	No
PROFIBUS	Yes
AS-Interface	No
<b>Protocols (Ethernet)</b>	
• TCP/IP	No
<b>Further protocols</b>	
• CAN	No
• Data-Highway	No
• DeviceNet	No
• INTERBUS	No
• Local Operating Network	No
• MODBUS	Yes
• SUCOnet	No
• other bus systems	Yes
<b>Degree and class of protection</b>	
Enclosure according to EN 60529	IP65
<b>Standards, approvals, certificates</b>	
Certifications	CE, cULus, C-TICK, SIBE
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
<b>Highest safety class achievable in safety mode</b>	
• Performance level according to ISO 13849-1	d
<b>Use in hazardous areas</b>	
• cULus Class I Zone 2, Division 2	No
• FM Class I Division 2	No
<b>Ambient conditions</b>	
<b>Free fall</b>	
• Fall height, max.	1.5 m
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	40 °C

<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C
• max.	60 °C
<b>Relative humidity</b>	
• Operation, max.	80 %

<b>Operating systems</b>	
pre-installed operating system	Windows CE

<b>Configuration</b>	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes

<b>Configuration software</b>	
• WinCC flexible Compact	Yes
• WinCC flexible Standard	Yes
• WinCC flexible Advanced	Yes
• WinCC Basic (TIA Portal)	No
• WinCC Comfort (TIA Portal)	Yes
• WinCC Advanced (TIA Portal)	Yes
• WinCC Professional (TIA Portal)	Yes
• Configuration tool	WinCC flexible Compact Version 2005 or higher (to be ordered separately)
• 2. Configuration kit	WinCC flexible Compact
— Version	Version 2005
— Configuration tool	WinCC flexible
— Type	Compact

<b>Languages</b>	
<b>Online languages</b>	
• Number of online/runtime languages	5
<b>Project languages</b>	
• Languages per project	32

<b>Functionality under WinCC (TIA Portal)</b>	
Libraries	Yes
Applications/options	none
• Pocket Word	No
• Pocket Excel	No
• PDF Viewer	No
• Media Player	No
• SIMATIC WinCC Sm@rtServer	Yes
• SIMATIC WinCC Audit	No

• Connection point identification	Yes
Number of Visual Basic Scripts	No
• Debugging in the simulator	No
Task planner	Yes
Help system	Yes
• Number of characters per info text	70
<b>Message system</b>	
• Number of alarm classes	32
• Number of messages	2 000
• Bit messages	Yes
— Number of bit messages	2 000
• Analog messages	Yes
— Number of analog messages	50
• Telegram message procedure Alarm S	No
• System messages HMI	Yes
• System messages PLC	No
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No
• Lines	1
• Number of characters per message	80
• Number of process values per message	8
• Message indicator	Yes
• acoustic feedback	No
• First/last value	Yes
<b>Recipe management</b>	
• Number of recipes	100
• Data records per recipe	200
• Entries per data record	200
• Recipe memory	32 KB integrated Flash, expandable
<b>Variables</b>	
• Number of variables per device	1 024
• Number of variables per screen	50
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
<b>Images</b>	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
<b>Image objects</b>	

• Text objects	2,500 text elements
• Number of I/O fields per image	50
• Index of screen context	No
• Return	Yes
• Graphics object	Bit maps, vector graphics
<b>Complex image objects</b>	
• Status/control	Yes; With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, invisible buttons
• Methods	Trend / profile
• Bar graphs	
— Number of bars per chart	5
• Limit value lines	Yes
• Number of visible switches per project	1 000
<b>Attributes for dynamic objects</b>	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
• Angle of rotation	No
<b>Lists</b>	
• Number of text lists per project	300
• Number of entries per text list	30
• Number of graphics lists per project	100
<b>Archiving</b>	
• Number of archives per device	0
• Message archive	No
• Process value archive	No
• Archiving methods	
— Sequential archive	No
— Short-term archive	No
• Memory location	
— PC card	No
— CF card	No
— USB memory	No
— Ethernet	No
• Data storage format	
— CSV	No
— TXT	No
• Online evaluation	
— using trend curves	No
<b>Security</b>	
• Number of user groups	50

• Number of user rights	32
• Password export/import	Yes
<b>Data carrier support</b>	
• PC card	No
• CF card	No
• Diskette drive	No
• Hard disk	No
<b>Transfer (upload/download)</b>	
• Transfer of configuration	MPI/PROFIBUS DP, serial, automatic transfer recognition
<b>Process coupling</b>	
• Connection to controller	S5, S7-200, S7- 300/400, TI 505, Win AC, SINUMERIK, SIMOTION, Allen Bradley (DF1), Allen Bradley (DF485), Mitsubishi (FX), OMRON (LINK/Multilink), Modicon (Modbus), weitere Fremdtreiber siehe Kapitel "Systemkopplungen"
• S7-1200	Yes; with restrictions
• S7-1500	Yes; with restrictions
• S7-200	Yes
— PPI (point-to-point)	Yes
— PPI network	Yes
— MPI	Yes
— PROFIBUS DP	Yes
• S7-300/400	Yes
— MPI	Yes
— PROFIBUS DP	Yes
— PROFINET	No
• LOGO!	No
• SINUMERIK	Yes
• SIMOTION	Yes
• S5	Yes
— serial	No
— PROFIBUS DP	Yes
• TI 505	Yes
• Allen Bradley (EtherNet/IP)	No
• Allen Bradley (DF1)	Yes
• Allen Bradley (DF485)	Yes
• Mitsubishi (MC TCP/IP)	No
• Mitsubishi (FX)	Yes
• Mitsubishi (MP4)	Yes
• Telemecanique (ADJUST)	No
• Telemecanique (Uni-Telway)	Yes
• OMRON (FINS TCP)	No
• OMRON (LINK/Multilink)	Yes

• Modicon (Modbus TCP/IP)	No
• Modicon (Modbus)	Yes
• GE-Fanuc (SNP)	Yes
<b>Functions</b>	
• Key repeat	No
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
• Menu tree editor	No
• Unit switchover	No
<b>Service tools/configuration aids</b>	
• Clean screen	No
• Touch calibration	Yes
• Backup/Restore manually	Yes
• Simulation	Yes
• Device switchover	Yes
• Delta transfer	Yes
• Monitoring function for battery and memory	Yes
• Trace (operation archive)	No
<b>Expandability/openness</b>	
• Open Platform Program	Yes
<b>Peripherals/Options</b>	
<b>Peripherals</b>	
• Printer	Yes
• SIMATIC HMI MM memory card: Multi Media Card	Yes
• SIMATIC HMI SD memory card: Secure Digital memory card	No
• USB memory	No
<b>Mechanics/material</b>	
Type of housing (front)	plastic
<b>Dimensions</b>	
Enclosure diameter	245 mm
Depth of housing	58 mm
<b>Weights</b>	
Weight (without packaging)	1.3 kg
<b>Other</b>	
free hotline	Yes
Warranty period	1 y



last modified:

04/28/2017