

SIMATIC DP, 5 ELECTRON. MODULES FOR ET 200S, 2 DO HIGH FEATURE DC 24V/2A, 15 MM WIDTH DIAGNOSIS F. SHORT-CIRCUIT AND OPEN-CIRCUIT, FIRST-UP SIGNAL WITH LED SF (GROUP FAULT), 5 PIECES PER PACKAGING UNIT



Supply voltage	
Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> <li>Reverse polarity protection</li> </ul>	24 V; From power module  Yes; polarity reversal can lead to the digital outputs being connected through
Input current	
from load voltage L+ (without load), max.	5 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA
Power loss	
Power loss, typ.	1.4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>with packing</li> <li>without packing</li> </ul>	2 bit  1 byte
Digital outputs	
Number of digital outputs	2

Short-circuit protection	Yes
• Response threshold, typ.	4 A
Limitation of inductive shutdown voltage to	-55 to -60 V, typ. L+( )
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
• on lamp load, max.	5 W
<b>Load resistance range</b>	
• lower limit	12 $\Omega$
• upper limit	3 400 $\Omega$
<b>Output voltage</b>	
• for signal "1", min.	L+ (-1 V)
<b>Output current</b>	
• for signal "1" rated value	2 A
• for signal "1" permissible range, min.	7 mA
• for signal "1" permissible range, max.	2.4 A
• for signal "0" residual current, max.	0.5 mA
<b>Output delay with resistive load</b>	
• "0" to "1", max.	100 $\mu$ s
• "1" to "0", max.	400 $\mu$ s
<b>Parallel switching of two outputs</b>	
• for uprating	No
• for redundant control of a load	Yes; per module
<b>Switching frequency</b>	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz; 0,5 H
• on lamp load, max.	10 Hz
<b>Total current of the outputs</b>	
• Current per module, max.	4 A
<b>Cable length</b>	
• shielded, max.	1 000 m
• unshielded, max.	600 m
<b>Isochronous mode</b>	
Isochronous operation (application synchronized up to terminal)	Yes
<b>Interrupts/diagnostics/status information</b>	
Diagnostic functions	Yes
Substitute values connectable	Yes; 0/1
<b>Diagnostic messages</b>	
• Diagnostic information readable	Yes
• Wire-break	Yes; channel by channel
• Short-circuit	Yes; channel by channel

Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes

Parameter	
Remark	3 byte
Diagnostics wire break	Disable / enable
Diagnostics short-circuit	Disable / enable
Response to CPU/master STOP	Substitute a value/keep last value

Potential separation	
Potential separation digital outputs	
• between the channels	No
• between the channels and backplane bus	Yes

Isolation	
Isolation tested with	500 V DC

Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm

Weights	
Weight, approx.	40 g
<b>last modified:</b>	03/07/2017