

SIMATIC S7-300, CP 340 COMMUNICATION PROCESSOR WITH
20MA INTERFACE (TTY) INCL. CONFIG. PACKAGE ON CD

Input current	
from backplane bus 5 V DC, max.	220 mA
Power loss	
Power loss, max.	0.85 W
Interfaces	
Number of interfaces	1; Isolated
Interface physics, 20 mA (TTY)	Yes
Transmission rate, min.	2.4 kbit/s
Transmission rate, max.	9.6 kbit/s
Point-to-point	
<ul style="list-style-type: none"> Cable length, max. supported printers 	1 000 m; 100 m active, 1000 m passive HP-Deskjet, HP-Laserjet, IBM-Proprinter, user-defined
Telegram length, max.	
— 3964 (R)	1 024 byte
— ASCII	1 024 byte
Transmission rate, 20 mA (TTY)	
— with 3964 (R) protocol, max.	19.2 kbit/s
— with ASCII protocol, max.	9.6 kbit/s
— with printer driver, max.	9.6 kbit/s
Software	
Block	
<ul style="list-style-type: none"> FB length in RAM, max. 	2 700 byte; Data communication, sending and receiving
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	300 g
last modified:	03/15/2018