

\*\*\* SPARE PART\*\*\* SIMATIC S7, TD 100C TEXTDISPLAY FOR S7-200, 4 LINES, WITH MOUNTING ACCESSORIES, CONFIGURATION WITH STEP7-MICRO/WIN

### Display

Design of display	LC display (reflecting)
<b>Line display</b>	
• Number of lines	4
• Number of characters per line	12; Characters/line: 12 or 16 characters/line: Chinese 8
• Character size	3.34 mm

### Supply voltage

Rated value (DC)	24 V; Supply from S7-200 communication interface
------------------	--

### Input current

Current consumption, max.	50 mA
---------------------------	-------

### 1. Interface

Physics	RS 485
<b>Functionality</b>	
• PPI	Yes
— Number of nodes, max.	126; S7-200, OP, TP, TBP, PG / PC

### Degree and class of protection

IP (at the front)	IP65
-------------------	------

### Ambient conditions

<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-20 °C
• max.	70 °C

### Dimensions

Width	90 mm
Height	76 mm
Depth	36 mm; max. 44 mm with fittings
Mounting cutout, width	82 mm
Mounting cutout, height	69.5 mm
Cabinet/switchboard thickness	1.5 mm; 1.5 to 4 mm

### Weights

---

Weight, approx.

120 g

**last modified:**

03/13/2017