

Product type designation

CP 343-1

COMMUNICATIONSPROCESSOR CP343-1 FOR CONNECTION OF SIMATIC S7-300 WITH IND. ETHERNET USING ISO, TCP/IP AND UDP, S7 COMM., FETCH/WRITE, SEND/RECEIVE, WITH AND W/O RFC 1006, DIAGN. EXPANSIONS, MULTICAST, PBK, INITIALIZATION THROUGH LAN, 10/100 MBIT



Figure similar

Transmission rate

Transfer rate

- at the 1st interface 10 ... 100 Mbit/s

Interfaces

Number of interfaces / acc. to Industrial Ethernet

1

Number of electrical connections

- at the 1st interface / acc. to Industrial Ethernet 1
- for power supply 1

Type of electrical connection

- at the 1st interface / acc. to Industrial Ethernet RJ45 port / AUI
- for power supply 2-pole plugable terminal block

Supply voltage, current consumption, power loss

Type of voltage / of the supply voltage

DC

Supply voltage / 1 / from backplane bus

5 V

Supply voltage / external

24 V

Supply voltage / external / at DC / Rated value

24 V

Relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> • at 5 V • at 24 V 	5 % 5 %
Consumed current	
<ul style="list-style-type: none"> • from backplane bus / at DC / at 5 V / typical • from external supply voltage / at DC / at 24 V / maximum 	0.07 A 0.73 A
Power loss [W]	10 W

Permitted ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • for vertical installation / during operation • for horizontally arranged busbars / during operation • during storage • during transport 	0 ... 40 °C 0 ... 60 °C -40 ... +70 °C -40 ... +70 °C
Relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
Protection class IP	IP20

Design, dimensions and weight

Module format	Compact module S7-300 double width
Width	80 mm
Height	125 mm
Depth	120 mm
Net weight	0.6 kg
Mounting type	
<ul style="list-style-type: none"> • S7-300 rail mounting 	Yes

Performance data / open communication

Number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	16
Amount of data	
<ul style="list-style-type: none"> • as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum • as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum • as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum • as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte 8 Kibyte 8 Kibyte 2 Kibyte

Number of Multicast stations	16
Performance data / S7 communication	
Number of possible connections / for S7 communication	
• maximum	16
Performance data / multi-protocol mode	
Number of active connections / with multi-protocol mode	32
Performance data / telecontrol	
Protocol / is supported	
• TCP/IP	Yes
Product function / MIB support	No
Protocol / is supported	
• SNMP v1	No
• DCP	No
• LLDP	No
Configuration software	
• required	STEP 7 V5.1 SP2 or higher
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher-level designation/location designation	Yes
Product functions / switch	
Product feature / Switch	No
Product functions / Redundancy	
Product function	
• Ring redundancy	No
Product functions / Time	
Product function / SICLOCK support	Yes
Product function / pass on time synchronization	Yes
Protocol / is supported	
• NTP	Yes
Further Information / Internet Links	
Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb

- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

06/15/2017