

Program Overview



sirius

POWER SUPPLIES



SIEMENS

Maximum Quality and Performance

DC Power Supplies by Siemens

Non-stabilized DC power supplies

Thanks to their rugged design, the 4AV devices feature a very high reliability. They are extremely resistant to the influence of external mains interferences and have a dampening effect on EMC. They are also suitable for the supply of capacitive loads as the connection of these consumers causes only minor voltage drops.

Filtered power supplies

Power supplies 4AV2, 4AV30 to 4AV35, 4AV36 and 4AV38 with add-on capacitors, 4AV4 and 4AV5 supply a non-stabilized 24 V DC voltage on the basis of single- or three-phase safety transformers with downstream rectifiers and capacitor filtering.

The devices 4AV2, 4AV30 to 4AV35, 4AV4 and 4AV5 are employed for:

- Supply of control circuits
- Power supply of electronic controls

They comply with the requirements in accordance with EN 61131-2 "Programmable logic controllers – equipment requirements and tests" and are, amongst others, suitable for SIMATIC.

The data listed in the selection tables are based on fixed service conditions, under which the devices can be loaded with the rated power or rated current:

- Pn due to continuous operation
- Frequency AC 50 Hz ... 60 Hz
- Installation altitude up to 1000 m above sea level
- Degree of protection IP00
- Ambient temperature t_a

The devices are designed for installation in encapsulated controls and electronic cabinets. They are climate-proof for installation in rooms with outdoor climates in accordance with DIN 50010.

Limit values:

Ambient temperature with the rated power or current for types:

- 4AV2 and 4AV3: up to +60 °C
- 4AV4 and 4AV5: up to +40 °C
- Minimum value for all types: –25 °C

Relative humidity:

- At +40 °C occasionally up to 100 %
- Annual average up to 80 %
- Occasional condensation possible

Further versions:

Unfiltered power supplies

The single-phase devices 4AV98 are particularly suited for the power supply of resistive and inductive consumers whose operating voltage does not entail any special ripple requirements. The three-phase devices 4AV96 are designed and approved in accordance with the VW equipment specifications.

The power supplies 4AV96 and 4AV98 consist of safety transformers in accordance with EN 61558-2-6 with downstream rectifiers in bridge circuit without capacitor filtering.

The devices are climate-proof for installation in rooms with outdoor climate in accordance with DIN 50010.

Limit values:

- Ambient temperature
- With rated power or rated current: +50 °C
- Minimum value: –25 °C

Relative humidity:

- At +40 °C occasionally up to 100 %
- Annual average up to 80 %
- Occasional condensation possible



Other products

Customized transformers and transformers for special applications:

- Toroidal-core transformers
- Equipment transformers
- Medium-frequency transformers
- Transformers for converters / power converter operation
- Special transformers for rail vehicles
- Special transformers for ships and portainers
Option: vibration-proof, low-noise version (only available in enclosure)
- Special transformers in acc. with DIN EN 60601-1 (VDE 0750) for medical engineering
- High-reactance transformers
- Toroidal-core and pillar-type variable-ratio transformers 4CH, 4CP, 4CI and 4CQ (see interactive catalog CA01 and A&D Mall)
- Transformers for noise-sensitive environments

AC voltage regulators:

- Magnetic voltage regulators, single-phase
- Transformer-type voltage regulators, single- and three-phase

DC power supplies:

- Rectifier units, non-stabilized, unfiltered
- Rectifier units with 24 V DC for the power supply of electronic controls, filtered
- Stabilized DC power supplies
- Multi-output power supply

Reactors:

- For variable-speed drives
 - Mains reactors
 - Commutating reactors
 - Smoothing reactors
 - Output filter reactors
- Air-core and iron-core reactors

Filters:

- For variable-speed drives
 - Radio interference suppression filters
 - dv/dt filters
 - Sine-wave filters

For detailed ordering information, please refer to the catalogs LV1, section 10 and 11, LV60, LV65 or the interactive catalog and the A&D Mall.


www.siemens.com/lowvoltage/mall

Non-Stabilized Power Supplies 4AV Filtered for the Supply of Electronic Controls

Selection and ordering data

Power supplies 4AV2 and 4AV4 supply non-stabilized 24 V DC on the basis of single-phase safety transformers with downstream rectifiers and capacitor filtering.

Rated output voltage U_{2N} 24 V DC in accordance with EN 61131-2³⁾ and SIMATIC with input voltage +6% to -10% and load 0% to 100%. Safety transformer in accordance with EN 61558-2-6, degree of protection IP00.

4AV21, 4AV23, 4AV41: 

4AV20, 4AV22, 4AV24, 4AV26: 

EMC in accordance with: EN 62041

4AV2 is suitable for the connection to public supply networks (residential applications) and industrial networks (industrial applications).

4AV4 is suitable for the connection to industrial networks (industrial applications).

4AV2: $t_a = \text{max. } 60 \text{ }^\circ\text{C/B}$, 4AV41: $t_a = 40 \text{ }^\circ\text{C/B}$

4AV2: CE , c_{us} at $60 \text{ }^\circ\text{C}$

4AV41: CE

4AV20, 4AV22, 4AV26 and 4AV4: Version with spring-loaded terminals listed in the LV1 catalog.

4AV2, 4AV4: single-phase; ripple < 5 %

PRI		230 (240) V ¹⁾ 115 (120) V	400 (415) V	400 (415) V 230 (240) V with tapping ± 15 V	400 (415) V 230 (240) V 115 (120) V			
SEC		24 V DC	24 V DC	24 V DC	24 V DC			
Rated output current I_d								
60 °C/B EN 61558 DCA c_{us}	40 °C/H EN 61558 DCA	Basic type	Order number supplement					
			With integrated DIN rail connection	With integrated DIN rail connection	Screw mounting ²⁾	DIN rail connection	Screw mounting ²⁾	DIN rail connection
1	1.2	4AV2102-	2EB00 - 0A	-	-	-	-	-
2.5	3	4AV2000-	-	-	2EB00 - 0A	2EB00 - 0A	-	-
3.5	4.2	4AV2302-	2EB00 - 0A	-	-	-	-	-
5	6	4AV2200-	-	-	2EB00 - 0A	2EB00 - 0B	-	-
10	12	4AV2400-	-	-	2EB00 - 0A	2EB00 - 0B	-	-
15	18	4AV2600-	-	-	2EB00 - 0A	-	-	-
1	1.2	4AV2106-	-	2EB00 - 0A	-	-	-	-
2.5	3	4AV2001-	-	-	-	-	2EB00 - 0A	2EB00 - 0A
3.5	4.2	4AV2306-	-	2EB00 - 0A	-	-	-	-
5	6	4AV2201-	-	-	-	-	2EB00 - 0A	2EB00 - 0B
10	12	4AV2401-	-	-	-	-	2EB00 - 0A	2EB00 - 0B
15	18	4AV2601-	-	-	-	-	2EB00 - 0A	-
-	1.5	4AV4101-	-	-	2EB00 - 0A	2EB00 - 0B	-	-
-	3	4AV4103-	-	-	2EB00 - 0A	2EB00 - 0A	-	-
-	6	4AV4106-	-	-	2EB00 - 0A	2EB00 - 0A	-	-
-	10	4AV4110-	-	-	2EB00 - 0A	2EB00 - 0B	-	-

¹⁾ When operated with the mains voltages stated in brackets, the upper limit for 24 V DC in accordance with EN 61131-2 with a mains voltage of +6% is met with a basic load of 10%. With no-load operation, 30.6 V can be reached.

²⁾ Types 4AV20, 4AV41 03 and 4AV41 06 are equipped with integrated DIN rail connection as a standard.

³⁾ EN 61131-2: Equipment requirements of a power supply and interface for programmable logic controllers. For limit values for 24 V DC, refer to technical information LV1 T "Technical Data".



4AV23



4AV2



4AV41

Power supplies 4AV3 and 4AV5 supply non-stabilized 24 V DC on the basis of three-phase safety transformers with downstream rectifiers and capacitor filtering.

Rated output voltage U_{2N} 24 V DC in accordance with EN 61131-2⁴⁾ and SIMATIC with input voltage +6% to -10% and load 0% to 100%. Safety transformer in accordance with EN 61558-2-6, degree of protection IP00.

4AV3, 4AV5: 

EMC in accordance with: EN 62041



4AV3 is suitable for the connection to public supply networks (residential applications) and industrial networks (industrial applications).

4AV5 is suitable for the connection to industrial networks (industrial applications).

4AV3: $t_a = \text{max. } 60 \text{ }^\circ\text{C/B}$, 4AV51: $t_a = 40 \text{ }^\circ\text{C/B}$

4AV30: ,  at $60 \text{ }^\circ\text{C}$

4AV36, 4AV38, 4AV51: 

4AV30 to 4AV35 and 4 AV5: three-phase; ripple < 5 %													
PRI		400 (415) V/230 V with tapping $\pm 20\text{V}/\pm 10 \text{ V}$ Y/ Δ		500 V/400 V (415) V		PRI		400 (415) V with tapping $\pm 20\text{V}$		575 (600) V–500 V 460 (480) V–400 (415) V 230 (240) V–200 V			
SEC		24 V DC		24 V DC		SEC		24 V DC		24 V DC			
Rated output current I_d						Rated output current I_d							
60 °C/B EN 61558 DC A 	40 °C/H EN 61558 DC A	Basic type		Order number supplement		60 °C/B EN 61558 DC A 	40 °C/H EN 61558 DC A	Basic type		Order number supplement			
				Standard version ¹⁾	Add-on capacitors ²⁾	Standard version ¹⁾	Add-on capacitors ²⁾			Standard version ¹⁾	Standard version ¹⁾	Add-on capacitors ²⁾	
10	12	4AV3000-	2EB00 - 0A	2EB00 - 0C				9	11	4AV3002-	-	2EB00 - 0A	2EB00 - 0C
15	18	4AV3100-	2EB00 - 0A	2EB00 - 0C				13.5	16	4AV3102-	-	2EB00 - 0A	2EB00 - 0C
20	24	4AV3200-	2EB00 - 0A	2EB00 - 0C				18	21.5	4AV3202-	-	2EB00 - 0A	2EB00 - 0C
30	36	4AV3300-	2EB00 - 0A	2EB00 - 0C				-	25	4AV5125-	2EB00 - 0A	-	-
40	48	4AV3400-	2EB00 - 0A	2EB00 - 0C				27	32.5	4AV3302-	-	2EB00 - 0A	2EB00 - 0C
50	60	4AV3500-	2EB00 - 0A	2EB00 - 0C				-	35	4AV5135-	2EB00 - 0A	-	-
								36	43	4AV3402-	-	2EB00 - 0A	2EB00 - 0C
15	18	4AV3101-			2EB00 - 0A	2EB00 - 0C		45	54	4AV3502-	-	2EB00 - 0A	2EB00 - 0C
30	36	4AV3301-			2EB00 - 0A	2EB00 - 0C							
50	60	4AV3500-			2EB00 - 0A	2EB00 - 0C							
4AV36 to 4AV38: three-phase; unfiltered: ripple < 5 %; with add-on capacitors: ripple 4 %													
80 ³⁾	96	4AV3601-			2EB00 - 0A	2EB00 - 0C							
150 ³⁾	180	4AV3801-			2EB00 - 0A	2EB00 - 0C							

¹⁾ Ripple < 5%

²⁾ Additional capacity (aluminum electrolyte) for 4AV30 to 4AV35 of 10000 μF ; for 4AV36 of 2 x 10000 μF ; for 4AV38 of 3 x 10000 μF

³⁾ No  approval

⁴⁾ EN 61131-2: Equipment requirements of a power supply and interface for programmable logic controllers. For limit values for 24 V DC, refer to technical information LV1 T "Technical Data".

For the respective ripple and buffer time values, refer to the LV1 catalog.



4AV30 up to 4AV33



4AV51

Non-Stabilized Power Supplies 4AV98 and 4AV96 Unfiltered for the Supply of General Loads

Selection and ordering data

The power supplies 4AV98 consist of single-phase safety transformers in accordance with EN 61558-2-6 with downstream rectifiers in bridge circuit without capacitor filtering.

Safety transformer in accordance with EN 61558-2-6, varistor protective circuit.

Output-side short-circuit and overload protection through installed fuse.

Ripple 48 %

$t_a = 50\text{ °C/B}$



4AV98: single-phase				
PRI		230 V		400 V
SEC		24 V DC		24 V DC
Rated power P_{2N}	Voltage rise with no-load operation U_A			
W	%	Basic type	Order number supplement	
50	24	4AV9806-	4CB00 - 2N	
80	18	4AV9806-	5CB00 - 2N	
125	14	4AV9806-	6CB00 - 2N	
200	11	4AV9806-	7CB00 - 2N	
315	10	4AV9806-	8CB00 - 2N	
500	9	4AV9800-	5CB00 - 2N	
50	24	4AV9807-	0CB00 - 2N	
80	18	4AV9807-	1CB00 - 2N	
125	14	4AV9807-	2CB00 - 2N	
200	11	4AV9807-	3CB00 - 2N	
315	10	4AV9807-	4CB00 - 2N	
500	9	4AV9802-	5CB00 - 2N	

The power supplies 4AV96 consist of three-phase safety transformers in accordance with EN 61558-2-6 with downstream rectifiers in bridge circuit without capacitor filtering.

Safety transformer in accordance with EN 61558-2-6. Shield winding between input and output winding. Varistor protective circuit.


Designed and approved in accordance with the VW equipment specifications.

Ripple < 5 %


$t_a = 50\text{ °C/B}$



4AV96: three-phase				
PRI		Primary-side short-circuit and overload protection for the rectifier with circuit breaker		400 V
SEC				DC 30-27-24 V
Rated output current I_d	Voltage rise with no-load operation U_A	Type	Setting value with 400 V AC	Order number
A	%		A	
4	3.5	3RV10 11-0EA10	0.28	4AV9604-1CB00-2N
12	3.3	3RV10 11-0JA10	0.8	4AV9604-5CB00-2N
25	3.1	3RV10 11-0CA10	1.8	4AV9604-2CB00-2N



4AV98



4AV96

Delivery

In the selection tables, the “24-hour service” delivery period is marked by a colored background.

24-hour service with degree of protection IP00, i.e. the devices are available ex stock, are shipped within 24 hours and delivered to the shipping address on the following day.

For products and options without “24-hour service” marking, the delivery period stated upon request is applicable.



Methodical quality

We offer a certified quality management system in accordance with DIN EN ISO 9001:2000 and a certified environmental management system in accordance with DIN ISO 14001:2004. We are a recognized supplier of leading original equipment manufacturers.

For further information, please refer to the LV1 catalog, section 11, or the interactive catalog and the A&D Mall.
www.siemens.com/lowvoltage/mall

Do you require further information?

Please contact:

MD_Anfrage.aud@siemens.com

or send a fax to:

+49 4 21/5 12 53 33

Siemens AG

Automation and Drives
Low-Voltage Controls and Distribution
P.O. Box 48 48, 90327 NUREMBERG
GERMANY

www.siemens.com/sirius

The information provided in this brochure contains merely general descriptions or characteristics of performance which in actual case of use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

All product designations may be trademarks or product names of Siemens AG or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.