

## SINAMICS - dostępne komponenty

**Kontakt:**  
**tel. 32 440 22 10**  
**e-mail: [biuro@adegis.com](mailto:biuro@adegis.com)**  
**[www.adegis.com](http://www.adegis.com)**

PRZEŚLIJ ZAPYTANIE dot. czasu realizacji



Numer artykułu	Producent	Opis	Nowe	Używane
6FX2002-1DC00-1AB0	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX2002-1DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITHOUT 24 V LENGTH (M) = 0 + 0 + 1 + 0	+ 10	0
6FX2002-1DC00-1AB5	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX2002-1DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITHOUT 24 V LENGTH (M) = 0 + 0 + 1 + 0,5	+ 10	0
6SL3000-0BE21-6AA0	SIEMENS	SINAMICS LINE FILTER FOR 16 KW ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ	0	+ 10
6SL3000-0BE21-6DA0	SIEMENS	SINAMICS / SIMODRIVE 611 BASIC LINE FILTER FOR 16KW ACTIVE LINE MODULE AND 16KW SMART LINE MODULE AND 20KW BASIC LINE MODULE AND SINAMICS S120 COMBI INPUT: 3AC 380-480V, 50/60HZ PLEASE OBSERVE CONDITIONS OF USE!	1	0
6SL3000-0BE23-6AA0	SIEMENS	SINAMICS LINE FILTER FOR 36 KW ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ	0	3
6SL3000-0BE25-5AA0	SIEMENS	SINAMICS LINE FILTER FOR 55 KW ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ	0	3
6FX5002-2DC00-1AB0	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX5002-2DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITH 24 V MOTION-CONNECT 500 LENGTH (M) = 0 + 0 + 1 + 0	1	0
6FX5002-2DC10-1AF0	SIEMENS	SIGNAL CABLE, PREASSEMBLED SIGNAL CABLE, PREASSEMBLED TYPE: 6FX5002-2DC10 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP67, WITH 24 V MOTION-CONNECT 500 LENGTH (M) = 0 + 0 + 5 + 0	+ 10	0
6FX5002-2DC10-1BA0	SIEMENS	SIGNAL CABLE, PREASSEMBLED SIGNAL CABLE, PREASSEMBLED TYPE: 6FX5002-2DC10 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP67, WITH 24 V MOTION-CONNECT 500 LENGTH (M) = 0 + 10 + 0 + 0	0	8
6FX5002-2DC10-1BF0	SIEMENS	SIGNAL CABLE, PREASSEMBLED SIGNAL CABLE, PREASSEMBLED TYPE: 6FX5002-2DC10 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP67, WITH 24 V MOTION-CONNECT 500 LENGTH (M) = 0 + 10 + 5 + 0	1	0
6SL3000-0BE28-0AA0	SIEMENS	SINAMICS LINE FILTER FOR 80 KW ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ	0	1
6SL3000-0BE28-0DA0	SIEMENS	SINAMICS BASIC LINE FILTER FOR 80KW ACTIVE LINE MODULE INPUT: 3-PH 380-480V, 50/60HZ	0	2
6SL3000-0BE32-5AA0	SIEMENS	SINAMICS/MICROMASTER PX LINE FILTER INPUT: 3AC 380-480 V, 50/60 HZ 250 A	0	1
6FX5002-5CS01-1AF0	SIEMENS	POWER CABLE, PREASSEMBLED TYPE: 6FX5002-5CS01 (1FT/1FK/1PH TO SINAMICS) 4X1.5 C, CONNECTOR SIZE 1/1.5 MM2 UL/CSA DESINA, MOTION-CONNECT 500 DMAX = 8.4 MM, LENGTH (M) = 0 + 0 + 5 + 0	1	0
6SL3000-0BE34-4AA0	SIEMENS	SINAMICS/MICROMASTER PX LINE FILTER INPUT: 3AC 380-480 V, 50/60 HZ 440 A	0	1
6FX5002-5CS51-1AF0	SIEMENS	POWER CABLE, PREASSEMBLED TYPE: 6FX5002-5CS51 (1FT/1FK TO SINAMICS) 4X6 C, CONNECTOR SIZE 1.5/6 MM2 UL/CSA DESINA, MOTION-CONNECT 500 DMAX = 15.9 MM, LENGTH (M) = 0 + 0 + 5 + 0	1	0
6SL3000-0BE36-0AA0	SIEMENS	SINAMICS/MICROMASTER PX LINE FILTER INPUT: 3AC 380-480 V, 50/60 HZ 600 A	0	1
6SL3000-0CE15-0AA0	SIEMENS	SINAMICS LINE REACTOR FOR 5 KW SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ	1	0
6SL3000-0CE21-0AA0	SIEMENS	SINAMICS LINE REACTOR FOR 10 KW SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ	0	3

## SINAMICS - dostępne komponenty

6SL3000-0CE21-6AA0	SIEMENS	SINAMICS LINE REACTOR FOR 16 KW SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ	2	1
6SL3000-0CE32-3AA0	SIEMENS	SINAMICS/MICROMASTER PX LINE REACTOR INPUT: 3AC 380-480 V, 50/60 HZ 224 A	3	1
6SL3000-0CE32-8AA0	SIEMENS	SINAMICS/MICROMASTER PX LINE REACTOR INPUT: 3AC 380-480 V, 50/60 HZ 278 A	2	0
6SL3000-0CE33-3AA0	SIEMENS	SINAMICS/MICROMASTER PX LINE REACTOR INPUT: 3AC 380-480 V, 50/60 HZ 331 A	1	0
6SL3000-0DE23-6AA0	SIEMENS	SINAMICS HFD LINE REACTOR FOR 36 KW ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60 HZ	0	1
6SL3000-0DE25-5AA1	SIEMENS	SINAMICS / SIMODRIVE HFD COMMUTATING REACTOR FOR 55KW ACTIVE LINE MODULE	3	0
6SL3000-0HE15-0AA0	SIEMENS	SINAMICS LINE FILTER FOR 5 KW SMART LINE MODULE INPUT: 3-PH. 380-480 V 50/60 HZ	0	2
6SL3000-0HE21-0AA0	SIEMENS	SINAMICS LINE FILTER FOR 10 KW SMART LINE MODULE INPUT: 3-PH. 380-480 V 50/60 HZ	0	1
6SL3040-0JA00-0AA0	SIEMENS	SINAMICS S110 CONTROL UNIT CU305 DP WITH PROFIBUS INTERFACE WITHOUT MEMORY CARD	0	+ 10
6SL3040-0JA01-0AA0	SIEMENS	SINAMICS S110 CONTROL UNIT CU305 PN WITH PROFINET INTERFACE WITHOUT MEMORY CARD	0	+ 10
6SL3040-0LA00-0AA0	SIEMENS	SINAMICS CONTROL UNIT CU310 DP WITH PROFIBUS INTERFACE WITHOUT COMPACTFLASH CARD	0	+ 10
6SL3040-0LA00-0AA1	SIEMENS	SINAMICS S120 CONTROL UNIT CU310 DP WITH PROFIBUS INTERFACE WITHOUT COMPACTFLASH CARD	0	+ 10
6SL3040-0LA01-0AA1	SIEMENS	SINAMICS S120 CONTROL UNIT CU310 PN WITH PROFINET INTERFACE WITHOUT COMPACTFLASH CARD	0	+ 10
6SL3040-0MA00-0AA1	SIEMENS	SINAMICS S120 CONTROL UNIT CU320 WITHOUT COMPACT FLASH CARD	0	+ 10
6FX8002-5CS01-1AG0	SIEMENS	POWER CABLE, PREASSEMBLED TYPE: 6FX8002-5CS01 4 X 1.5 C, CONNECTOR FULL THREAD SIZE 1 FOR SINAMICS S120 MOTOR MODULE MOTION-CONNECT 800PLUS TRAILING TYPE, UL/CSA DESINA DMAX = 9.5 MM, LENGTH (M) = 0 + 0 + 6 + 0	1	0
6SL3040-0NB00-0AA0	SIEMENS	SINAMICS NUMERIC CONTROL EXTENSION NX15 EXTENSION DRIVE CONTROL FOR SINUMERIK 840 D SL UP TO 6 AXES	0	+ 10
6SL3040-0NC00-0AA0	SIEMENS	SINAMICS NUMERIC CONTROL EXTENSION NX10 EXTENSION DRIVE CONTROL FOR SINUMERIK 840 D SL UP TO 3 AXES	0	+ 10
6SL3040-0PA00-0AA1	SIEMENS	CONTROL UNIT ADAPTER CUA31 FOR POWER MODULES PM340	+ 10	+ 10
6SL3040-0PA01-0AA0	SIEMENS	CONTROL UNIT ADAPTER CUA32 FOR POWER MODULES PM340 WITH INTERFACE FOR INCREMENTAL ENCODER HTL/TTL	0	+ 10
6SL3040-1LA00-0AA0	SIEMENS	SINAMICS S120 CONTROL UNIT CU310-2 DP WITH PROFIBUS INTERFACE WITHOUT COMPACTFLASH CARD	0	+ 10
6SL3040-1LA01-0AA0	SIEMENS	SINAMICS S120 CONTROL UNIT CU310-2 PN WITH PROFINET INTERFACE WITHOUT COMPACTFLASH CARD	0	+ 10
6SL3040-1MA00-0AA0	SIEMENS	SINAMICS S120 CONTROL UNIT CU320-2 DP WITH PROFIBUS INTERFACE WITHOUT COMPACT FLASH CARD.	0	+ 10
6SL3040-1MA01-0AA0	SIEMENS	SINAMICS S120 CONTROL UNIT CU320-2 PN WITHOUT COMPACT FLASH CARD	0	+ 10
6SL3040-1NB00-0AA0	SIEMENS	SINAMICS NUMERIC CONTR. EXTENSION NX15.3 EXTENSION DRIVE CONTROL FOR SINUMERIK 840 D SL SINUMERIK 828D UP TO 6 AXES	0	+ 10
6SL3053-0AA00-3AA0	SIEMENS	SINAMICS VOLTAGE SENSING MODULE VSM10 WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3053-0AA00-3AA1	SIEMENS	SINAMICS VOLTAGE SENSING MODULE VSM10	1	+ 10
6SL3054-0CD00-1AA0	SIEMENS	SINAMICS S120 COMPACTFLASH CARD WITHOUT PERFORMANCE EXTENSION INCLUDING CERTIFICATE OF LICENCE V2.03	0	1
6SL3054-0CD01-1AA0	SIEMENS	SINAMICS S120 COMPACTFLASH CARD WITH FIRMWARE OPTION PERFORMANCE EXTENSION 1 INCLUDING CERTIFICATE OF LICENCE V2.03	1	0

## SINAMICS - dostępne komponenty

6SL3054-0CE00-1AA0	SIEMENS	SINAMICS S120 COMPACTFLASH CARD W/O PERFORMANCE EXTENSION INCLUDING CERTIFICATE OF LICENCE V2.04	0	2
6SL3054-0CG00-1AA0	SIEMENS	SINAMICS S120 COMPACTFLASH CARD W/O PERFORMANCE EXTENSION INCLUDING CERTIFICATE OF LICENCE V2.6	0	1
6SL3054-0ED00-1BA0	SIEMENS	SINAMICS S120 COMPACTFLASH CARD W/O PERFORMANCE EXTENSION INCLUDING CERTIFICATE OF LICENCE V4.3	3	+ 10
6SL3054-0ED01-1BA0	SIEMENS	SINAMICS S120 COMPACTFLASH CARD WITH FIRMWARE OPTION PERFORMANCE-EXTENSION 1 INCLUDING CERTIFICATE OF LICENCE V4.3	1	0
6SL3054-4AG00-2AA0	SIEMENS	SINAMICS SD-CARD 512 MB EMPTY	8	0
6SL3055-0AA00-2CA0	SIEMENS	SINAMICS S120 COMMUNICATION BOARD CAN CBC10 FOR CONTROL UNIT CU320	0	+ 10
6SL3055-0AA00-2EB0	SIEMENS	SINAMICS S120 CBE20 PROFINET MODULE TO CONNECTION ON PROFINET IO WITH 4 RJ45 PORTS WITH SWITCH FUNCTIONALITY	+ 10	+ 10
6SL3055-0AA00-2TA0	SIEMENS	SINAMICS / SIMOTION TERMINAL BOARD TB30 FOR CONTROL UNIT CU320-X AND SIMOTION D4X5-X	0	+ 10
6SL3055-0AA00-3AA0	SIEMENS	SINAMICS TERMINAL MODULE CABINET TM31 WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-3AA1	SIEMENS	SINAMICS TERMINAL MODULE TM31 ADD ON BOARD FOR SINAMICS WITH DIGITAL AND ANALOG IN- AND OUTPUTS IP20 FOR CAP RAIL MOUNTING	0	+ 10
6SL3055-0AA00-3BA0	SIEMENS	SINAMICS S120 TERMINAL MODULE CABINET TM54F WITHOUT DRIVE-CLIQ CABLE ADD ON BOARD FOR SINAMICS CONVERTORS WITH FAIL-SAFE IN- AND OUTPUTS	0	+ 10
6SL3055-0AA00-3FA0	SIEMENS	SINAMICS TERMINAL MODULE TM15 24 DI/O; 24 V DC/0.5 A; WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-3HA0	SIEMENS	SINAMICS TERMINAL MODULE TM17 HIGH FEATURE; 16 DI/O; 24 V DC/0.5 A; WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-3PA0	SIEMENS	SINAMICS TERMINAL MODULE CABINET TM41 WITHOUT DRIVE-CLIQ CABLE	2	+ 10
6SL3055-0AA00-4CA0	SIEMENS	SINAMICS OPERATOR PANEL AOP30 ENGLISH / GERMAN CU320 SW V1.3; V2.1 NMA: A5E00118669	0	4
6SL3055-0AA00-4CA2	SIEMENS	SINAMICS OPERATION PANEL AOP30 ENGLISH / GERMAN FOR FIRMWARE V2.3	0	5
6SL3055-0AA00-4CA3	SIEMENS	SINAMICS OPERATOR PANEL AOP30 LANGUAGE INDEPENDENT FOR FIRMWARE FROM V2.4!	0	+ 10
6SL3055-0AA00-4CA4	SIEMENS	SINAMICS OPERATOR PANEL AOP30 LANGUAGE INDEPENDENT FOR FIRMWARE FROM V2.4!	0	+ 10
6SL3055-0AA00-4CA5	SIEMENS	SINAMICS OPERATOR PANEL AOP30 LANGUAGE INDEPENDENT WITH MEMORY EXTENTION FOR FIRMWARE FROM V2.4	0	+ 10
6SL3055-0AA00-5AA0	SIEMENS	SINAMICS SENSOR MODULE SMC10 RESOLVER WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-5AA3	SIEMENS	SINAMICS S120 SENSOR MODULE SMC10 SENSOR BOARD FOR EVALUATION OF A RESOLVER WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-5BA1	SIEMENS	SINAMICS SENSOR MODULE SMC20 INCREMENTAL ENCODER: SIN/COS 1VPP ABSOLUTE ENCODER: ENDAT WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-5BA2	SIEMENS	SINAMICS S120 SENSOR MODULE SMC20 INCREMENTAL ENCODER: SIN/COS 1VPP ABSOLUTE ENCODER: ENDAT WITHOUT DRIVE-CLIQ CABLE 30 MM WIDTH	0	+ 10
6SL3055-0AA00-5BA3	SIEMENS	SINAMICS S120 SENSOR MODULE SMC20 BOARD FOR EVALUATION OF INCREMENTAL ENCODER: SIN/COS 1VPP ABSOLUTE ENCODER: ENDAT WITHOUT DRIVE-CLIQ CABLE 30 MM WIDTH	1	+ 10
6SL3055-0AA00-5CA0	SIEMENS	SINAMICS SENSOR MODULE SMC30 INCREMENTAL ENCODER: TTL/HTL WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-5CA1	SIEMENS	SINAMICS SENSOR MODULE SMC30 INCREMENTAL ENCODER: TTL/HTL OR KOMBI ENCODER SSI WITH INCREMENTAL TRACES WITHOUT DRIVE-CLIQ CABLE	0	+ 10

## SINAMICS - dostępne komponenty

6SL3055-0AA00-5CA2	SIEMENS	SINAMICS SENSOR MODULE SMC30 FOR INCREMENTAL ENCODER: TTL/HTL OR KOMBI ENCODER SSI WITH INCREMENTAL TRACES OR KOMBI ENCODER SSI WITHOUT INCREMENTAL SIGNALS / WITHOUT DRIVE-CLIQ CABLE 30 MM WIDTH	0	+ 10
6SL3055-0AA00-5DA0	SIEMENS	SINAMICS S120 SENSOR MODULE SMC40 BOARD FOR EVALUATION OF ENDAT 2.2 ENCODER 30 MM WIDTH	0	+ 10
6SL3055-0AA00-5EA0	SIEMENS	SINAMICS SENSOR MODULE SME20 INCREMENTAL ENCODER: SIN/COS 1VPP PROTECTION IP67 WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-5HA0	SIEMENS	SINAMICS SENSOR MODULE SME25 ABSOLUTE ENCODER: ENDAT PROTECTION IP67	1	0
6SL3055-0AA00-5JA3	SIEMENS	SINAMICS SENSOR MODULE SME120 INCREMENTAL ENCODER: SIN/COS 1VPP; PTC- AND KTY-INPUTS WITH SECURE ELECTRICAL ISOLATION; DEGREE OF PROTECTION IP67; WITHOUT DRIVE-CLIQ CABLE	0	1
6SL3055-0AA00-5KA3	SIEMENS	SINAMICS SENSOR MODULE SME125 ABSOLUTE ENCODER: ENDAT; PTC- AND KTY-INPUTS WITH SECURE ELECTRICAL ISOLATION; DEGREE OF PROTECTION IP67; WITHOUT DRIVE-CLIQ CABLE	0	1
6SL3055-0AA00-6AA0	SIEMENS	SINAMICS SINAMICS DRIVE-CLIQ MODULE CABINET DMC20 WITHOUT DRIVE-CLIQ CABLE	0	+ 10
6SL3055-0AA00-6AB0	SIEMENS	SINAMICS DME20 DRIVE-CLIQ MODULE EXTERNAL IP67 WITHOUT 24V SUPPLY CABLE WITHOUT DRIVE-CLIQ CABLE	0	7
6SL3060-4AA10-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 0.95 M	+ 10	0
6SL3060-4AA50-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 5.0 M	7	0
6SL3060-4AB00-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 0.11 M	+ 10	+ 10
6SL3060-4AD00-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 0.16 M	+ 10	+ 10
6SL3060-4AF00-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 0.21 M	6	+ 10
6SL3060-4AF10-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 1.45 M	2	0
6SL3060-4AH00-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 0.26 M	7	5
6SL3060-4AK00-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 0.31 M	+ 10	4
6SL3060-4AU00-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 0.60 M	+ 10	4
6SL3060-4AW00-0AA0	SIEMENS	SINAMICS DRIVE-CLIQ CABLE IP20/IP20 LENGTH: 1.20 M	4	0
6SL3100-0BE21-6AB0	SIEMENS	SINAMICS S120 ACTIVE INTERFACE MODULE FOR 16KW ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ FRAME SIZE: BOOKSIZE	0	+ 10
6SL3100-0BE23-6AB0	SIEMENS	SINAMICS S120 ACTIVE INTERFACE MODULE FOR 36KW ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ FRAME SIZE: BOOKSIZE	0	4
6SL3100-0BE25-5AB0	SIEMENS	SINAMICS ACTIVE INTERFACE MODULE FOR 55KW ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ	0	+ 10
6SL3100-0BE28-0AB0	SIEMENS	SINAMICS ACTIVE INTERFACE MODULE FOR 80KW ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ	0	8
6SL3100-0BE31-2AB0	SIEMENS	SINAMICS ACTIVE INTERFACE MODULE FOR 120KW ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ	0	7
6SL3100-1AE31-0AB0	SIEMENS	SINAMICS BREAKING MODULE INPUT: 600 V DC OUTPUT: PEAK 100 KW/2 S	0	+ 10
6SL3100-1AE31-0AB1	SIEMENS	SINAMICS BREAKING MODULE INPUT: 600 V DC OUTPUT: PEAK 100 KW/2 S	1	10
6SL3100-1BE21-3AA0	SIEMENS	SINAMICS / SIMODRIVE HFD-RESISTOR 15 R 800 W FOR HFD-REACTOR	1	3
6SL3100-1CE14-0AA0	SIEMENS	SINAMICS CAPACITOR MODULE INPUT: 600 V DC 4000 UF	0	2
6SL3100-1DE22-0AA0	SIEMENS	SINAMICS CONTROL SUPPLY MODULE INPUT: 600 V DC/3-PH. 380-480 V 50/60 HZ OUTPUT: 26 V DC /-2%, 20 A	0	+ 10
6SL3100-1DE22-0AA1	SIEMENS	SINAMICS CONTROL SUPPLY MODULE INPUT: 600 V DC/3-PH. 380-480 V 50/60 HZ OUTPUT: 24..28.V DC +/-2%, 20 A	0	+ 10

## SINAMICS - dostępne komponenty

6RA8000-0MV62-0AA0	SIEMENS	SINAMICS DCM CONTROL MODULE WITHOUT POWER SECTION INCL 40A CONTROLLABLE FIELD RECTIFIER; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	2
6RA8025-6DS22-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR TWO-QUADRANT DRIVES CONNECTION B6C INPUT: 3-PHASE AC 400V, 50A CONTROLLABLE FIELD RECTIFIER D485/60 MRE-GEE6S22 OUTPUT: DC 485V, 60A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6RA8025-6DV62-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 50A CONTROLLABLE FIELD RECTIFIER D420/60 MREQ-GEG6V62 OUTPUT: DC 420V, 60A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6RA8028-6DS22-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR TWO-QUADRANT DRIVES CONNECTION B6C INPUT: 3-PHASE AC 400V, 75A CONTROLLABLE FIELD RECTIFIER D485/90 MRE-GEE6S22 OUTPUT: DC 485V, 90A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6SL3100-1VE00-0AA0	SIEMENS	SINAMICS VOLTAGE CLAMPING MODULE INPUT: 600 V DC	0	3
6RA8028-6FV62-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 480V, 75A CONTROLLABLE FIELD RECTIFIER D500/90 MREQ-GEG6V62 OUTPUT: DC 500V, 90A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6RA8078-6DV62-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 232A CONTROLLABLE FIELD RECTIFIER D420/280 MREQ-GEG6V62 OUTPUT: DC 420V, 280A ; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6SL3111-3VE21-6FA0	SIEMENS	SINAMICS S120 POWER MODULE INPUT: 3AC 400V 16KW OUTPUT: 3AC 400V, 18A, 5A, 5A FRAME SIZE: COMBI EXTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS	0	6
6RA8081-6DV62-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 332A CONTROLLABLE FIELD RECTIFIER D420/400 MREQ-GEG6V62 OUTPUT: DC 420V, 400A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	3
6SL3111-4VE21-6EA0	SIEMENS	SINAMICS S120 COMBI POWER MODULE INPUT: 3AC 400V, 16KW OUTPUT: 3AC 400V, 24A, 9A, 9A, 9A, FRAME SIZE: COMBI EXTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS	0	+ 10
6SL3111-4VE21-6FA0	SIEMENS	SINAMICS S120 COMBI POWER MODULE INPUT: 3AC 400V, 16KW OUTPUT: 3AC 400V, 18A,9A,5A,5A FRAME SIZE: COMBI EXTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS	0	5
6SL3111-4VE22-0HA0	SIEMENS	SINAMICS S120 COMBI POWER MODULE INPUT: 3AC 400V, 20KW OUTPUT: 3AC 400V,30A,12A,9A,9A FRAME SIZE: COMBI EXTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS	0	8
6SL3120-1TE13-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 3 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE13-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 3A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE13-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 3A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	1	3

## SINAMICS - dostępne komponenty

6SL3120-1TE13-0AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400V, 3A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	4
6SL3120-1TE15-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 5 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	2	+ 10
6SL3120-1TE15-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 5A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE15-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 5A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	7
6SL3120-1TE21-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3 AC 400 V, 9 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	+ 10
6SL3120-1TE21-0AA1	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 9 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE21-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 9A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE21-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 9A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	6
6SL3120-1TE21-8AA1	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 18 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE21-8AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE21-8AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	2
6SL3120-1TE23-0AA1	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 30 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE23-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 30A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE23-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 30A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	1	2
6SL3120-1TE24-5AA1	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 45 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	9
6SL3120-1TE24-5AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 45A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10

## SINAMICS - dostępne komponenty

6SL3120-1TE26-0AA1	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 60 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE26-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 60A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE28-5AA1	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 85 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE28-5AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 85A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE31-3AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 132 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	1	5
6SL3120-1TE31-3AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 132A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE32-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 200 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	10
6SL3120-1TE32-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 200A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-1TE32-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 200A OUTPUT: AT 8 KHZ / 140A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE- CLIQ CABLE	0	1
6SL3120-1VE21-8AA0	SIEMENS	SINAMICS S120 VALUE SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 18 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	1	5
6SL3120-2TE13-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 3 A/3 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE13-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A/3A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE13-0AA4	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A/3A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	4
6SL3120-2TE13-0AB0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 3A/3A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	10
6SL3120-2TE15-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 5 A/5 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE15-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A/5A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10

## SINAMICS - dostępne komponenty

6SL3120-2TE15-0AA4	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A/5A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	2
6SL3120-2TE21-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 9 A/9 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE21-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 9A/9A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE21-0AA4	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 9A/9A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE21-0AB0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 9A/9A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	+ 10
6SL3120-2TE21-8AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH 400 V, 18 A/18 A INTERNAL AIR-COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE21-8AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A/18A FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3120-2TE21-8AB0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400V, 18A/18A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	+ 10
6SL3120-2VE15-0AA0	SIEMENS	SINAMICS S120 VALUE DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 5 A/5 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	1	3
6SL3121-1TE21-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-1TE21-8AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-1TE21-8AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-1TE23-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 30 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-1TE24-5AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 45 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3121-1TE23-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 30A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-1TE24-5AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 45A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	4



## SINAMICS - dostępne komponenty

6SL3121-1TE26-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 60 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	1	10
6SL3121-1TE28-5AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 85A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3121-2TE15-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 5 A/5 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-2TE15-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A/5A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	6
6SL3121-2TE21-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 9 A/9 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	9
6SL3121-2TE21-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A/9A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-2TE21-8AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 18 A/18 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-2TE21-8AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A/18A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3126-1TE26-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 60 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3126-2TE15-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A/5A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3126-2TE15-0AA4	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A/5A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	5
6SL3126-2TE21-8AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A/18A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	1	10
6SL3130-1TE22-0AA0	SIEMENS	SINAMICS S120 BASIC LINE MODULE INPUT: 3PH 380-480V, 50/60HZ OUTPUT: DC 600V, 34 A, 20KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3130-1TE24-0AA0	SIEMENS	SINAMICS S120 BASIC LINE MODULE INPUT: 3PH 380-480V, 50/60HZ OUTPUT: DC 600V, 67 A, 40KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3130-1TE31-0AA0	SIEMENS	SINAMICS S120 BASIC LINE MODULE INPUT: 3PH 380-480V, 50/60HZ OUTPUT: DC 600V, 167 A, 100KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3130-6AE15-0AA0	SIEMENS	SINAMICS SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 8.3 A, 5 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER	0	+ 10

## SINAMICS - dostępne komponenty

6SL3130-6AE15-0AB0	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 600VDC, 8.3A, 5KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER MODULES PAINTED	0	+ 10
6SL3130-6AE21-0AB0	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 600VDC, 17A, 10KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER MODULES PAINTED	0	2
6SL3130-6TE21-6AA3	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 27A, 16KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3130-6TE21-6AB0	SIEMENS	SINAMICS SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 27 A, 16 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE PAINTED MODULE	0	+ 10
6SL3130-6TE23-6AA3	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 60A, 36KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3130-6TE23-6AB0	SIEMENS	SINAMICS SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 60 A, 36 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE PAINTED MODULE	0	7
6SL3130-7TE21-6AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 27 A, 16 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	+ 10
6SL3130-7TE21-6AA1	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 27 A, 16 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	+ 10
6SL3130-7TE21-6AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3-PH 380-480V, 50/60HZ OUTPUT: DC 600V, 27A, 16KW FRAME SIZE: BOOKSIZE INTERNE LUFTKUEHLUNG INKL. DRIVE-CLIQ LEITUNG	0	+ 10
6SL3130-7TE21-6AA4	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3-PH 380-480V, 50/60HZ OUTPUT: DC 600V, 27A, 16KW FRAME SIZE: BOOKSIZE INTERNE LUFTKUEHLUNG INKL. DRIVE-CLIQ LEITUNG	0	1
6SL3130-7TE21-6AB0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 600VDC, 27A, 16KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE MODULE PAINTED	0	9
6SL3130-7TE23-6AA1	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 60 A, 36 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	1
6SL3130-7TE23-6AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 60A, 36KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3130-7TE23-6AB0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 600V DC, 60A, 36KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE BOARD COATED	0	2
6SL3130-7TE25-5AA2	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 92 A, 55 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	+ 10
6SL3130-7TE25-5AB0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 600 V DC, 92A, 55KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE BOARD COATED	0	2
6SL3130-7TE28-0AA1	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 133 A, 80 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	+ 10

## SINAMICS - dostępne komponenty

6SL3130-7TE28-0AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 133A, 80KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3130-7TE31-2AA1	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 200 A, 120 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	5
6SL3130-7TE31-2AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 200A, 120KW FRAME SIZE: BOOKSIZE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	5
6SL3130-7VE21-6AA0	SIEMENS	SINAMICS S120 VALUE ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 27 A, 16 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	1
6SL3131-6AE15-0AA0	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 8.3 A, 5 KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	1
6SL3131-6AE21-0AA1	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 17 A, 10 KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	2
6SL3131-7TE21-6AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 27 A, 16 KW EXTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	+ 10
6SL3131-7TE23-6AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT:: DC 600V, 60A, 36KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3131-7TE25-5AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 92 A, 55 KW EXTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	10
6SL3131-7TE25-5AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 92A, 55KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3136-7TE28-0AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 133A, 80KW FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3161-0EP00-0AA0	SIEMENS	SINAMICS S120 COMBI EXTERNAL FAN UNIT INPUT: DC 20,4 - 28,8V POWER CONSUMPTION: 18W CURRENT CONSUMPTION: 0,8A VOLUMETRIC AIR FLOW: 290 CBM/H W:258MM, H:104MM, D:86MM	0	6
6SL3162-1AH00-0AA0	SIEMENS	SINAMICS SHIELD CONNECTION SHEET FOR 300 MM LINE/MOTOR MODULES	0	1
6SL3162-2AA01-0AA0	SIEMENS	SINAMICS REPLACEMENT 24-V PLUG-IN JUMPERS FOR MODULES IN BOOKSIZE DESIGN	+ 10	0
6SL3162-2BD00-0AA0	SIEMENS	SINAMICS DC LINK RECTIFIER ADAPTER FOR DIRECT INFEED SCREW TERMINALS 0.5-10 MM2 FOR 50 AND 100 MM LINE/MOTOR MODULES IN BOOKSIZE FORMAT	1	0
6SL3162-2BM00-0AA0	SIEMENS	SINAMICS DC LINK RECTIFIER ADAPTER FOR DIRECT INFEED SCREW TERMINALS 35-95 MM2 FOR 150, 200 AND 300 MM LINE/MOTOR MODULES IN BOOKSIZE FORMAT	0	6
6SL3162-2BM01-0AA0	SIEMENS	SINAMICS DC LINK ADAPTER SET FOR MULTI-TIER DESIGN SCREW TERMINALS 35-95 SQMM FOR ALL LINE/MOTOR MODULES IN BOOKSIZE FORMAT	+ 10	8
6SL3162-2MA00-0AA0	SIEMENS	SINAMICS S120 POWER CONNECTOR WITH SCREW TERMINALS FOR MOTOR MODULES 3-30 A FRAME SIZE: BOOKSIZE	5	+ 10
6SL3162-8AB00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT MOTOR MODULE 50MM	2	0

## SINAMICS - dostępne komponenty

6SL3201-0BE12-0AA0	SIEMENS	SINAMICS BRAKING RESISTOR FOR POWER MODULE FSB FOOT PRINT	0	1
6SL3201-0BE14-3AA0	SIEMENS	SINAMICS BRAKING RESISTOR R=370OHM P_RATED=75W P_MAX=1500W/12S/5% DUTY STANDALONE	3	0
6SL3201-0BE21-0AA0	SIEMENS	SINAMICS BRAKING RESISTOR R=140OHM P_RATED=200W P_MAX=4000W/12S/5% DUTY STANDALONE	+ 10	0
6SL3202-0AJ23-2CA0	SIEMENS	SINAMICS OUTPUT REACTOR FOR POWER MODULE FSC FOOT PRINT	8	+ 10
6SL3203-0CD21-0AA0	SIEMENS	SINAMICS LINE REACTOR FOR POWER MODULE FSB 2.2 AND 3,0 KW, FOOT PRINT	5	6
6SL3203-0CD21-4AA0	SIEMENS	SINAMICS LINE REACTOR FOR POWER MODULE FSB 4.0 KW, FOOT PRINT	+ 10	2
6SL3203-0CD22-2AA0	SIEMENS	SINAMICS LINE REACTOR FOR POWER MODULE FSC 7,5 AND 11 KW RATED POWER BASED ON I_L FOOT PRINT	1	5
6SL3203-0CD23-5AA0	SIEMENS	SINAMICS LINE REACTOR FOR POWER MODULE FSC 15 KW, RATED POWER BASED ON I_L FOOT PRINT	0	4
6SL3203-0CD25-3AA0	SIEMENS	SINAMICS LINE REACTOR FOR POWER MODULE FSD 30 KW, RATED POWER BASED ON I_L FOOT PRINT	0	4
6SL3203-0CJ24-5AA0	SIEMENS	SINAMICS LINE REACTOR FOR POWER MODULE FSD 18.5 AND 22 KW, RATED POWER BASED ON I_L FOOT PRINT	1	0
6SL3203-0CJ28-6AA0	SIEMENS	SINAMICS LINE REACTOR FOR POWER MODULE FSE 37 AND 45 KW, RATED POWER BASED ON I_L FOOT PRINT	2	4
6SL3210-1KE11-8UF1	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225,4(HXWXD) EXTER	0	2
6SL3210-1KE12-3AB1	SIEMENS	SINAMICS G120C RATED POWER 0,75KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: USS/ MODBUS RTU; PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X7	0	1
6SL3210-1KE12-3AP1	SIEMENS	SINAMICS G120C RATED POWER 0,75KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203	0	3
6SL3210-1KE14-3AF1	SIEMENS	SINAMICS G120C RATED POWER 1,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225,	0	1
6SL3210-1KE15-8AF1	SIEMENS	SINAMICS G120C RATED POWER 2,2KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225	0	1
6SL3210-1KE15-8UF1	SIEMENS	SINAMICS G120C RATED POWER 2,2KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225,4(HXWXD) EXTERN	0	3
6SL3210-1KE18-8AF1	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225,	0	1

## SINAMICS - dostępne komponenty

6SL3210-1KE18-8AP0	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(	0	7
6SL3210-1KE18-8AP1	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203	+ 10	1
6SL3210-1KE18-8UP1	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD) EXTERNA	0	1
6SL3210-1KE21-3AF1	SIEMENS	SINAMICS G120C RATED POWER 5,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203	0	1
6SL3210-1KE23-2UP0	SIEMENS	SINAMICS G120C RATED POWER 15,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X203(HXWXD)	0	1
6SL3210-1KE23-8AP1	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X2	0	1
6SL3210-1KE23-8UB0	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X203(HXWXD)	0	5
6SL3210-1KE23-8UP0	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X203(HXWXD)	0	8
6SL3210-1NE17-7UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 3KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND PANEL APPROVED FOR C	0	2
6SL3210-1PE16-1AL1	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP. -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 2,2KW AT 150% 3S,110% 5	+ 10	5
6SL3210-1SB11-0AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 1AC 200-240V, 50/60HZ OUTPUT: 3AC 0,9A (0,12KW) FRAME SIZE: BLOCKSIZE SIZE FSA WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	3
6SL3210-1SB11-0UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 1AC 200-240V, 50/60HZ OUTPUT: 3AC 0,9A (0,12KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	0	7

## SINAMICS - dostępne komponenty

6SL3210-1SB14-0AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 1AC 200-240V, 50/60HZ OUTPUT: 3AC 3,9A (0,75KW) FRAME SIZE: BLOCKSIZE SIZE FSA WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	9
6SL3210-1SB14-0UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 1AC 200-240V, 50/60HZ OUTPUT: 3AC 3,9A (0,75KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	0	+ 10
6SL3210-1SE11-3UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 1,3A (0,37KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	0	6
6SL3210-1SE11-7UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 1,7A (0,55KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	0	1
6SL3210-1SE12-2UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 2,2A (0,75KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	0	5
6SL3210-1SE13-1UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 3,1A (1,1KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	0	4
6SL3210-1SE14-1UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 4,1A (1,5KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	0	6
6SL3210-1SE16-0UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 5,9A (2,2KW) FRAME SIZE: BLOCKSIZE SIZE FSB INTERNAL AIR COOLING	0	1
6SL3210-1SE21-8UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 18A (7,5KW) FRAME SIZE: BLOCKSIZE SIZE FSC INTERNAL AIR COOLING	0	4
6SL3210-1SE22-5AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 25A (11KW) FRAME SIZE: BLOCKSIZE SIZE FSC WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	3
6SL3210-1SE22-5UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 25A (11KW) FRAME SIZE: BLOCKSIZE SIZE FSC INTERNAL AIR COOLING	0	10
6SL3210-1SE23-2UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 32A (15KW) FRAME SIZE: BLOCKSIZE SIZE FSC INTERNAL AIR COOLING	0	1
6SL3210-1SE23-8AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 38A (18,5KW) FRAME SIZE: BLOCKSIZE SIZE FSD WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	2
6SL3210-1SE23-8UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 38A (18,5KW) FRAME SIZE: BLOCKSIZE SIZE FSD INTERNAL AIR COOLING	0	3
6SL3210-1SE24-5AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 45A (22KW) FRAME SIZE: BLOCKSIZE SIZE FSD WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	1
6SL3210-1SE26-0AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 60A (30KW) FRAME SIZE: BLOCKSIZE SIZE FSD WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	2
6SL3210-1SE27-5UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 75A (37KW) FRAME SIZE: BLOCKSIZE SIZE FSE INTERNAL AIR COOLING	3	1

## SINAMICS - dostępne komponenty

6SL3210-1SE31-0AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 90A (45KW) FRAME SIZE: BLOCKSIZE SIZE FSE WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	2
6SL3210-1SE31-1UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 110A (55KW) FRAME SIZE: BLOCKSIZE SIZE FSF INTERNAL AIR COOLING	0	5
6SL3210-1SE31-8AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 178A (90KW) FRAME SIZE: BLOCKSIZE SIZE FSF WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	5
6SL3210-5BB13-7AV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,37KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C2 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X150X146(WXHxD)	0	1
6SL3210-5BB21-1UV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 1,1KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSB 140X160X165(HXWXD)	0	5
6SL3210-5BB21-5AV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 1,5KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C2 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSB 140X160X165(WXHxD)	0	1
6SL3210-5BB23-0UV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 3,0 KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSC 184X182X169(WXHxD)	0	5
6SL3210-5BE13-7UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 0.37KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X150X146(HXWXD)	0	1
6SL3210-5BE22-2UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 2.2KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X166X146(WXHxD)	0	10
6SL3210-5BE24-0UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 4KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSB 140X160X165(WXHxD)	0	+ 10
6SL3210-5CC14-0UA0	SIEMENS	SINAMICS V60 CONTROLLED POWER MODULE CPM60.1 INPUT: 3AC 220-240V 50/60HZ OUTPUT: 3AC 4A (0,8 KW)	0	8
6SL3210-5FE11-0UA0	SIEMENS	SINAMICS V90 INPUT: 3AC 380-480V -15%/+10% 3.8A 45- 66HZ OUTPUT: 0-INPVT V 3.0A 0-330HZ PROTECTION: IP20 MOTOR:0.75/1.0KW FRAME SIZE A, 80X180X200(WXHxD)	0	5
6SL3210-5FE15-0UA0	SIEMENS	SINAMICS V90 NPUT: 3AC 380-480V -15%/+10% 15.8A 45- 66HZ OUTPUT: 0-INPVT V 1.2A 0-330HZ MOTOR: 5.0KW PROTECTION: IP20 FRAME SIZE C 140X260X240 (WXHxD)	0	2

## SINAMICS - dostępne komponenty

6SL3211-0AB11-2BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.12KW; VT: 0.12KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	+ 10
6SL3211-0AB12-5UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.25KW; VT: 0.25KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	+ 10
6SL3211-0AB12-5UB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS- PROTOCOL) CT: 0.25KW; VT: 0.25KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT ANALOG I	0	2
6SL3211-0AB13-7BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.37KW; VT: 0.37KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	1	+ 10
6SL3211-0AB13-7UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.37KW; VT: 0.37KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	4
6SL3211-0AB17-5BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	+ 10
6SL3211-0AB17-5BB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS- PROTOCOL) CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT AN	9	7
6SL3211-0AB17-5UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	+ 10	0
6SL3211-0AB21-1AA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. A FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 1.1KW; VT: 1.1KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	+ 10
6SL3211-0AB21-5AA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. A FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 1.5KW; VT: 1.5KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	+ 10
6SL3211-0AB21-5UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 1.5KW; VT: 1.5KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	10
6SL3211-0AB22-2AA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. A FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 2.2KW; VT: 2.2KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	+ 10



## SINAMICS - dostępne komponenty

6SL3211-0AB23-0AA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. A FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 3.0KW; VT: 3.0KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	5
6SL3211-0AB23-0UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 3.0KW; VT: 3.0KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	2
6SL3211-0KB17-5BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXD) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +40 DEG C WITHOUT	0	6
6SL3223-0DE27-5AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO+40 DEG C (LO) 540 X 180 X 249 (HXBXT), FSB WITHOUT CONTR	0	2
6SL3223-0DE31-8AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 620 X 230 X 249 (HXBXT), FSC WITHOUT CONT	2	0
6SL3223-0DE33-7AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 37KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 751 X 320 X 329 (HXBXT), FSE WITHOUT CONTROL UNIT A	0	2
6SL3224-0BE13-7UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 173 X 73 X 145 (HXWXD), FSA PROTECTION IP20 WITHOUT CO	0	+ 10
6SL3224-0BE15-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,55KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 173 X 73 X 145 (HXWXD), FSA PROTECTION IP20 WITHOUT CO	0	+ 10
6SL3224-0BE17-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,75KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 173 X 73 X 145 (HXWXD), FSA PROTECTION IP20 WITHOUT CO	0	+ 10
6SL3224-0BE21-1UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,1KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 173 X 73 X 145 (HXWXD), FSA PROTECTION IP20 WITHOUT CON	0	4
6SL3224-0BE21-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 173 X 73 X 145 (HXWXD), FSA PROTECTION IP20 WITHOUT CON	0	+ 10

## SINAMICS - dostępne komponenty

6SL3224-0BE22-2AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 2,2KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 270 X 153 X 165 (HXWXD), FSB PROTECTION IP2	0	1
6SL3224-0BE22-2UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 2,2KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 270 X 153 X 165 (HXWXD), FSB PROTECTION IP20 WITHOUT CO	0	8
6SL3224-0BE23-0AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3,0KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 270 X 153 X 165 (HXWXD), FSB PROTECTION IP2	0	1
6SL3224-0BE23-0UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3,0KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 270 X 153 X 165 (HXWXD), FSB PROTECTION IP20 WITHOUT CO	0	5
6SL3224-0BE24-0AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4,0KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 270 X 153 X 165 (HXWXD), FSB PROTECTION IP2	0	2
6SL3224-0BE24-0UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4,0KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C 270 X 153 X 165 (HXWXD), FSB PROTECTION IP20 WITHOUT CO	0	+ 10
6SL3224-0BE25-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 5,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 7,5KW FOR 150% 3S,11	3	+ 10
6SL3224-0BE25-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 5,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100%	0	+ 10
6SL3224-0BE27-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 11KW FOR 150% 3S,110	0	+ 10
6SL3224-0BE27-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 11KW FOR 150% 3S,110% 57S,100% 2	0	+ 10
6SL3224-0BE31-1AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 15KW FOR 150% 3S,110%	0	10

## SINAMICS - dostępne komponenty

6SL3224-0BE31-1UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 15KW FOR 150% 3S,110% 57S,100% 24	0	+ 10
6SL3224-0BE31-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 150% 3S,110%	0	3
6SL3224-0BE31-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 24	+ 10	5
6SL3224-0BE32-2AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 30KW FOR 150% 3S,110% 5	1	+ 10
6SL3224-0BE32-2UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 30KW FOR 150% 3S,110% 57S,100% 240S	0	2
6SL3224-0BE33-0AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 37KW FOR 150% 3S,110% 5	0	3
6SL3224-0BE33-7AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 45KW FOR 150% 3S,110% 5	0	+ 10
6SL3224-0BE38-8UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 90KW FOR 160% 3S,136% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 110KW FOR 150% 3S,110% 57S,100% 240	0	5
6SL3224-0BE41-1UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 110KW FOR 160% 3S,136% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 132KW FOR 150% 3S,110% 57S,100% 24	0	3
6SL3225-0BE25-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 5,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO 50 DEG C OUTPUT LIGHT OVERLOAD: 7,5KW FOR 150% 3S,110%	0	+ 10
6SL3225-0BE25-5AA1	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 5,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 7,5KW FOR 150% 3S,110%	1	+ 10

## SINAMICS - dostępne komponenty

6SL3225-0BE27-5AA1	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 11KW FOR 150% 3S,110% 5	0	9
6SL3225-0BE31-1AA1	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 15KW FOR 150% 3S,110% 57	0	+ 10
6SL3225-0BE31-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 150% 3S,110%	9	+ 10
6SL3225-0BE31-8AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 18,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 22KW FOR 150% 3S,110%	0	4
6SL3225-0BE32-2AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 30KW FOR 150% 3S,110% 57	0	+ 10
6SL3225-0BE33-0AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 37KW FOR 150% 3S,110% 57	2	+ 10
6SL3225-0BE33-7AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 45KW FOR 150% 3S,110% 57	0	+ 10
6SL3225-0BE34-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 55KW FOR 150% 3S,110% 57	0	3
6SL3225-0BE35-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 55KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 75KW FOR 150% 3S,110% 57	0	1
6SL3225-0BE37-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 75KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 90KW FOR 150% 3S,110% 57	0	2
6SL3225-0BH31-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC660-690V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO 50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 140% 3S,110% 57S,100% 240	0	1

## SINAMICS - dostępne komponenty

6SL3225-0BH31-5UA1	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC500-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 140% 3S,110% 57S,100% 2	0	2
6SL3225-0SE17-5UA0	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 65 MM 3AC380-480V 10/- 15% 47-63HZ POWER 0.75 KW / 1.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	+ 10
6SL3225-0SE17-5UA1	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 65 MM 3AC380-480V 10/- 15% 47-63HZ POWER 0.75 KW / 1.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	+ 10
6SL3225-0SE17-5UA2	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 65 MM 3AC380-480V +10/- 15% 47-63HZ POWER 0.75 KW / 1.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	9
6SL3225-0SE22-2UA0	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 130 MM 3AC380-480V 10/- 15% 47-63HZ POWER 2.2 KW / 3.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	1	+ 10
6SL3225-0SE22-2UA1	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 130 MM 3AC380-480V 10/- 15% 47-63HZ POWER 2.2 KW / 3.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	+ 10
6SL3225-0SE24-0UA0	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 130 MM 3AC380-480V 10/- 15% 47-63HZ POWER 4.0 KW / 5.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	+ 10
6SL3225-0SE24-0UA1	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 130 MM 3AC380-480V 10/- 15% 47-63HZ POWER 4.0 KW / 5.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	+ 10
6SL3225-0SE24-0UA2	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 130 MM 3AC380-480V +10/-15% 47-63HZ POWER 4.0 KW / 5.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	1
6SL3225-0SE24-0UA3	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONVERTER POWER MODULE IPM25 MODULE WIDTH 130 MM 3AC380-480V +10/-15% 47-63HZ POWER 4.0 KW / 5.0 HP OVERLOAD 150% 60S, 200% 3S POWER RECOVERY EXPANDABLE WITH BRAKE CONTROL MODULE OPTION: EXT. EMC-FILTER (CL. A)	0	1
6SL3235-0TE21-1SB0	SIEMENS	FREQ. CONVERTER FOR ET 200PRO WITH FAIL-SAFE FUNCTIONS MODULE WIDTH 155 MM 3AC380-480V 10/- 10% 47-63HZ POWER 1.1KW/1.5HP(0... 55 DEG) POWER 1.5KW/2.0HP(0... 45 DEG) OVERLOAD 150% 60S, 200% 3S POWER RECOVERY WITH BRAKE CONTROL DC180V WITH EMC-FILTER	0	3

## SINAMICS - dostępne komponenty

6SL3243-0BB30-1HA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 HVAC USS/ MODBUS RTU/BACNET MS/TP 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	+ 10
6SL3243-0BB30-1HA2	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 HVAC USS/ MODBUS RTU/BACNET MS/TP 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	2	+ 10
6SL3243-0BB30-1HA3	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 HVAC USS/ MODBUS RTU/BACNET MS/TP 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	8
6SL3243-0BB30-1PA2	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 DP INTEGRATED PROFIBUS DP 6 DI, 3 , DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 , PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20,	+ 10	+ 10
6SL3244-0BA10-0BA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E, E-TYPE STANDARD RS485-INTERFACE, USS-PROTOCOL 6 DI, 3 DO, 2 AI, 2 AO PTC/KTY INTERFACE EM-BRAKE RELAY, PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT POWER MODULE AND BOP	+ 10	+ 10
6SL3244-0BA20-1BA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240S S-TYPE STANDARD RS485-INTERFACE, USS-PROTOCOL 9 DI, 3 DO, 2 AI, 2 AO PTC/KTY INTERFACE EM-BRAKE RELAY, MMC INTERFACE ENCODER INTERFACE PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT POWER MODULE AND BOP	2	+ 10
6SL3244-0BA20-1FA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240S PN S-TYPE STANDARD PROFINET 9 DI, 4 DO, 2 AI, 2 AO PTC/KTY INTERFACE EM-BRAKE RELAY, MMC INTERFACE ENCODER INTERFACE PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT POWER MODULE AND BOP	0	+ 10
6SL3244-0BA20-1PA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240S DP S-TYPE STANDARD PROFIBUS DP 9 DI, 3 DO, 2 AI, 2 AO PTC/KTY INTERFACE EM-BRAKE RELAY, MMC INTERFACE ENCODER INTERFACE PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT POWER MODULE AND BOP	0	+ 10
6SL3244-0BA21-1PA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240S DP-F S-TYPE SAFETY INTEGRATED PROFIBUS DP 8 DI, 3 DO, 2 AI, 2 AO PTC/KTY INTERFACE EM-BRAKE RELAY, MMC INTERFACE ENCODER INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO 45 DEG C WITHOUT POWER MODULE AND BOP	0	6
6SL3244-0BB00-1BA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU240B-2 B-TYPE RS485-INTERFACE WITH USS-/MODBUS RTU-PROTOCOL 4 DI, 1 DO, 1 AI, 1 AO PTC/KTY/THERMOCLICK INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	0	+ 10
6SL3244-0BB00-1PA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240B-2 DP B-TYPE PROFIBUS DP 4 DI, 1 DO, 1 , AI, 1 AO PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 , AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	6	5
6SL3244-0BB00-1PA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU240B-2 DP B-TYPE PROFIBUS DP 4 DI, 1 DO, 1 AI, 1 AO PTC/KTY/THERMOCLICK INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	0	+ 10
6SL3244-0BB12-1BA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 E-TYPE SAFETY INTEGRATED STO RS485-INTERFACE, USS-PROTOCOL 6DI, 3DO, 2AI, 2AO, MAX 1F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO 50 DEG C WITHOUT POWER MODULE AND PANEL	0	+ 10

## SINAMICS - dostępne komponenty

6SL3244-0BB12-1BA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 E-TYPE SAFETY INTEGRATED STO RS485-INTERFACE, USS-PROTOCOL 6DI, 3DO, 2AI, 2AO, MAX 1F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	1	+ 10
6SL3244-0BB12-1FA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 PN E-TYPE SAFETY INTEGRATED STO PROFINET 6DI, 3DO, 2AI, 2AO, MAX 1F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	0	+ 10
6SL3244-0BB12-1PA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 DP E-TYPE SAFETY INTEGRATED STO PROFIBUS DP 6DI, 3DO, 2AI, 2AO, MAX 1F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	0	+ 10
6SL3244-0BB13-1FA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 PN-F E-TYPE SAFETY INTEGRATED STO, SS1, SLS, PROFINET 6DI, 3DO, 2AI, 2AO, MAX 3F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	0	+ 10
6SL3244-0BB13-1PA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 DP-F E-TYPE SAFETY INTEGRATED STO, SS1, SLS, PROFIBUS DP 6DI, 3DO, 2AI, 2AO, MAX 3F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	+ 10	+ 10
6SL3244-0SA00-1AA1	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONTROL UNIT MODULE WIDTH 15 MM COMBINEABLE WITH CONVERTER POWER MODULE IPM25 CONTROL METHODS: U/F,FCC,SLVC, VC WITH ENCODER, TORQUE CONTROL INPUT MOTOR ENC.: HTL UNIPOLAR INPUT MOTOR TEMP.: PTC/KTY RS232: START-UP-TOO	0	+ 10
6SL3244-0SA01-1AA0	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONTROL UNIT SAFETY INTEGRATED MODULE WIDTH 15 MM COMBINEABLE WITH CONVERTER POWER MODULE IPM25 CONTROL METHODS: U/F,FCC,SLVC, VC WITH ENCODER, TORQUE CONTROL INPUT MOTOR ENC.: HTL UNIPOLAR INPUT MOTOR TEMP.: PTC/KTY R	0	+ 10
6SL3244-0SA01-1AA1	SIEMENS	FREQUENCY CONVERTER FOR ET 200S CONTROL UNIT SAFETY INTEGRATED MODULE WIDTH 15 MM COMBINEABLE WITH CONVERTER POWER MODULE IPM25 CONTROL METHODS: U/F,FCC,SLVC, VC WITH ENCODER, TORQUE CONTROL INPUT MOTOR ENC.: HTL UNIPOLAR INPUT MOTOR TEMP.: PTC/KTY R	2	+ 10
6SL3246-0BA22-1FA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU250S-2 PN INTEGRIERT PROFINET SUPPORT OF VECTOR CONTROL, EASY POSITIONING EPOS VIA EXTENDED FUNCTION LICENSE 4 CONFIGURABLE DI/DO, 6 DI (USABLE AS 3 F-DI), 5 DI, 3 DO (USABLE AS 1 F-DO), 2 AI, 2 AO SAFETY INTEGRATED STO,	0	+ 10
6SL3246-0BA22-1PA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU250S-2 DP INTEGRIERT PROFIBUS SUPPORT OF VECTOR CONTROL, EASY POSITIONING EPOS VIA EXTENDED FUNCTION LICENSE 4 CONFIGURABLE DI/DO, 6 DI (USABLE AS 3 F-DI), 5 DI, 3 DO (USABLE AS 1 F-DO), 2 AI, 2 AO SAFETY INTEGRATED STO,	0	+ 10
6SL3252-0BB01-0AA0	SIEMENS	SINAMICS SAFE BRAKE RELAY FOR POWER MODULE WITH SINAMICS S120 APPROVED FROM V2.6	3	0
6SL3255-0AA00-2AA1	SIEMENS	SINAMICS G110 / G120 PC-INVERTER CONNECTION KIT 3M RS232 STANDARD CABLE AND ONE 9-PIN SUB-D CONNECTOR FOR G110 AND G120 CONTROL UNITS CU240E, CU240S	3	1
6SL3255-0AA00-4BA0	SIEMENS	SINAMICS G110 BASIC OPERATOR PANEL (BOP)	1	10
6SL3255-0AA00-4BA1	SIEMENS	SINAMICS G110 BASIC OPERATOR PANEL (BOP)	+ 10	+ 10
6SL3255-0AA00-4CA1	SIEMENS	SINAMICS G120 BASIC OPERATOR PANEL (BOP-2)	0	9
6SL3255-0AA00-4JA0	SIEMENS	SINAMICS G120 INTELLIGENT OPERATOR PANEL(IOP)	0	9

## SINAMICS - dostępne komponenty

6SL3255-0AA00-4JA1	SIEMENS	SINAMICS G120 INTELLIGENT OPERATOR PANEL IOP OPTIONAL OPERATOR PANEL FOR SINAMICS G120, G120P, G110M, G110D, G120D, G120C, S110, ET200S FC, ET200PRO FC LANGUAGE SUPPORT: GERMAN, ENGLISH, FRENCH, ITALIAN, SPANISH, PORTUGUESE, DUTCH, SWEDISH, RUSSIAN,	6	+ 10
6SL3260-2TA00-0AA0	SIEMENS	BACKPLANE BUS MODULE 155MM FOR ET 200PRO FREQ. CONVERTER	1	4
6SL3262-1AA00-0BA0	SIEMENS	SINAMICS SCREENING KIT FOR POWER MODULE FSA PM240	1	0
6SL3262-1AB00-0DA0	SIEMENS	SINAMICS SCREENING KIT FOR POWER MODULE FSB PM240	1	0
6SL3262-1AC00-0DA0	SIEMENS	SINAMICS SCREENING KIT FOR POWER MODULE FSC PM240 AND PM250	2	0
6SL3300-7TE32-6AA0	SIEMENS	SINAMICS ACTIVE INTERFACE MODULE FOR 3AC 380-480V, 50/60HZ 132 KW AND 160 KW ACTIVE LINE MODULE INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	1	2
6SL3300-7TE33-8AA0	SIEMENS	SINAMICS ACTIVE INTERFACE MODULES FOR 3-PH 380-480 V, 50/60 HZ 235 KW ACTIVE LINE MODULE INTERNAL AIR COOLING	0	+ 10
6SL3320-1TE32-1AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULES INPUT: 600 V DC OUTPUT: 3-PH 400 V, 210 A FRAME SIZE: CHASSIS INTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	1	2
6SL3320-1TE32-6AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULES INPUT: 600 V DC OUTPUT: 3-PH 400 V, 260 A FRAME SIZE: CHASSIS INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	7
6SL3320-1TE33-1AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULES INPUT: 600 V DC OUTPUT: 3-PH 400 V, 310 A FRAME SIZE: CHASSIS INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	1	3
6SL3320-1TE38-4AA3	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: DC 510 - 720V OUTPUT: 3AC 0 - 480V, 840A RATED POWER: 450KW CHASSIS UNIT IP00 INTERNAL AIR COOLING INCL. DRIVE- CLIQ CABLE	0	1
6SL3325-1TG41-3AA3	SIEMENS	SINAMICS S120 MOTOR MODULE INPUT: DC 675 - 1035V OUTPUT: 3AC 500-690V, 50/60HZ, 1270A, RATED POWER: 1200KW CHASSIS UNIT IP00 LIQUID COOLING	0	4
6SL3330-7TE32-1AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3-PH 380- 480V, 50/60HZ OUTPUT: 600 V DC, 235 A, 132 KW INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	4
6SL3330-7TE33-8AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3-PH 380-480V, 50/60HZ OUTPUT: 600 V DC, 390 A, 235 KW INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	2	5
6SL3330-7TE33-8AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3-PH 380- 480V, 50/60HZ OUTPUT: 600 V DC, 425 A, 235 KW INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3350-6TK00-0EA0	SIEMENS	SINAMICS SPARE PART CONTROL INTERFACE MODULE (CIM) FOR AIRCOOLED DRIVES	0	+ 10
6SL3351-1AE32-1AA1	SIEMENS	SINAMICS/MICROMASTER PX REPLACEMENT POWER BLOCK FOR 3AC 380-480 V, 50/60 HZ, 210 A AC DRIVE/POWER MODULES RECTIFIER AND 3 PHASES	0	1
6SL3351-1AE32-6AA1	SIEMENS	SINAMICS/MICROMASTER PX SPARE POWER BLOCK FOR 3PH. 380-480 V, 50/60 HZ, 260 A AC DRIVE/POWER MODULES RECTIFIER AND 3 PHASES	0	3
6SL3351-1AE32-6AA2	SIEMENS	SINAMICS/MICROMASTER PX REPLACEMENT POWER BLOCK FOR 3AC 380-480 V, 50/60 HZ, 260 A AC DRIVE/POWER MODULES RECTIFIER AND 3 PHASES	0	1
6SL3351-3AE33-1DB0	SIEMENS	SINAMICS G150 REPLACEMENT IPD	0	2
6SL3351-3AH38-1DB0	SIEMENS	SINAMICS G150 REPLACEMENT IPD	0	1
6SL3352-1AE32-6AA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR DC 510-750V, 260A MOTOR MODULE 3 PHASES BOARD COATED AND NICKEL-PLATED BUSBAR	0	1
6SL3352-1AE38-4CA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR DC 510-750V, 840A	0	1



## SINAMICS - dostępne komponenty

6SL3352-1AE38-4EA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR DC 510-750V, 840A	0	1
6SL3352-1AE41-4FA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR DC 510-750V, 1405A	0	1
6SL3352-1AG41-3FA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR DC 675-1035V, 1270A MOTOR MODULE U OR V OR W PHASE VARNISHED ASSEMBLIES AND NICKEL-PLATED CONDUCTOR BAR	0	+ 10
6SL3352-6BE00-0AA0	SIEMENS	SINAMICS/MICROMASTER PX REPLACEMENT POWER SUPPLY FOR 3AC 380-480 V, 50/60 HZ AC DRIVE/POWER/MOTOR MODULE	0	4
6SL3352-6BE00-0AA1	SIEMENS	SINAMICS/MICROMASTER PX REPLACEMENT POWER SUPPLY FOR 3AC 380-480V, 50/60HZ AC DRIVE/POWER/MOTOR MODULE PLEASE ORDER SPARE PART IN CASE OF REPAIR;DEFECT PART AS CREDIT	0	+ 10
6SL3352-6BH00-0AA1	SIEMENS	SINAMICS REPLACEMENT POWER SUPPLY FOR 3AC 500-690V, 50/60HZ AC DRIVE/POWER/MOTOR MODULE	0	7
6SL3352-6TG33-3AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 500-690V, 50/60HZ, 330A MOTOR MODULE	0	1
6SL3352-6TG35-8AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 500-690V, 50/60HZ, 575A MOTOR MODULE	0	1
6SL3353-1AE41-3FA0	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR 3AC 380-480V, 50/60HZ, 1300A SMART LINE MODULE RECTIFIER VARNISHED ASSEMBLIES AND NICKEL-PLATED CONDUCTOR BAR	0	3
6SL3420-2TE11-7AA0	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 1,7A/1,7A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	2
6SL3420-2TE13-0AA0	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A/3A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3420-2TE13-0AA1	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A/3A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	1	2
6SL3420-2TE15-0AA0	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A/5A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	6
6SL3420-2TE15-0AA1	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A/5A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3430-6TE21-6AA0	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 27A, 16KW FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	5
6SL3511-1PE17-5AM0	SIEMENS	SINAMICS G110D AC-DRIVE, WITH REPAIR SWITCH WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER WITH AS-INTERFACE BUS INTERFACE 3AC380-500V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,75KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +40 DEG C	0	3
6SL3511-1PE23-0AM0	SIEMENS	SINAMICS G110D AC-DRIVE, WITH REPAIR SWITCH WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER WITH AS-INTERFACE BUS INTERFACE 3AC380-500V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3,0KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +40 DEG C	0	1

## SINAMICS - dostępne komponenty

6SL3525-0PE17-5AA0	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,75KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO 40 DEG C 210 X 450 X 110 (HXWXD), FSA PROTECTION IP6	0	+ 10
6SL3525-0PE17-5AA1	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,75KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +55 DEG C 210 X 450 X 110 (HXWXD), FSA PROTECTION I	0	8
6SL3525-0PE21-5AA1	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +55 DEG C 210 X 450 X 110 (HXWXD), FSA PROTECTION IP	2	+ 10
6SL3525-0PE24-0AA1	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4,0KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +55 DEG C 210 X 450 X 220 (HXWXD), FSC PROTECTION IP	0	10
6SL3544-0FA20-1FA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU240D PN PROFINET 6 DI, 2 DO PTC/KTY INTERFACE EM-BRAKE CONTROL, MMC INTERFACE ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP -10 TO 55 DEG C WITHOUT POWER MODULE	0	+ 10
6SL3544-0FA20-1PA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU240D DP PROFIBUS DP 6 DI, 2 DO PTC/KTY INTERFACE EM-BRAKE CONTROL, MMC INTERFACE ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP -10 TO 55 DEG C WITHOUT POWER MODULE	0	2
6SL3544-0FA21-1PA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU240D DP-F PROFIBUS AND SAFETY INTEGRATED 6 DI, 2 DO PTC/KTY INTERFACE EM-BRAKE CONTROL, MMC INTERFACE ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP 0 TO 40 DEG C WITHOUT POWER MODULE	0	+ 10
6SL3544-0FB21-1FA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU240D-2 PN-F PROFINET AND SAFETY INTEGRATED 6 DI/3 F-DI, 2 DO/1 F-DO, 2 AI USB INTERFACE SD/MMC-INTERFACE HTL-ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE	0	1
6SL3555-0PL00-2AA0	SIEMENS	SINAMICS G110D MANUAL-LOCAL-KEYSWITCH	0	1
6SL3760-1AA00-0AA0	SIEMENS	VENTILATION GRILL FOR CABINET SPARE PART FOR CABINET UNIT SINAMICS G150 / S150 S120 CABINET MODULE NMA: A5E00147053	0	+ 10
6SL3995-6AX00-0AA0	SIEMENS	POWERSTACKADAPTER PSA FOR SINAMICS	0	1
6SL3995-6LX00-0AA0	SIEMENS	AVT COMBI FOR SINAMICS MEDIUM-VOLTAGE CONVERTERS	0	1
6SN1111-0AA00-0DV0	SIEMENS	SINAMICS / SIMODRIVE- SUBASSEMBY WITH ELECTRICAL FILTER FUNCTION HFD PACKET 55 KW; 800 W; CONTAINS: HFD- REACTOR 6SL3000-0DE25-5AA1 DAMPING RESISTOR 800 W 6SL3100-1BE21-3AA0	3	0
6AG1225-0BE27-5AA1	SIEMENS	SIPLUS SINAMICS G120 FSC 7,5KW	+ 10	0
6FX2002-1DC00-1AA1	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX2002-1DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITHOUT 24 V LENGTH (M) = 0 + 0 + 0 + 0,1	2	0
6FX2002-1DC00-1AA2	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX2002-1DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITHOUT 24 V LENGTH (M) = 0 + 0 + 0 + 0,2	10	0
6FX2002-1DC00-1AA3	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX2002-1DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITHOUT 24 V LENGTH (M) = 0 + 0 + 0 + 0,3	+ 10	0

## SINAMICS - dostępne komponenty

6FX2002-1DC00-1AA6	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX2002-1DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITHOUT 24 V LENGTH (M) = 0 + 0 + 0 + 0,6	2	0
6FX2002-1DC00-1AB2	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX2002-1DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITHOUT 24 V LENGTH (M) = 0 + 0 + 1 + 0,2	+ 10	0
6FX5002-2DC10-1AH5	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX5002-2DC10 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP67, WITH 24 V MOTION-CONNECT 500 LENGTH (M) = 0 + 0 + 7 + 0,5	8	0
6FX5002-5CS01-1AH5	SIEMENS	POWER CABLE, PREASSEMBLED TYPE: 6FX5002-5CS01 (1FT/1FK/1PH TO SINAMICS) 4X1.5 C, CONNECTOR SIZE 1/1.5 MM2 UL/CSA DESINA, MOTION-CONNECT 500 DMAX = 8.4 MM, LENGTH (M) = 0 + 0 + 7 + 0,5	4	0
6RA8091-6DV62-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 996A CONTROLLABLE FIELD RECTIFIER D420/1200 MREQ-GEGF6V62 OUTPUT: DC 420V, 1200A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	1	0
6RA8025-6DV62-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 50A CONTROLLABLE FIELD RECTIFIER D420/60 MREQ-GEG6V62 OUTPUT: DC 420V, 60A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6RA8028-6DV62-0AP0	SIEMENS	SINAMICS DCM DC-PACKAGE 3AC 400V/50HZ/DC 90A/4Q 1 6RA8028-6DV62-0AA0 1 SWITCH-DISCONNECTOR-FUSE 1 CONTACTOR ARM+SNUBBER 1 COMMUTATING CHOKE ARMATURE 3 AC_SEMICONDUCTOR FUSE 1 DC_SEMICONDUCTOR FUSE+HOLDER 1 CONTACTOR EXCITATION INCL. SNUBBER CIRCUIT 1	0	1
6SL3054-0GA00-1AA0	SIEMENS	SINAMICS G SINGLE LICENSE	0	1
6SL3040-1NC00-0AA0	SIEMENS	SINAMICS NUMERIC CONTR. EXTENSION NX10.3 EXTENSION DRIVE CONTROL FOR SINUMERIK 840D SL AND 828D UP TO 3 AXES	0	+ 10
6SL3054-0TA00-1BA0-Z	SIEMENS	SINAMICS S120 COMPACTFLASH CARD W/O PERFORMANCE EXTENSION INCLUDING CERTIFICATE OF LICENCE V4.3 SP2	0	5
6SL3054-1BD00-0AA0	SIEMENS	SINAMICS G150 COMPACTFLASH CARD FIRMWARE VERSION V01.03 NMA: A5E00229894	0	1
6SL3054-1CC00-1AA0	SIEMENS	SINAMICS G150 COMPACTFLASH CARD FIRMWARE VERSION V02.02	8	0
6SL3054-1ED00-1AA0	SIEMENS	SINAMICS G150 COMPACTFLASH CARD FIRMWARE-VERSION V04.03.02	0	1
6SL3054-4EB00-0AA0	SIEMENS	SINAMICS S110 MULTIMEDIA-CARD 64 MB INCLUDING CERTIFICATE OF LICENCE V4.1	0	1
6SL3055-0AA00-3KA0	SIEMENS	SINAMICS TERMINAL MODULE CABINET TM120 WITHOUT DRIVE-CLIQ CABLE ADD ON BOARD FOR SINAMICS CONVERTERS PTC- AND KTY-ANALOG INPUTS WITH SAFE ELECTRICAL ISOLATION	0	1
6SL3055-0AA00-3LA0	SIEMENS	SINAMICS TERMINALMODULE TM150 ADD ON BOARD FOR TEMPERATURE EVALUATION UNIT FOR G130/G150, S120/S150, GM150/GL150, SM120/SM150, SL150 AND SINAMICS DCM	1	6
6SL3055-0AA00-5BA0	SIEMENS	SINAMICS SENSOR MODULE SMC20 INCREMENTAL ENCODER: SIN/COS 1VPP ABSOLUTE ENCODER: ENDAT WITHOUT DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	+ 10
6SL3072-4AA02-0XG0	SIEMENS	SOFTWARE AUF DVD: STARTDRIVE ENGINEERING- UND INBETRIEBNAHMETOOL FUER SINAMICS VERSION V11 SP1 FUER WINDOWS SERVER 2003 SP2, UND WINDOWS XP PROF SP3, UND WINDOWS 7 PROFESSIONAL / ENTERPRISE / ULTIMATE 32/64 BIT DEUTSCH, ENGLISCH, SPANISCH FRANZOESISC	2	0

## SINAMICS - dostępne komponenty

6SL3072-4DA02-0XG0	SIEMENS	SOFTWARE ON DVD: STARTDRIVE ENGINEERING- AND COMMISSIONING TOOL FOR SINAMICS GERMAN, ENGLISH, SPANISH FRENCH, ITALIAN AND CHINESE (SIMPLIFIED) INCLUDING SINGLE LICENSE	2	0
6SL3120-1TE21-8AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3PH 400 V, 18 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE PAINTED MODULES	0	+ 10
6SL3120-1TE23-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 30 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	4
6SL3120-1TE23-0AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600VDC OUTPUT: 3AC 400V, 30A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE MODULES PAINTED	0	+ 10
6SL3120-1TE24-5AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400V, 45A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	1
6SL3120-1TE26-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3 AC 400 V, 60 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	2
6SL3120-1TE26-0AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400V, 60A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED,	0	1
6SL3120-1TE28-5AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3 AC 400 V, 85 A , INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	6
6SL3120-1VE21-0AA0	SIEMENS	SINAMICS S120 VALUE SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3 AC 400 V, 9 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	2
6SL3120-2TE15-0AB0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 5A/5A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	+ 10
6SL3111-3VE21-6EA0	SIEMENS	SINAMICS S120 COMBI POWER MODULE INPUT: 3AC 400V, 16KW OUTPUT: 3AC 400V, 24A, 9A, 9A FRAME SIZE: COMBI EXTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS	0	2
6SL3111-3VE22-0HA0	SIEMENS	SINAMICS S120 COMBI POWER MODULE INPUT: 3AC 400V, 20KW OUTPUT: 3AC 400V, 30A, 9A, 9A FRAME SIZE: COMBI EXTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS	0	8
6SL3111-4VE21-0EA0	SIEMENS	SINAMICS S120 COMBI POWER MODULE INPUT: 3AC 400V, 10KW OUTPUT: 3AC 400V,24A,12A,12A,12A DESIGN: COMBI EXTERNAL AIR COOLING SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS	0	1
6SL3120-1TE15-0AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400V, 5A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	5
6SL3120-1TE21-0AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600VDC OUTPUT: 3AC 400V, 9A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE MODULES PAINTED	0	5
6SL3120-1TE21-8AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 18 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	+ 10
6SL3121-1TE13-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 3 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	6
6SL3121-1TE13-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT 3AC 400V, 3A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3121-1TE15-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 5 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	4

## SINAMICS - dostępne komponenty

6SL3121-1TE15-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3121-1TE21-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 9 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3121-1TE21-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3121-1TE21-8AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 18 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3162-8BD00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT MOTOR MODULE 100MM	1	0
6SL3121-1TE28-5AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH 400 V, 85 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	7
6SL3121-2TE21-0AA4	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A/9A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	3
6SL3125-3UE31-5AA0	SIEMENS	SINAMICS S120 HIGH FREQUENCY DRIVE DAMPING MODULE 150A, 32 KHZ MAX. OUTPUT FREQUENCY: 2100 HZ FRAME SIZE: BOOKSIZE,	0	2
6SL3125-3UE32-2AA0	SIEMENS	SINAMICS S120 HIGH FREQUENCY DRIVE DAMPING MODULE 225A, 16 KHZ MAX. OUTPUT FREQUENCY: 1200 HZ FRAME SIZE: BOOKSIZE	0	1
6SL3126-1TE15-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 5 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3126-1TE15-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A FRAME SIZE: BOOKSIZE COLD- PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	2
6SL3126-1TE21-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 9 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE,	0	2
6SL3162-8EM50-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT MOTOR MODULE 300MM LIQUID COOLED	1	0
6SL3126-1TE21-8AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 18 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3126-1TE21-8AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A FRAME SIZE: BOOKSIZE COLD- PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	2
6SL3126-1TE23-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 30 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	3
6SL3126-1TE24-5AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 45 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3126-1TE28-5AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 85 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	7
6SL3126-2TE13-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: DC 600 V OUTPUT: 3-PH. 400 V, 3 A/3 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3126-2TE21-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH. 400 V, 9A/9A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	1

## SINAMICS - dostępne komponenty

6SL3126-2TE21-0AA4	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A/9A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	2
6SL3126-2TE21-8AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH 400 V, 18 A/18 A COLD PLATE AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3130-7TE23-6AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 60 A, 36 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	1
6SL3130-7TE25-5AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 92 A, 55 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	2
6SL3130-7TE25-5AA1	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 92 A, 55 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	1	1
6SL3130-7TE31-2AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 200 A, 120 KW INTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	2
6SL3163-8FD00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT ALM/SLM 100MM	1	0
6SL3131-6TE21-6AA3	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 27A, 16KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3131-6TE23-6AA3	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 60A, 36KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	3
6SL3131-7TE31-2AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 600V , DC, 200A, 120KW EXTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND , DRIVE-CLIQ CABLE,	0	1
6SL3136-6AE21-0AA1	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 17 A, 10 KW FRAME SIZE: BOOKSIZE COLD PLATE COOLING INCL. CONTROL VOLTAGE ADAPTER	0	1
6SL3136-6TE23-6AA0	SIEMENS	SINAMICS S120 SMART LINE MODULE COLD PLATE COOLING INPUT 3AC 380-460V 50/60HZ OUTPUT DC 600V 60A 36KW	0	1
6SL3136-7TE28-0AA1	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 600V DC, 134A, 80KW COLD-PLATE COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	5
6SL3163-8GF00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT ALM/SLM/BLM 150MM	1	0
6SL3163-8HH00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT ALM/SLM/BLM 200MM	2	0
6SL3163-8JM00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT ALM 300MM	1	0
6SL3163-8LD00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT BLM 100MM	1	0
6SL3210-1KE11-8UP1	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD) EXTERNA	1	0
6SL3203-0BE27-5BA0	SIEMENS	SINAMICS LINE FILTER CLASS B FOR POWER MODULE FSD 3AC 380V-480V 72A	0	1
6SL3203-0BE31-1BA0	SIEMENS	SINAMICS LINE FILTER CLASS B FOR POWER MODULE FSE 3AC 380V-480V 105A	0	2
6SL3203-0BE31-8BA0	SIEMENS	SINAMICS LINE FILTER CLASS B FOR POWER MODULE FSF 3AC 380V-480V 204A	0	1

## SINAMICS - dostępne komponenty

6SL3203-0CE21-8AA0	SIEMENS	SINAMICS LINE REACTOR 380-480V 3AC 47-63HZ I_LN = 22,3A STANDALONE	0	1
6SL3210-1KE11-8AB0	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73	0	2
6SL3210-1KE11-8AB1	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU; PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X7	0	1
6SL3210-1KE11-8AC1	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXW	0	2
6SL3210-1KE11-8AP1	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203	0	1
6SL3210-1KE11-8UP0	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD)	0	1
6SL3210-1KE12-3AP0	SIEMENS	SINAMICS G120C RATED POWER 0,75KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203	0	4
6SL3210-1KE12-3UB1	SIEMENS	SINAMICS G120C RATED POWER 0,75KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD) EXT	1	0
6SL3210-1KE13-2AB0	SIEMENS	SINAMICS G120C RATED POWER 1,1KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X	0	1
6SL3210-1KE13-2UF1	SIEMENS	SINAMICS G120C RATED POWER 1,1KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225,4(HXWXD) EXTERN	0	2
6SL3210-1KE14-3AP1	SIEMENS	SINAMICS G120C RATED POWER 1,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(	0	2
6SL3210-1KE14-3UF1	SIEMENS	SINAMICS G120C RATED POWER 1,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225,4(HXWXD) EXTERN	0	1

## SINAMICS - dostępne komponenty

6SL3210-1KE15-8AB0	SIEMENS	SINAMICS G120C RATED POWER 2,2KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73	0	3
6SL3210-1KE15-8AP1	SIEMENS	SINAMICS G120C RATED POWER 2,2KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203	0	1
6SL3210-1KE17-5UF1	SIEMENS	SINAMICS G120C RATED POWER 3,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X225,4(HXWXD) EXTERN	0	1
6SL3210-1KE18-8AB0	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X	0	3
6SL3210-1KE18-8AB1	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73	0	1
6SL3210-1KE18-8AC0	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWX)	0	3
6SL3210-1KE18-8AC1	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWX)	0	2
6SL3210-1KE18-8UB1	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD) EXT	0	1
6SL3210-1KE18-8UC0	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD)	0	1
6SL3210-1KE18-8UP0	SIEMENS	SINAMICS G120C RATED POWER 4,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXWXD)	0	1
6SL3210-1KE21-7UB1	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU; PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203(HXWXD) E	0	2



## SINAMICS - dostępne komponenty

6SL3210-1KE21-3AB0	SIEMENS	SINAMICS G120C RATED POWER 5,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100	0	1
6SL3210-1KE21-7UC0	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203(HXWXD)	0	3
6SL3210-1KE21-3UB1	SIEMENS	SINAMICS G120C RATED POWER 5,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203(HXWXD) EX	0	4
6SL3210-1KE21-3UF1	SIEMENS	SINAMICS G120C RATED POWER 5,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X 100X 225,4 (HXWXD) E	0	2
6SL3210-1KE21-7AB0	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100	0	5
6SL3210-1KE21-7AB1	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X10	0	1
6SL3210-1KE21-7AC0	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203(HXW)	0	5
6SL3210-1KE21-7AP0	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203	0	10
6SL3210-1KE22-6UB1	SIEMENS	SINAMICS G120C RATED POWER 11,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X203(HXWXD) E	0	1
6SL3210-1KE22-6UF1	SIEMENS	SINAMICS G120C RATED POWER 11,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X 140X 225,4 (HXWXD)	0	1
6SL3210-1KE23-8AB1	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU; PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X	0	1

## SINAMICS - dostępne komponenty

6SL3210-1KE23-2UB1	SIEMENS	SINAMICS G120C RATED POWER 15,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X203(HXWXD) E	0	3
6SL3210-1KE23-2UF1	SIEMENS	SINAMICS G120C RATED POWER 15,0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X 140X 225,4 (HXWXD)	0	2
6SL3210-1KE23-8AB0	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X14	0	3
6SL3210-1KE23-8AC0	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X203(HX	0	2
6SL3210-1KE23-8AC1	SIEMENS	SINAMICS G120C SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FS	0	2
6SL3210-1KE23-8AF1	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X2	0	6
6SL3210-1KE23-8AP0	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X20	0	2
6SL3210-1KE23-8UC0	SIEMENS	SINAMICS G120C RATED POWER 18,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSC 295X140X203(HXWXD)	0	4
6SL3210-1NE11-3AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,37KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND P	3	1
6SL3210-1NE11-7AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,55KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND P	0	+ 10
6SL3210-1NE15-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 2,2KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND PA	0	8

## SINAMICS - dostępne komponenty

6SL3210-1NE12-2AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,75KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND P	0	5
6SL3210-1NE13-1AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 1,1KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND PA	0	4
6SL3210-1NE14-1AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 1,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND PA	0	5
6SL3210-1NE26-0AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 30KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 419 X 275 X 204 (HXWXD), FSD WITHOUT CONTROL UNIT AND PANEL APPR	0	5
6SL3210-1NE17-7AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 3KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND PANE	0	+ 10
6SL3210-1NE21-0AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 4KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 292 X 100 X 165 (HXWXD), FSB WITHOUT CONTROL UNIT AND PAN	0	1
6SL3210-1NE21-0UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 4KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 292 X 100 X 165 (HXWXD), FSB WITHOUT CONTROL UNIT AND PANEL APPROVED FOR	0	1
6SL3210-1NE21-3AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 5,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 292 X 100 X 165 (HXWXD), FSB WITHOUT CONTROL UNIT AND P	0	2
6SL3210-1NE26-0UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 30KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 419 X 275 X 204 (HXWXD), FSD WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU240B/	0	5
6SL3210-1NE21-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 292 X 100 X 165 (HXWXD), FSB WITHOUT CONTROL UNIT AND P	0	2
6SL3210-1NE21-8UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 292 X 100 X 165 (HXWXD), FSB WITHOUT CONTROL UNIT AND PANEL APPROVED FO	0	2

## SINAMICS - dostępne komponenty

6SL3210-1NE22-6AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 11KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND PA	0	8
6SL3210-1NE22-6AL1	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 11KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND PA	0	1
6SL3210-1NE27-5AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 37KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 635 X 275 X 204 (HXWXD), FSD WITHOUT CONTROL UNIT AND PANEL APPR	0	5
6SL3210-1NE22-6UL1	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 11KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND PANEL APPROVED FOR	0	3
6SL3210-1NE23-2AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 15KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND PA	0	1
6SL3210-1NE23-2AL1	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 15KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND PA	0	1
6SL3210-1NE23-2UL1	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 15KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND PANEL APPROVED FOR	0	2
6SL3210-1NE23-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND	0	+ 10
6SL3210-1NE23-8AL1	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND	0	4
6SL3210-1NE23-8UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 355 X 140 X 165 (HXWXD), FSC WITHOUT CONTROL UNIT AND PANEL APPROVED F	0	2
6SL3210-1NE24-5AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 22KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 419 X 275 X 204 (HXWXD), FSD WITHOUT CONTROL UNIT AND PANEL APPR	0	9

## SINAMICS - dostępne komponenty

6SL3210-1NE27-5UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 37KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 499 X 275 X 204 (HXWXD), FSE WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU240B/	0	6
6SL3210-1NE24-5UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 22KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 419 X 275 X 204 (HXWXD), FSD WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU240B/	2	5
6SL3210-1NE28-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 45KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 635 X 275 X 204 (HXWXD), FSE WITHOUT CONTROL UNIT AND PANEL APPR	0	3
6SL3210-1NE28-8UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 45KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 499 X 275 X 204 (HXWXD), FSE WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU240B/	0	2
6SL3210-1NE31-1AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 55KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 934 X 350 X 316 (HXWXD), FSF WITHOUT CONTROL UNIT AND PANEL APPR	0	8
6SL3210-1NE31-1UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 55KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 634 X 350 X 316 (HXWXD), FSF WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU240B/	0	9
6SL3210-1NE31-5AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 75KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 934X 350X 316 (HXWXD), FSF WITHOUT CONTROL UNIT AND PANEL APPROV	0	3
6SL3210-1NE31-5UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 75KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 634 X 350 X 316 (HXWXD), FSF WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU240B/	0	1
6SL3210-1NE31-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 90KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 634 X 350 X 316 (HXWXD), FSF WITHOUT CONTROL UNIT AND PANEL APPR	0	3
6SL3210-1NE31-8UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 90KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 634 X 350 X 316 (HXWXD), FSF WITHOUT CONTROL UNIT AND PANEL APPROVED FOR CU240B/	0	3
6SL3210-1NE32-1UL0	SIEMENS	POWER MODULE PM230 (3AC, 400V, UF, 110KW) FSF IP20	0	2
6SL3210-1NE32-5UL0	SIEMENS	SINAMICS PM230 (3AC, 400V, UF, 132KW) FSF, IP20	0	4

## SINAMICS - dostępne komponenty

6SL3210-1PC22-8AL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC200-240V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 5,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 5	0	1
6SL3210-1PE13-2UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,75KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 1,1KW FOR 150% 3S,110%	0	1
6SL3210-1PE11-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 0,55KW FOR	0	3
6SL3210-1PE11-8UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 0,55KW FOR 150% 3S,110%	0	2
6SL3210-1PE12-3UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,55KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 0,75KW FOR 150% 3S,110%	0	2
6SL3210-1PE12-3UL1	SIEMENS	SINAMICS POWER MODULE PM240-2 UNFILTERED WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,55KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP. -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 0,75KW AT 150% 3S,110% 57S,100% 240S A	1	6
6SL3210-1PE13-2AL1	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,75KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP. -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 1,1KW AT 150% 3S,110%	7	2
6SL3210-1PE14-3AL1	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,1KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP. -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 1,5KW AT 150% 3S,110% 5	0	1
6SL3210-1PE16-1AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 2,2KW FOR 15	0	2
6SL3210-1PE16-1UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 2,2KW FOR 150% 3S,110%	0	2
6SL3210-1PE16-1UL1	SIEMENS	SINAMICS POWER MODULE PM240-2 UNFILTERED WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP. -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 2,2KW AT 150% 3S,110% 57S,100% 240S AMB	0	4

## SINAMICS - dostępne komponenty

6SL3210-1PE18-0ULO	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 2,2KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 3KW FOR 150% 3S,110% 57S	0	1
6SL3210-1PE21-1ALO	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 4KW FOR 150% 3S,110% 57S,1	1	1
6SL3210-5BE24-0CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 4KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:F5B 140X160X165(HXWDX)	0	4
6SL3210-1PE21-1ULO	SIEMENS	SINAMICS POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 4KW FOR 150% 3S,110% 57S,100% 240S AMB	0	1
6SL3210-1PE23-3ULO	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 15KW FOR 150% 3S,110% 57S,100% 2	0	5
6SL3210-1QE23-8ALO	SIEMENS	POWERMODULE 250, INPUT 3AC 400-480V +/-10% 36A	0	1
6SL3210-1QE24-5ALO	SIEMENS	6SL3210-1QE24-5ALO	0	1
6SL3210-1QE28-8ALO	SIEMENS	POWERMODULE 250, AC3 400-480V +/-10% 84A	0	2
6SL3210-5BB11-2AV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,12KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C2 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:F5A 90X150X146(HXWDX)	0	6
6SL3210-5BB11-2UV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,12KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:F5A 90X166X146(HXWDX)	0	1
6SL3210-5BB12-5UV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,25KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:F5A 90X166X146(HXWDX)	0	1
6SL3210-5BE25-5CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 5.5KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:F5C 184X182X169(WXHXD)	0	1
6SL3210-5BB13-7UV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,37KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:F5A 90X150X146(WXHXD)	0	2

## SINAMICS - dostępne komponenty

6SL3210-5BB15-UUV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,55KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X150X146(WXHxD)	0	1
6SL3210-5BE25-UUV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 5.5KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSC 184X182X169(WXHxD)	0	7
6SL3210-5BB17-UUV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,75KW / 0,75HP WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X166X146(HXWxD)	0	6
6SL3210-5BB18-UUV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,75KW / 1HP WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X166X146(WXHxD)	0	1
6SL3210-5BB21-UUV0	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 1,5KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSB 140X160X165(HXWxD)	0	5
6SL3210-5BE15-5CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 0.55KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X150X146(WXHxD)	0	1
6SL3210-5BE15-UUV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 0.55KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X150X146(HXWxD)	1	1
6SL3210-5BE27-UUV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 7.5KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSD 240X207X173(WXHxD)	0	3
6SL3210-5BE17-5CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 0.75KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X150X146(WXHxD)	0	2
6SL3210-5BE17-UUV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 0.75KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X150X146(WXHxD)	0	8
6SL3210-5BE21-1UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 1.1KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X166X146(WXHxD)	0	3



## SINAMICS - dostępne komponenty

6SL3210-5BE21-5UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 1.5KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSA 90X166X146(HXWXD)	1	+ 10
6SL3210-5BE31-1CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 11KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSD 240X207X173(WXHXD)	0	1
6SL3210-5DE13-5UA0	SIEMENS	SINAMICS V70 INPUT: 3AC 380-480V -15%/+10% 3.8A 45-66HZ OUTPUT:0-INPUT V 3.0A 0-330HZ PROTECTION: IP20 MOTOR:0.75/1.0KW FRAME SIZE A,80X180X200 (WXHXD);	0	4
6SL3210-5BE31-1UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 11KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSD 240X207X173(WXHXD)	0	2
6SL3210-5BE31-5CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 15KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSD 240X207X173(WXHXD)	1	0
6SL3210-5BE31-5UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 15KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSD 240X207X173(WXHXD)	1	1
6SL3210-5DE16-0UA0	SIEMENS	SINAMICS V70 INPUT: 3AC 380-480V -15%/+10% 5.8A 45-66HZ OUTPUT:0-INPUT V 4.6A 0-330HZ MOTOR:1.5KW PROTECTION: IP20 FRAME SIZE B 100X180X220 WXHXD	0	1
6SL3210-5DE12-4UA0	SIEMENS	SINAMICS V70 INPUT: 3AC 380-480V -15%/+10% 1.5A 45-66HZ OUTPUT: 0-INPUT V 1.2A 0-330HZ MOTOR:0.4KW PROTECTION: IP20 FRAME SIZE A, 80X180X200 (WXHXD)	0	1
6SL3211-1PE18-0ULO	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 PUSH-THROUGH WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 2,2KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 3KW FOR 150% 3S,110%	1	2
6SL3210-5FE10-4UA0	SIEMENS	SINAMICS V90 INPUT: 3AC 380-480V -15%/+10% 1.5A 45-66HZ OUTPUT: 0-INPUT V 1.2A 0-330HZ PROTECTION: IP20 MOTOR:0.4KW FRAME SIZE FSA60X180X200(WXHXD)	0	2
6SL3210-5FE11-5UA0	SIEMENS	SINAMICS V90 INPUT: 3AC 380-480V 15%/+10% 6.6A 45-66HZ OUTPUT: 0-INPUT V 5.3A 0-330HZ MOTOR:1.5/1.75KW PROTECTION: IP20 FRAME SIZE B, 100X180X220(WXHXD)	0	3
6SL3210-5FE12-0UA0	SIEMENS	SINAMICS V90 INPUT: 3AC 380-480V -15%/+10% 9.8A 45-66HZ OUTPUT: 0-INPUT V 7.8A 0-330HZ PROTECTION: IP20 MOTOR:2.0/2.5KW FRAME SIZE B,100X180X220(WXHXD)	0	7
6SL3210-5FE17-0UA0	SIEMENS	SINAMICS V90 INPUT: 3AC 380-480V 15%/+10% 16.5A 45-66HZ OUTPUT: 0-INPUT V 13.2A 0-330HZ MOTOR: 7.0KW PROTECTION: IP20 FRAME SIZE C, 140X260X240(WXHXD)	0	1

## SINAMICS - dostępne komponenty

6SL3211-1NE17-7AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 / PT 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 3KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 238 X 126 X 171 (HXWXD), FSA WITHOUT CONTROL UNIT AN	0	4
6SL3211-1NE21-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 / PT 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 345 X 154 X 171 (HXWXD), FSB WITHOUT CONTROL UNIT	0	7
6SL3211-1NE23-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 / PT 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 411 X 200 X 171 (HXWXD), FSC WITHOUT CONTROL UNIT	0	3
6SL3211-1NE28-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP20 / PT 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 45KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 411 X 200 X 171 (HXWXD), FSC WITHOUT CONTROL UNIT	0	1
6SL3211-1NE31-1AL0	SIEMENS	SINAMICS POWER MODULE 230	0	1
6SL3211-1PE23-3UL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 15KW FOR 150% 3S,110% 57S,100% 240S A	0	1
6SL3211-1PE16-1AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 PUSH-THROUGH WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 2,2KW	2	1
6SL3216-5BE17-5CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 0.75KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 90X150X115 (WXHDX) FLAT	0	1
6SL3217-0CE31-5UA0	SIEMENS	SINAMICS V10-1 AC-DRIVE, WITHOUT FILTER 3AC380V -15/+20% 48-52HZ OUTPUT 15,0KW OVERLOAD 150% 60S,100% 240S, CYCLE 300S AMBIENT TEMP 0 TO +50 DEG C 401 X 260 X 223 (HXWXD), FSD PROTECTION IP21 WITH BOP	0	1
6SL3217-0CE32-2UA0	SIEMENS	SINAMICS V10-1 AC-DRIVE, WITHOUT FILTER 3AC380V -15/+20% 48-52HZ OUTPUT 22,0KW OVERLOAD 150% 60S,100% 240S, CYCLE 300S AMBIENT TEMP 0 TO +50 DEG C 401 X 260 X 223 (HXWXD), FSD PROTECTION IP21 WITH BOP	0	7
6SL3217-0CE32-2UA1	SIEMENS	SINAMICS V10-1 AC-DRIVE, WITHOUT FILTER 3AC400V -15/+20% 48-52HZ OUTPUT 22,0KW OVERLOAD 150% 60S,100% 240S, CYCLE 300S AMBIENT TEMP 0 TO +50 DEG C 401 X 260 X 223 (HXWXD), FSD PROTECTION IP21 WITH BOP	0	1
6SL3223-0DE34-5BA1	SIEMENS	SINAMICS POWER MODULE PM230 IP55	0	3
6SL3225-0BH31-1UA0	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITHOUT FILTER POSSIBILITY OF , REGENERATION 3AC660-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR, 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT , OVERLOAD: 15KW FOR 140% 3S,110% 57S,10	0	1

## SINAMICS - dostępne komponenty

6SL3225-0BH31-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC660-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 140% 3S,110	0	3
6SL3243-6BB30-1HA2	SIEMENS	SINAMICS G120P BT CONTROL UNIT CU230P-2 BT USS/MODBUS RTU/BACNET MS/TP 6, DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V , DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	+ 10
6SL3243-0BB30-1CA2	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 CAN INTEGRATED CANOPEN 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	5
6SL3243-0BB30-1CA3	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 CAN INTEGRATED CANOPEN 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	1
6SL3243-6BB30-1HA3	SIEMENS	SINAMICS G120P BT CONTROL UNIT CU230P-2 BT USS/MODBUS RTU/BACNET MS/TP 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	+ 10
6SL3243-0BB30-1PA3	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 DP INTEGRATED PROFIBUS DP 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	6
6SL3244-0BB00-1BA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240B-2 B-TYPE RS485-INTERFACE, USS-PROTOCOL 4 DI, 1 DO, 1 AI, 1 AO PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	3	+ 10
6SL3244-0BB13-1BA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 F E-TYPE SAFETY INTEGRATED STO, SS1, SLS, RS485-INTERFACE, 6DI, 3DO, 2AI, 2AO, MAX 3F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO 50 DEG C WITHOUT POWER MODULE AND PANEL	0	10
6SL3244-0BB13-1BA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 F E-TYPE SAFETY INTEGRATED STO, SS1, SLS, RS485-INTERFACE, 6DI, 3DO, 2AI, 2AO, MAX 3F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	0	7
6SL3244-0BB13-1PA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 DP-F E-TYPE SAFETY INTEGRATED STO, SS1, SLS, PROFIBUS DP 6DI, 3DO, 2AI, 2AO, MAX 3F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MODULE AND PANEL	0	+ 10
6SL3244-0BB12-1PA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU240E-2 DP E-TYPE SAFETY INTEGRATED STO PROFIBUS DP 6DI, 3DO, 2AI, 2AO, MAX 1F-DI PTC/KTY INTERFACE USB- AND SD/MMC-INTERFACE PROTECTION IP20 AMBIENT TEMP 0 TO 50 DEG C WITHOUT , POWER MODULE AND PANEL	0	6
6SL3264-1EA00-0HA0	SIEMENS	SINAMICS G120 CU SCREENING TERMINATION KIT 2 INCLUDES SCREENING PLATE AND FIXING ELEMENTS FOR CONTROL UNITS CU240B-2, CU240E-2 AND CU240E-2 F VARIANT: RS485, PROFIBUS DP	1	0
6SL3310-1UE34-6AA0	SIEMENS	SINAMICS G120P POWER MODULE IP00 3AC 380-480V, 50/60HZ, 460A NOM. POWER RATING: 250KW 6-PULSE SUPPLY WITHOUT REGENERATIVE FEEDBACK TYPE WITHOUT CONTROL MODULE	0	1

## SINAMICS - dostępne komponenty

6SL3325-1TG41-6AA3	SIEMENS	SINAMICS S120 MOTOR MODULE INPUT: DC 675 - 1035V OUTPUT: 3AC 500-690V, 50/60HZ, 1500A, RATED POWER: 1500KW CHASSIS UNIT IP00 LIQUID COOLING	0	7
6SL3330-7TH41-0AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE 3AC 660-690V, , 50/60HZ, 1025A OUTPUT: DC 890 - 1035V RATED POWER: 1100KW CHASSIS UNIT , IP00 INTERNAL AIR COOLING INCL. DRIVE- CLIQ CABLE	0	1
6SL3350-6TK00-0CA0	SIEMENS	SINAMICS SPARE PART CONTROL INTERFACE MODULE (CIM) DESIGN FPGA FOR AIRCOOLED DRIVES	0	+ 10
6SL3351-3AE35-0AA0	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED POWER MODULE 3AC 380-480V, 50/60HZ / 490A	0	1
6SL3351-3AH34-1DB0	SIEMENS	SINAMICS G150 REPLACEMENT IPD	0	1
6SL3351-3AH37-4DB0	SIEMENS	SINAMICS G150 REPLACEMENT IPD	0	1
6SL3352-3AG31-2AC0	SIEMENS	SINAMICS S150 REPLACEMENT IPD MOTOR MODULE 500- 690V, 110KW	0	1
6SL3352-1AG37-4FA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR DC 675- 1035V, 735A MOTOR MODULE U OR V OR W PHASE VARNISHED ASSEMBLIES AND NICKEL-PLATED CONDUCTOR BAR	0	3
6SL3352-3AE33-8AC0	SIEMENS	SINAMICS S150 REPLACEMENT IPD MOTOR MODULE 380- 480V, 200KW	0	1
6SL3352-3AG31-5AA0	SIEMENS	SINAMICS S120 REPLACEMENT IPD MOTOR MODULE 500- 690V, 132KW	0	1
6SL3353-3AG41-3AA4	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED ACTIVE LINE MODULE WITH FPGA 3AC 380-480V, 50/60HZ, 1270A	0	6
6SL3352-6TE33-1AA0	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 380-480V, 50/60HZ, 310A MOTOR MODULE	0	1
6SL3352-6TE33-1AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3PH 380-480 V, 50/60 HZ, 310 A MOTOR MODULE	0	1
6SL3352-6TG41-3AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 500-690V, 50/60HZ, 1270A MOTOR MODULE	0	1
6SL3353-3AE41-0AA4	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED ACTIVE LINE MODULE WITH FPGA 3AC 380-480V, 50/60HZ, 985A	6	+ 10
6SL3353-3AE41-4AA4	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED ACTIVE LINE MODULE WITH FPGA 3AC 380-480V, 50/60HZ, 1405A	0	6
6SL3353-3AG41-0AA4	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED ACTIVE LINE MODULE WITH FPGA 3AC 500-690V, 50/60HZ, 1025A	0	1
6SL3353-3AG41-4BA0	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED BASIC LINE MODULE 1100 KW 3AC 500-690V / 1400A	0	1
6SL3353-6TE33-8AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3PH 380-480 V, 50/60 HZ, 380 A ACTIVE LINE MODUL	0	2
6SL3420-1TE21-8AA1	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE EINGANG: DC 600V AUSGANG: 3AC 400V, 18A BAUFORM BOOKSIZE COMPACT INTERNE LUFTKUEHLUNG OPTIMIERTE PULSMUSTER UND UNTERSTUETZUNG HOHERWERTIGE SAFETY FUNKTIONEN INKL. DRIVE-CLIQ LEITUNG	0	2
6SL3353-6TE41-0AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 380-480 V, 50/60HZ, 985 A ACTIVE LINE MODULE	0	2
6SL3355-2DX00-1AA0	SIEMENS	SAFE BRAKE ADAPTER AC 230V / 2A FOR SAFE BRAKE CONTROL	0	1
6SL3400-1AE31-0AA0	SIEMENS	SINAMICS BRAKING MODULE COMPACT INPUT: DC600V OUTPUT: PDB/PMAX 5/100KW	0	1
6SL3400-1AE31-0AA1	SIEMENS	SINAMICS BRAKING MODULE COMPACT INPUT: DC600V OUTPUT: PDB/PMAX 5/100KW	0	3
6SL3400-1AE31-0AB0	SIEMENS	6SL3400-1AE31-0AB0	0	9

## SINAMICS - dostępne komponenty

6SL3420-1TE13-0AA1	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE- CLIQ CABLE	1	6
6SL3420-1TE15-0AA1	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE- CLIQ CABLE	0	5
6SL3420-1TE15-0AX0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 60V OUTPUT: 3AC 40V, 5A , FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	5
6SL3420-1TE15-0AX1	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 60V OUTPUT: 3AC 40V, 5A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	4
6SL3420-1TE21-0AA1	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE- CLIQ CABLE	5	6
6SL3544-0FB21-1PA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU240D-2 DP-F PROFIBUS DP AND SAFETY INTEGRAT 6 DI/3 F-DI, 2 DO/1 F-DO, 2 AI USB INTERFACE SD/MMC-INTERFACE HTL-ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP 0 TO +55 DEG C WITHOUT POWER MODULE	0	1
6SL3546-0FB21-1FA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU250D-2 PN-F PROFINET, STO ON-BOARD POSITIONING (EPOS) 6 DI/3 F- DI, 2 DO/1 F-DO, 2 AI USB INTERFACE SD/MMC-INTERFACE HTL AND SSI ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP -10 TO +50 DEG C WITHOUT POWER MODULE	0	2
6SL3546-0FB21-1FB0	SIEMENS	SINAMICS G120D CONTROL UNIT CU250D-2 PN-F PP PROFINET AND SAFETY INTEGRATED POSITIONING (EPOS) PUSH-PULL DESIGN 6 DI/3 F-DI, 2 DO/1 F-DO, 2 AI SD/MMC-INTERFACE HTL AND SSI ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP 0 TO +50 DEG C WITHOUT POWER MO	0	1
6SL3546-0FB21-1PA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU250D-2 DP-F PROFIBUS DP AND SAFETY INTEGRAT POSITIONING (EPOS) 6 DI/3 F- DI, 2 DO/1 F-DO, 2 AI USB INTERFACE SD/MMC-INTERFACE HTL AND SSI ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP 0 TO +55 DEG C WITHOUT POWER MODULE	0	1
6SL3555-2BC10-0AA0	SIEMENS	SINAMICS S120M ADAPTER MODULE 600 FRAME SIZE: BOOKSIZE COMPACT INPUT: DC 600V INTERNAL AIR COOLING	0	+ 10
6RA8028-6DV62-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 75A CONTROLLABLE FIELD RECTIFIER D420/90 MREQ-GEG6V62 OUTPUT: DC 420V, 90A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6RA8078-6DS22-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR TWO-QUADRANT DRIVES CONNECTION B6C INPUT: 3-PHASE AC 400V, 232A CONTROLLABLE FIELD RECTIFIER D485/280 MRE-GEEF6S22 OUTPUT: DC 485V, 280A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	2
6RA8087-6GV62-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 575V, 706A CONTROLLABLE FIELD RECTIFIER D600/850 MREQ-GEGF6V62 OUTPUT: DC 600V, 850A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	0

## SINAMICS - dostępne komponenty

6RA8091-6DV62-0AA0	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 996A CONTROLLABLE FIELD RECTIFIER D420/1200 MREQ-GEGF6V62 OUTPUT: DC 420V, 1200A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	0
6SL3000-0BE41-2AA0	SIEMENS	SINAMICS LINE FILTER CL. A1 INPUT: 3AC 380-480V, 50/60HZ 1200A NMA: A5E00105341	0	1
6SL3000-0EE38-8AA0	SIEMENS	SINAMICS LINE REACTOR FOR SMART LINE MODULE 500KW 3AC 380-480V, 50/60HZ, 885A	1	1
6SL3000-0EE41-4AA0	SIEMENS	SINAMICS LINE REACTOR FOR SMART LINE MODULE 630/800KW 3AC 380-480V, 50/60HZ, 1430A	2	1
6SL3000-2BE32-1AA0	SIEMENS	SINAMICS/MICROMASTER PX MOTOR INDUCTOR FOR 3-PH 380-480 V, 50/60 HZ, 210 A AC DRIVES/POWER MODULES/ MOTOR MODULES	2	0
6SL3000-2BE32-6AA0	SIEMENS	SINAMICS/MICROMASTER PX MOTOR INDUCTOR FOR 3-PH 380-480 V, 50/60 HZ, 260 A AC DRIVES/POWER MODULES/ MOTOR MODULES	1	5
6SL3040-0GA00-1AA0	SIEMENS	SINAMICS G130 CONTROL UNIT KIT GROUP MLFB CONSISTING OF: CONTROL UNIT CU320 COMPACTFLASH CARD G130 MICROMASTER STARTER UNIT DOCUMENTATION CD	2	0
6SL3040-0JA02-0AA0	SIEMENS	SINAMICS S110 CONTROL UNIT CU305 CAN WITH CAN-BUS INTERFACE	0	+ 10
6SL3040-0LA01-0AA0	SIEMENS	SINAMICS CONTROL UNIT CU310 PN WITH ROFINET INTERFACE WITHOUT COMPACTFLASH CARD	0	+ 10
6SL3040-0MA00-0AA0	SIEMENS	SINAMICS CU320 CONTROL UNIT WITHOUT COMPACT FLASH CARD WITHOUT UL APPROVAL	0	2
6SL3055-0AA00-4CA1	SIEMENS	SINAMICS OPERATOR PANEL AOP30 ENGLISH / ITALIAN CU320 SW V2.2	1	0
6SL3066-2DA00-0AA0	SIEMENS	SINAMICS CABINET BUSHING FOR DRIVE-CLIQ-CABLE PROTECTION IP54	0	1
6SL3100-1AE31-0AA0	SIEMENS	SINAMICS BRAKING MODULE INPUT: 600 V DC OUTPUT: PEAK 100 KW/2 S	0	2
6SL3121-1TE15-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	3
6SL3121-1TE26-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 60A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	3
6SL3121-1TE32-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 200A OUTPUT: WITH 8 KHZ / 140A FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3121-2TE13-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: 600 V DC OUTPUT 3-PH. 400 V, 3 A/3 A EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	6
6SL3125-1TE32-0AA4	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 200A OUTPUT: AT 8 KHZ / 140A FRAME SIZE: BOOKSIZE LIQUID COOLED OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE (WITHOUT CONTROL	0	1
6SL3126-1TE15-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	6

## SINAMICS - dostępne komponenty

6SL3126-1TE21-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	4
6SL3126-1TE23-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 30A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3126-1TE26-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 60A FRAME SIZE: BOOKSIZE COLD-PLATE COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3126-1TE32-0AA3	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 200A FRAME SIZE: BOOKSIZE OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE COLD-PLATE COOLING	0	2
6SL3126-2TE13-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A/3A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	6
6SL3126-2TE21-0AA3	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A/9A FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3131-6AE21-0AA0	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3 AC 380-480 V, 50/60HZ OUTPUT: 600 V DC, 17 A, 10 KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	8
6SL3131-7TE21-6AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 27A, 16KW FRAME SIZE: BOOKSIZE EXTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3136-1TE22-0AA0	SIEMENS	SINAMICS S120 BASIC LINE MODULE INPUT: 3PH 380-480V, 50/60HZ OUTPUT: DC 600V, 34 A, 20KW FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3136-1TE24-0AA0	SIEMENS	SINAMICS S120 BASIC LINE MODULE INPUT: 3PH 380-480V, 50/60HZ OUTPUT: DC 600V, 67 A, 40KW FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING INCL. DRIVE-CLIQ CABLE	0	3
6SL3136-1TE31-0AA0	SIEMENS	SINAMICS S120 BASIC LINE MODULE INPUT: 3PH 380-480V, 50/60HZ OUTPUT: DC 600V, 167 A, 100KW FRAME SIZE: BOOKSIZE COLD-PLATE-COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3136-6AE15-0AA0	SIEMENS	SINAMICS S120 SMART LINE MODULE INPUT: 3-PH 380-480 V, 50/60 HZ OUTPUT: 600 V DC, 8.3 A, 5 KW FRAME SIZE: BOOKSIZE COLD PLATE AIR COOLING INCL. CONTROL VOLTAGE ADAPTER	0	1
6SL3136-7TE21-6AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3AC 380-480V, 50/60HZ OUTPUT: DC 600V, 27A, 16KW FRAME SIZE: BOOKSIZE COLD PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	4
6SL3136-7TE23-6AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3-PH. 380-480 V 50/60 HZ OUTPUT: 600 V DC, 60 A, 36 KW COLD-PLATE COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	4
6SL3136-7TE25-5AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3-PH. 380-480 V 50/60 HZ OUTPUT: 600 V DC, 92 A, 55 KW COLD-PLATE COOLING INCL. CONTROL VOLTAGE ADAPTER AND DRIVE-CLIQ CABLE	0	2

## SINAMICS - dostępne komponenty

6SL3162-2DB00-0AA0	SIEMENS	SINAMICS ZK-BUSBAR SET REINFORCED, FOR 50 MM MODULE BOOKSIZE FOR THE EXCHANGE FOR ZK 1 PACKAGE WITH 10 PCS FOR 5 MODULES	4	0
6SL3162-2DD00-0AA0	SIEMENS	SINAMICS ZK-BUSBAR SET REINFORCED, FOR 100 MM MODULE BOOKSIZE FOR THE EXCHANGE FOR ZK 1 PACKAGE WITH 10 PCS FOR 5 MODULES	10	0
6SL3162-8CF00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT MOTOR MODULE 150MM	1	0
6SL3162-8DH00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT MOTOR MODULE 200MM	1	0
6SL3200-0SP01-0AA0	SIEMENS	SINAMICS SPARE PART CIM PM-IF FOR POWER MODULE PM240 FSGX CIB, POWER SUPPLY BOARD AND MOUNTING KIT	0	10
6SL3202-0AE21-0CA0	SIEMENS	SINAMICS OUTPUT REACTOR FOR POWER MODULE FSB FOOT PRINT	0	+ 10
6SL3203-0BE21-6SA0	SIEMENS	SINAMICS SUPPL. LINE FILTER CL. B FOR POWER MODULE FSB FOOT PRINT 3AC 380-480V 10,2A 296 X 153 X 50 MM H X W X D	1	0
6SL3210-1SB12-3UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 1AC 200-240V, 50/60HZ OUTPUT: 3AC 2,3A (0,37KW) FRAME SIZE: BLOCKSIZE SIZE FSA INTERNAL AIR COOLING	5	4
6SL3210-1SE27-5AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 75A (37KW) FRAME SIZE: BLOCKSIZE SIZE FSE WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	1
6SL3210-1SE31-1AA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 110A (55KW) FRAME SIZE: BLOCKSIZE SIZE FSF WITH INTEGRATED LINE FILTER INTERNAL AIR COOLING	0	2
6SL3211-0AB11-2BA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CLASS B FILTR 1AC200-240V 10/-10% 47-63HZ ANALOG INPUT CT: 0,12KW; VT: 0,12KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	2
6SL3211-0AB11-2BB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 0.12KW; VT: 0.12KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT AN	0	1
6SL3211-0AB11-2UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0,12KW; VT: 0,12KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1
6SL3211-0AB11-2UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.12KW; VT: 0.12KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	4
6SL3211-0AB11-2UB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 0.12KW; VT: 0.12KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT ANALOG I	0	1
6SL3211-0AB12-5BA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CLASS B FILTR 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0,25KW; VT: 0,25KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	2



## SINAMICS - dostępne komponenty

6SL3211-0AB12-5BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.25KW; VT: 0.25KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	+ 10
6SL3211-0AB12-5BB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 0.25KW; VT: 0.25KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT AN	0	1
6SL3211-0AB12-5UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V 10/-10% 47-63HZ ANALOG INPUT CT: 0,25KW; VT: 0,25KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1
6SL3211-0AB12-5UB0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V 10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 0,25KW; VT: 0,25KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT BOP WITHOUT ANALOG INP	0	1
6SL3211-0AB13-7UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V 10/-10% 47-63HZ ANALOG INPUT CT: 0,37KW; VT: 0,37KW CT-OVERLOAD: 150% 60S 150 X 90 X 116 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	1	1
6SL3211-0AB15-5BA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CLASS B FILTR 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0,55KW; VT: 0,55KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	2
6SL3211-0AB15-5BB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 0.55KW; VT: 0.55KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT AN	0	1
6SL3211-0AB15-5UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0,55KW; VT: 0,55KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1
6SL3211-0AB15-5UB0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 0.55KW; VT: 0.55KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT ANALOG	0	1
6SL3211-0AB17-5BA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CLASS B FILTR 1AC200-240V 10/-10% 47-63HZ ANALOG INPUT CT: 0,75KW; VT: 0,75KW CT-OVERLOAD: 150% 60S 150 X 90 X 131 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO 40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	2
6SL3211-0AB21-1AA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CLASS A FILTR 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 1,1KW; VT: 1,1KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1

## SINAMICS - dostępne komponenty

6SL3211-0AB21-1AB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. A FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 1.1KW; VT: 1.1KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT ANA	0	1
6SL3211-0AB21-1UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 1.1KW; VT: 1.1KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	6
6SL3211-0AB21-5AB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. A FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 1.5KW; VT: 1.5KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT ANA	0	2
6SL3211-0AB21-5UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 1,5KW; VT: 1,5KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1
6SL3211-0AB21-5UB0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V 10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 1,5KW; VT: 1,5KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO 40 DEG C WITHOUT BOP WITHOUT ANALOG INPU	0	2
6SL3211-0AB21-5UB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 1.5KW; VT: 1.5KW CT-OVERLOAD: 150% 60S 160 X 140 X 142 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT ANALOG IN	0	1
6SL3211-0AB22-2AB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. A FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 2.2KW; VT: 2.2KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT ANA	0	3
6SL3211-0AB22-2UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V 10/-10% 47-63HZ ANALOG INPUT CT: 2,2KW; VT: 2,2KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO 50 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1
6SL3211-0AB23-0AA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CLASS A FILTR 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 3,0KW; VT: 3,0KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1
6SL3211-0AB23-0UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 3,0KW; VT: 3,0KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT RS485-INTERFACE	0	1
6SL3211-0AB23-0UB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS-PROTOCOL) CT: 3.0KW; VT: 3.0KW CT-OVERLOAD: 150% 60S 181 X 184 X 152 (HXWXD) PROTECTION IP20 AMBIENT TEMP -10 TO +40 DEG C WITHOUT BOP WITHOUT ANALOG IN	0	1
6SL3211-0KB11-2BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.12KW; VT: 0.12KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXD) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +50 DEG C WITHOU	0	3

## SINAMICS - dostępne komponenty

6SL3211-0KB11-2UA0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0,12KW; VT: 0,12KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) PROTECTION IP20 WITHOUT HEATSINK AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP WITHOUT RS485-IN	0	1
6SL3211-0KB11-2UA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.12KW; VT: 0.12KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP	0	3
6SL3211-0KB11-2UB0	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS- PROTOCOL) CT: 0,12KW; VT: 0,12KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) PROTECTION IP20 WITHOUT HEATSINK AMBIENT TEMP -10 TO +50 DEG C WITHOUT BOP	0	2
6SL3211-0KB11-2UB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS- PROTOCOL) CT: 0.12KW; VT: 0.12KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +50	0	2
6SL3211-0KB12-5BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.25KW; VT: 0.25KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +50 DEG C WITHOU	2	3
6SL3211-0KB13-7BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.37KW; VT: 0.37KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +50 DEG C WITHOU	0	9
6SL3211-0KB13-7BB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS- PROTOCOL) CT: 0.37KW; VT: 0.37KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 T	0	1
6SL3211-0KB15-5BA1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ ANALOG INPUT CT: 0.55KW; VT: 0.55KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +50 DEG C WITHOU	0	1
6SL3211-0KB15-5UB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE, WITHOUT FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS- PROTOCOL) CT: 0.55KW; VT: 0.55KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 TO +50	0	1
6SL3211-0KB17-5BB1	SIEMENS	SINAMICS G110 - CPM110 AC-DRIVE,BUILT IN CL. B FILTER 1AC200-240V +10/-10% 47-63HZ RS485-INTERFACE (USS- PROTOCOL) CT: 0.75KW; VT: 0.75KW CT-OVERLOAD: 150% 60S 150 X 90 X 101 (HXWXd) IP20; WITH FLAT HEATSINK; COLDPLATE ASSEMBLY ONLY AMBIENT TEMP -10 T	0	1
6SL3215-1SE23-8UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 38A (18,5KW) FRAME SIZE: BLOCKSIZE SIZE FSD LIQUID COOLING	0	5
6SL3215-1SE26-0UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 60A (30KW) FRAME SIZE: BLOCKSIZE SIZE FSD LIQUID COOLING	0	+ 10

## SINAMICS - dostępne komponenty

6SL3215-1SE27-5UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 75A (37KW) FRAME SIZE: BLOCKSIZE SIZE FSE LIQUID COOLING	0	6
6SL3215-1SE31-0UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 90A (45KW) FRAME SIZE: BLOCKSIZE SIZE FSE LIQUID COOLING	0	+ 10
6SL3215-1SE31-8UA0	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE PM340 INPUT: 3AC 380-480V, 50/60HZ OUTPUT: 3AC 178A (90KW) FRAME SIZE: BLOCKSIZE SIZE FSF LIQUID COOLING	0	4
6SL3223-0DE13-7BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,37KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO+40 DEG C (LO) 460 X 154 X 249 (HXBXT), FSA WITHOUT CON	0	1
6SL3223-0DE17-5AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,75KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO+40 DEG C (LO) 460 X 154 X 249 (HXBXT), FSA WITHOUT CON	0	1
6SL3223-0DE17-5BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,75KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO+40 DEG C (LO) 460 X 154 X 249 (HXBXT), FSA WITHOUT CONT	0	1
6SL3223-0DE21-5AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 1,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO+40 DEG C (LO) 460 X 154 X 249 (HXBXT), FSA WITHOUT CONTR	1	1
6SL3223-0DE22-2AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 2,2KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO+40 DEG C (LO) 460 X 154 X 249 (HXBXT), FSA WITHOUT CONT	2	0
6SL3223-0DE27-5BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO+40 DEG C (LO) 540 X 180 X 249 (HXBXT), FSB WITHOUT CONTR	0	2
6SL3223-0DE31-8BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) XXX X XXX X XXX (HXWXd), FSC WITHOUT CON	0	1
6SL3223-0DE32-2BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 22KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 640 X 320 X 329 (HXBXT), FSD WITHOUT CONTR	0	1
6SL3223-0DE33-0AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 30KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 640 X 320 X 329 (HXBXT), FSD WITHOUT CONTROL UNIT A	0	5

## SINAMICS - dostępne komponenty

6SL3223-0DE33-0BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 30KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 640 X 320 X 329 (HXBXT), FSD WITHOUT CONTR	0	1
6SL3223-0DE33-7BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 37KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 751 X 320 X 329 (HXBXT), FSE WITHOUT CONTROL UNIT A	0	2
6SL3223-0DE34-5AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 45KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 751 X 320 X 329 (HXBXT), FSE WITHOUT CONTROL UNIT A	0	2
6SL3223-0DE35-5AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 55KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 915 X 410 X 416 (HXBXT), FSF WITHOUT CONTR	0	1
6SL3223-0DE37-5AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 75KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 915 X 410 X 416 (HXBXT), FSF WITHOUT CONTR	0	1
6SL3223-0DE37-5BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 75KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 915 X 410 X 416 (HXBXT), FSF WITHOUT CONTROL UNIT A	0	2
6SL3223-0DE38-8AA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 90KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 915 X 410 X 416 (HXBXT), FSF WITHOUT CONTR	0	2
6SL3223-0DE38-8BA0	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 90KW FOR 110% 60S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 915 X 410 X 416 (HXBXT), FSF WITHOUT CONTROL UNIT A	1	0
6SL3224-0BE31-8UA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITHOUT FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 18,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 22KW FOR 150% 3S,110% 57S,100% 24	0	1
6SL3224-0BE34-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM240 WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 55KW FOR 150% 3S,110% 5	9	0
6SL3225-0BE27-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO 50 DEG C OUTPUT LIGHT OVERLOAD: 11KW FOR 150% 3S,110% 5	0	7

## SINAMICS - dostępne komponenty

6SL3225-0BE31-1AA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO 50 DEG C OUTPUT LIGHT OVERLOAD: 15KW FOR 150% 3S,110% 57	0	10
6SL3225-0BE31-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240	0	3
6SL3225-0BE32-2UA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 30KW FOR 150% 3S,110% 57S,100% 240S	0	4
6SL3225-0BE33-0UA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 37KW FOR 150% 3S,110% 57S,100% 240S	0	3
6SL3225-0BE33-7UA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 45KW FOR 150% 3S,110% 57S,100% 240S	0	5
6SL3225-0BE35-5UA0	SIEMENS	SINAMICS G120 POWER MODULE PM250 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 55KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 75KW FOR 150% 3S,110% 57S,100% 240S	0	1
6SL3225-0BH27-5AA0	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC660-690V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO 50 DEG C OUTPUT LIGHT OVERLOAD: 11KW FOR 140% 3S,110	0	1
6SL3225-0BH27-5AA1	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC500-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 11KW FOR 140% 3S,110% 3S,110%	0	2
6SL3225-0BH27-5UA1	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC660-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 11KW FOR 140% 3S,110% 57S,100% 2	0	2
6SL3225-0BH31-1UA1	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC500-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 15KW FOR 140% 3S,110% 57S,100% 240	0	1
6SL3225-0BH31-5AA1	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC500-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 18,5KW FOR 140% 3S,110	0	+ 10

## SINAMICS - dostępne komponenty

6SL3225-0BH32-2AA0	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC660-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 30KW FOR 140% 3S,110%	0	2
6SL3225-0BH33-7AA0	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC660-690V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO 50 DEG C OUTPUT LIGHT OVERLOAD: 55KW FOR 140% 3S,110% 57	0	1
6SL3225-0BH33-7AA1	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC500-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 55KW FOR 140% 3S,110%	0	+ 10
6SL3243-0BA30-1CA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 CAN INTEGRATED CANOPEN 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20 WITHOUT POWER MODULE AND PANEL	0	3
6SL3243-0BA30-1HA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 HVAC INTEGRATED USS/ MODBUS RTU 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20 WITHOUT POWER MODULE AND PANEL	0	+ 10
6SL3243-0BA30-1PA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 DP INTEGRATED PROFIBUS DP 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20 WITHOUT POWER MODULE AND PANEL	0	9
6SL3243-0BB30-1CA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 CAN INTEGRATED CANOPEN 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	+ 10
6SL3243-0BB30-1PA1	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 DP INTEGRATED PROFIBUS DP 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	0	+ 10
6SL3255-0AA00-2AA0	SIEMENS	SINAMICS G110 PC-INVERTER CONNECTION KIT	0	3
6SL3255-0BT01-0PA0	SIEMENS	SINAMICS G120 CHEMICAL INDUST. MODULE CM240NE FOR OPERATION WITH CU240S DP-F CU250S-2 DP ATEX CERTIFIED COLD LEADER EVALUATION,NAMUR TERMINAL STRIP FOR OPERATION WITH CU250S-2 DP THE SUPPLEMENTARY KIT (6SL3260-4TA00-1AA6) IS NEEDED (RAIL MOUNTING)	2	2
6SL3261-1BA00-0AA0	SIEMENS	SINAMICS G110 DIN RAIL MOUNTING KIT SIZE 1, FS A UTILIZED BY SINAMICS V20	4	0
6SL3298-0AA11-0AP0	SIEMENS	SINAMICS G110 OPERATING INSTRUCTIONS CPM110 IN GERMAN	2	0
6SL3300-7TG41-3AA0	SIEMENS	SINAMICS S120 SINAMICS S120 ACTIVE INTERFACE MODULE FOR ACTIVE LINE MODULE 1100/1400KW 3AC 500-690V, 50/60HZ, 1270A RATED POWER: 1400KW CHASSI UNIT IP00 INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	5
6SL3310-1GH38-1AA0	SIEMENS	SINAMICS G130 POWER MODULE IP00 3-PH. 660-690 V, 50/60 HZ, 810A UNIT RATING: 800 KW (VT) 6-PULSE SUPPLY WITHOUT POWER RECOVERY INCL. DRIVE-CLIQ CABLE WITHOUT CONTROL MODULE	1	0

## SINAMICS - dostępne komponenty

6SL3310-1TE32-6AA3	SIEMENS	SINAMICS S120 CONVERTER POWER MODULE 3AC 380-480V, 50/60HZ, 260A (132 KW) INTERNAL AIR COOLING FRAME SIZE: CHASSIS SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE AND MOUNTING PLATE FOR CU310	0	1
6SL3320-1TE33-8AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH 400 V, 380 A FRAME SIZE: CHASSIS INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3320-1TE35-0AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3-PH 400 V, 490 A FRAME SIZE: CHASSIS INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	1	0
6SL3320-1TE36-1AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 510-720V DC OUTPUT: 3-PHASE AC 0-480V, 605A NOMINAL POWER RATING: 315KW CHASSIS UNIT IP00 INTERNAL AIR COOLING INCL. DRIVE CLIQ CABLE	1	0
6SL3320-1TE41-0AA0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 510-720V DC OUTPUT: 3-PHASE AC 0-480V, 985A NOMINAL POWER RATING: 560KW CHASSIS UNIT IP00 INTERNAL AIR COOLING INCL. DRIVE CLIQ CABLE	0	1
6SL3325-1TG38-1AA3	SIEMENS	SINAMICS S120 MOTOR MODULE INPUT: DC 675 - 1035V OUTPUT: 3AC 500-690V, 50/60HZ, 810A, RATED POWER: 800KW CHASSIS UNIT IP00 LIQUID COOLING	0	1
6SL3330-6TE41-1AA0	SIEMENS	SINAMICS S120 SMART LINE MODULE 3AC 380-480V, 50/60HZ OUTPUT: DC 510 - 650V, 1050A RATED POWER: 500KW CABINET UNIT IP00 INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3330-6TE41-3AA0	SIEMENS	SINAMICS S120 SMART LINE MODULE 3AC 380-480V, 50/60HZ OUTPUT: DC 510 - 650V, 1300A RATED POWER: 630KW CABINET UNIT IP00 INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3330-7TE32-1AA0	SIEMENS	SINAMICS ACTIVE LINE MODULE INPUT: 3-PH 380-480V, 50/60HZ OUTPUT: 600 V DC, 220 A, 132 KW INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	3	0
6SL3330-7TE32-6AA3	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE INPUT: 3-PH 380-480V, 50/60HZ OUTPUT: 600 V DC, 291 A, 160 KW INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3330-7TG41-3AA0	SIEMENS	SINAMICS S120 ACTIVE LINE MODULE 3AC 500-690V, 50/60HZ, 1270A OUTPUT: DC 750 - 1035V RATED POWER: 1400KW CABINET UNIT IP00 INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	3
6SL3330-7TG41-3AA3	SIEMENS	SINAMICS ACTIVE LINE MODULE 3AC 500-690V, 50/60HZ, 1270A OUTPUT: DC 750 - 1035V RATED POWER: 1400KW BUILT-IN UNIT IP00 DESIGN CIM INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	2
6SL3330-7TG41-3AA4	SIEMENS	SINAMICS ACTIVE LINE MODULE 3AC 500-690V, 50/60HZ, 1270A OUTPUT: DC 750 - 1035V RATED POWER: 1400KW BUILT-IN UNIT IP00 DESIGN CIM INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3351-6GH28-5AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 660-690 V, 50/60HZ, 85 A POWER MODULE	0	4
6SL3351-6GH31-0AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 660-690 V, 50/60HZ, 100 A POWER MODULE	0	1
6SL3351-6GH31-2AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 660-690 V, 50/60HZ, 120 A POWER MODULE	0	2
6SL3351-6GH31-8AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 660-690 V, 50/60HZ, 175 A POWER MODULE	0	1
6SL3351-6GH32-2AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 660-690 V, 50/60HZ, 215 A POWER MODULE	0	1
6SL3351-6GH34-1AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 660-690 V, 50/60HZ, 410 A POWER MODULE	0	1
6SL3351-6GH34-7AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 660-690 V, 50/60HZ, 465 A POWER MODULE	0	2
6SL3352-1AE38-4BA0	SIEMENS	SINAMICS SPARE POWER BLOCK FOR 3AC 380-480 V, 50/60 HZ, 845 A AC DRIVE/POWER MODULE DC 510-650 V, 840 A MOTOR MODULE V AND W PHASES	0	1
6SL3353-3AG35-5CA0	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED SMART LINE MODULE	0	1



## SINAMICS - dostępne komponenty

6SL3355-3AE32-1AA0	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR WATERCOOLED POWER MODULE 3AC 380-480V, 50/60HZ / 210A	0	2
6SL3420-1TE13-0AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	8
6SL3420-1TE15-0AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 5A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3420-1TE21-0AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 9A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	+ 10
6SL3420-1TE21-8AA0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 18A FRAME SIZE BOOKSIZE COMPACT INTERNAL AIR COOLING OPTIMIZED PULSE PATTERNS AND HELP HIGHER ORDER SAFETY FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	9
6SL3462-1CC00-0AA0	SIEMENS	SINAMICS S120 DISTANCE BOLT SET (4 PIECES) FOR MOTOR MODULES FORMAT BOOKSIZE COMPACT NOTE: MOUNTING OF 50 MM MODULES VIA 2 DISTANCE BOLTS MOUNTING OF 75 MM MODULES VIA 4 DISTANCE BOLTS	2	0
6SL3511-0PE23-0AM0	SIEMENS	SINAMICS G110D AC-DRIVE, W/O REPAIR SWITCH WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER WITH AS-INTERFACE BUS INTERFACE 3AC380-500V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3,0KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +40 DEG C	1	0
6SL3511-0PE24-0AM0	SIEMENS	SINAMICS G110D AC-DRIVE, W/O REPAIR SWITCH WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER WITH AS-INTERFACE BUS INTERFACE 3AC380-500V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4,0KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +40 DEG C 2	0	2
6SL3511-1PE21-5AM0	SIEMENS	SINAMICS G110D AC-DRIVE, WITH REPAIR SWITCH WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER WITH AS-INTERFACE BUS INTERFACE 3AC380-500V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +40 DEG C	0	3
6SL3511-1PE27-5AM0	SIEMENS	SINAMICS G110D AC-DRIVE, WITH REPAIR SWITCH WITH BUILT IN CL. A FILTER WITH BULT IN BRAKING CHOPPER WITH AS-INTERFACE BUS INTERFACE 3AC380-500V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +40 DEG C	0	1
6SL3525-0PE21-5AA0	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,5KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO 40 DEG C 210 X 450 X 110 (HXWXD), FSA PROTECTION IP65	0	+ 10
6SL3525-0PE23-0AA0	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 3,0KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO 40 DEG C 210 X 450 X 180 (HXWXD), FSB PROTECTION IP65	0	1
6SL3525-0PE24-0AA0	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4,0KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO 40 DEG C 210 X 450 X 220 (HXWXD), FSC PROTECTION IP65	0	+ 10

## SINAMICS - dostępne komponenty

6SL3525-0PE27-5AA0	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V 10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO 40 DEG C 210 X 450 X 220 (HXWXD), FSC PROTECTION IP65	0	+ 10
6SL3525-0PE27-5AA1	SIEMENS	SINAMICS G120D POWER MODULE PM250D WITH BUILT IN CL. A FILTER POSSIBILITY OF REGENERATION 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 60S,100% 300S AMBIENT TEMP -10 TO +55 DEG C 210 X 450 X 220 (HXWXD), FSC PROTECTION IP	0	5
6SL3544-0FA21-1FA0	SIEMENS	SINAMICS G120D CONTROL UNIT CU240D PN-F PROFINET AND SAFETY INTEGRATED 6 DI, 2 DO PTC/KTY INTERFACE EM-BRAKE CONTROL, MMC INTERFACE ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP 0 TO 40 DEG C WITHOUT POWER MODULE	2	+ 10
6SL3710-1GE32-1CA0	SIEMENS	SINAMICS G150 CONVERTER CABINET UNIT, AC/AC 3AC 380-480 V, 50/60 HZ NOM. POWER RATING: 110 KW 6-PULSE SYSTEM WITHOUT REGENERATIVE FEEDBACK VERSION C, INCL. EMV-FILTER 2. AMB. CONDITION, CATEGORY C3	0	1
6RA8028-6DV62-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 75A CONTROLLABLE FIELD RECTIFIER D420/90 MREQ-GEG6V62 OUTPUT: DC 420V, 90A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6SL3054-0CG00-1AA0-Z	SIEMENS	SINAMICS S120 COMPACTFLASH CARD W/O PERFORMANCE EXTENSION INCLUDING CERTIFICATE OF LICENCE V2.6	0	1
6SL3210-1KE21-7AC1	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203	0	2
6SL3210-1PB13-8AL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 1/3AC200-240V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,55KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 0,75KW FOR 150% 3S,11	0	4
6SL3243-0BB30-1FA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU230P-2 PN INTEGRATED PROFINET 6 DI, 3 DO, 4 AI, 2 AO 1 MOTOR TEMP. SENSOR INPUT 2 PSU-OUT(10V DC, 24V DC) 1 PSU-IN (24V DC) USB- AND MMC-INTERFACE PROTECTION IP20	2	1
6SL3420-2HX00-0AA0	SIEMENS	SINAMICS S120 HYDRAULIC LINEAR ACTOR 2 AXIS-CONTROLLER	0	+ 10
6SL3210-1KE21-7AP1	SIEMENS	SINAMICS G120C RATED POWER 7,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFIBUS-DP PROTECTION: IP20/ UL OPEN TYPE SIZE: FSB 196X100X203	1	1
6SL3352-1AE41-0FA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR DC 510-750V, 985A MOTOR MODULE U OR V OR W PHASE VARNISHED ASSEMBLIES AND NICKEL-PLATED CONDUCTOR BAR	0	4
6SL3120-1TE15-0AD0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 5A FRAME SIZE: BOOKSIZE D-TYPE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1

## SINAMICS - dostępne komponenty

6SL3120-1TE21-0AD0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 9A FRAME SIZE: BOOKSIZE D-TYPE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6SL3055-0AA00-6AA1	SIEMENS	SINAMICS DRIVE-CLIQ MODULE CABINET DMC20 WITHOUT DRIVE-CLIQ CABLE	0	1
6SL3120-1VE22-4AA0	SIEMENS	SINAMICS S120 VALUE SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400 V, 24 A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE WITHOUT UL APPROVAL	0	1
6SL3210-1PE21-4UL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 5,5KW FOR 150% 3S,110% 57S,100% 240S A	0	8
6SL3246-0BA22-1CA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU250S-2 CAN INTEGRIERT CANOPEN SUPPORT OF VECTOR CONTROL, EASY POSITIONING EPOS VIA EXTENDED FUNCTION LICENSE 4 CONFIGURABLE DI/DO, 6 DI (USABLE AS 3 F-DI), 5 DI, 3 DO (USABLE AS 1 F-DO), 2 AI, 2 AO SAFETY INTEGRATED STO,	0	2
6SL3246-0BA22-1BA0	SIEMENS	SINAMICS G120 CONTROL UNIT CU250S-2 INTEGRIERT RS485/USS/MODBUS RTU SUPPORT OF VECTOR CONTROL, EASY POSITIONING EPOS VIA EXTENDED FUNCTION LICENSE 4 CONFIGURABLE DI/DO, 6 DI (USABLE AS 3 F-DI), 5 DI, 3 DO (USABLE AS 1 F-DO), 2 AI, 2 AO SAFETY INTEGRA	0	+ 10
6SL3225-0BH32-2UA0	SIEMENS	SINAMICS G120 POWER MODULE PM260 WITHOUT FILTER POSSIBILITY OF REGENERATION 3AC660-690V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LIGHT OVERLOAD: 30KW FOR 140% 3S,110% 57S,100% 24	0	1
6SL3223-0DE31-5BA1	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 15KW FOR 150% 3S,110% 57S,100% 240S AMBIE. TEMP -10 TO+40 DEG C(LO) 620 X 230 X 249 (HXBXT), FSC WITHOUT CONTRO	0	2
6SL3223-0DE27-5BA1	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100% 240S AMBIE. TEMP -10 TO+40 DEG C(LO) 540 X 180 X 249 (HXBXT), FSB WITHOUT CONTR	0	3
6SL3223-0DE25-5BA1	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 5,5KW FOR 150% 3S,110% 57S,100% 240S AMBIE. TEMP -10 TO+40 DEG C(LO) 540 X 180 X 249 (HXBXT), FSB WITHOUT CONTR	0	1
6SL3223-0DE23-0AA1	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 3KW FOR 150% 3S,110% 57S,100% 240S AMBIE. TEMP -10 TO+40 DEG C(LO) 460 X 154 X 249 (HXBXT), FSA WITHOUT CONTROL	0	3
6SL3223-0DE15-5BA1	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. B FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,55KW FOR 150% 3S,110% 57S,100% 240S AMBIE. TEMP -10 TO+40 DEG C(LO) 460 X 154 X 249 (HXBXT), FSA WITHOUT CONT	0	1
6FX5002-2DC10-1AK0	SIEMENS	SIGNAL CABLE, PREASSEMBLED TYPE: 6FX5002-2DC10 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP67, WITH 24 V MOTION-CONNECT 500 LENGTH (M) = 0 + 0 + 9 + 0	4	0

## SINAMICS - dostępne komponenty

6SL3210-1PE31-1UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 55KW FOR 150% 3S,110% 57S,1	0	1
6SL3210-1PE23-8AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 18.5KW FOR 150%	0	1
6SL3210-1PE14-3UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 1,1KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 1,5KW FOR 150% 3S,110% 5	0	1
6SL3210-1PE13-2AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 STANDARD WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,75KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP 0 TO +50 DEG C OUTPUT LOW OVERLOAD: 1,1KW FOR 1	0	2
6SL3210-1PC26-8UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 UNFILTERED WITH BUILT IN BRAKING CHOPPER 3AC200-240V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 18.5KW FOR 150% 3S,110% 57S,100	0	1
6SL3351-6GE36-1AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 380-480 V, 50/60HZ, 605 A POWER MODULE	0	1
6SL3353-3AE35-5CA0	SIEMENS	SINAMICS S120 SPARE IPD-CARD FOR AIRCOOLED SMART LINE MODULE	1	0
6SL3353-1AE35-5AA0	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR 3AC 380-480V, 50/60HZ, 550A SMART LINE MODULE RECTIFIER AND 3 PHASES VARNISHED ASSEMBLIES AND NICKEL-PLATED CONDUCTOR BAR	1	0
6SL3223-0DE31-1AA1	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 11KW FOR 150% 3S,110% 57S,100% 240S AMBIE. TEMP -10 TO+40 DEG C(LO) 620 X 230 X 249 (HXBXT), FSC WITHOUT CONTRO	0	3
6SL3217-0CE15-5UA1	SIEMENS	SINAMICS V10-1 AC DRIVE, UNFILTERED 3AC400V-15/+20% 48-52HZ OUTPUT 0.55 KW OVERLOAD 150% 60S, 100% 240S CYCLE 300S AMBIENT TEMPERATURE 0 TO +50 °C 230X 140X 155 (HXWXd), FSA DEGREE OF PROTECTION IP21 WITH BOP	0	2
6SL3210-1KE12-3AC1	SIEMENS	SINAMICS G120C RATED POWER 0,75KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: CANOPEN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSA 196X73X203(HXW	0	2
6SL3210-1PE21-8AL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 5,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 5	1	0
6SL3210-1PE22-7UL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 7,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 11KW FOR 150% 3S,110% 57S,100% 240S	0	+ 10

## SINAMICS - dostępne komponenty

6SL3064-8MA00-0AA0	SIEMENS	SINAMICS/SINUMERIK/SIMOTION TERMINAL KIT CU320/NCU 7X0.1/ NCU 7X0.2/D4X5/D445-1 1 COMPLETE SET	1	0
6SL3210-1PE21-8UL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 5,5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 7,5KW FOR 150% 3S,110% 57S,100% 240S	0	8
6SL3120-2TE21-0AD0	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3-PH 400V, 9A/9A FRAME SIZE: BOOKSIZE D-TYPE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	3
6SL3210-5BE31-8UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ OUTPUT HIGH OVERLOAD: 18,5KW WITH 150% OVERLOAD FOR 60SEC OUTPUT LOW OVERLOAD: 22KW WITH 110% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTIO	2	0
6SL3210-5BE32-2UV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW WITH 150% OVERLOAD FOR 60SEC OUTPUT LOW OVERLOAD: 30KW WITH 110% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION	2	0
6SL3210-1PE24-5AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 18.5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 22KW FOR 150%	0	2
6SL3210-1PH22-3AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 15KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 18.5KW FOR 150%	0	1
6SL3210-1PE26-0AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 30KW FOR 150% 3	0	1
6SL3210-1PE27-5AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 37KW FOR 150% 3	0	6
6SL3210-1PH22-0AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 11KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 15KW FOR 150% 3	0	1
6SL3210-1PH24-2AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 37KW FOR 150% 3	0	2
6SL3210-1PH25-2AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 45KW FOR 150% 3	0	1

## SINAMICS - dostępne komponenty

6SL3210-1PE32-5UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 110KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 132KW FOR 150% 3S,110% 57S	0	1
6SL3210-1PH31-4UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 110KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 132KW FOR 150% 3S,110% 57S	0	1
6SL3210-1PH21-4UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 7.5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 11KW FOR 150% 3S,110% 57S,	0	2
6SL3210-1PE26-0UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 22KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 30KW FOR 150% 3S,110% 57S,1	0	2
6SL3210-1PE28-8UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 45KW FOR 150% 3S,110% 57S,1	0	1
6SL3210-1PH24-2UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 37KW FOR 150% 3S,110% 57S,1	0	1
6SL3210-1PH25-2UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 37KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 45KW FOR 150% 3S,110% 57S,1	0	2
6SL3210-1PH26-2UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 3AC500-690V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 55KW FOR 150% 3S,110% 57S,1	0	1
6SL3210-1PC24-2UL0	SIEMENS	SINAMICS G120 POWER MODULE PM240-2 UNFILTERED WITH BUILT IN BRAKING CHOPPER 3AC200-240V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 7.5KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 11KW FOR 150% 3S,110% 57S,100%	0	1
6SL3210-1PE21-4AL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITH BUILT IN CL. A FILTER WITH BUILT IN BRAKING CHOPPER 3AC380-480V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 4KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 5,5KW FOR 150% 3S,110% 57S	3	0
6SL3210-1PB13-8UL0	SIEMENS	SINAMICS POWER MODULE PM240-2 WITHOUT FILTER WITH BUILT IN BRAKING CHOPPER 1/3AC200-240V +10/-10% 47-63HZ OUTPUT HIGH OVERLOAD: 0,55KW FOR 200% 3S,150% 57S,100% 240S AMBIENT TEMP -10 TO +50 DEG C OUTPUT LOW OVERLOAD: 0,75KW FOR 150% 3S,110% 57S,100%	0	6

## SINAMICS - dostępne komponenty

6SL3211-1NE17-7UL0	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 / PT 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 3KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 238 X 126 X 171 (HXWXD), FSA WITHOUT CONTROL UNIT AND PANEL APPROVED	0	1
6SL3223-0DE31-8AA1	SIEMENS	SINAMICS G120P POWER MODULE PM230 WITH BUILT IN CL. A FILTER PROTECTION IP55 / UL TYPE12 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 18,5KW FOR 150% 3S,110% 57S,100% 240S AMBIE. TEMP -10 TO+40 DEG C(LO) 620 X 230 X 249 (HXBXT), FSC WITHOUT CONT	0	2
6SL3210-5BE31-8CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ OUTPUT HIGH OVERLOAD: 18,5KW WITH 150% OVERLOAD FOR 60SEC OUTPUT LOW OVERLOAD: 22KW WITH 110% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP	2	0
6SL3210-1NE12-2UG1	SIEMENS	SINAMICS G120 POWER MODULE PM230 UNFILTERED PROTECTION IP20 3AC380-480V +10/-10% 47-63HZ OUTPUT LOW OVERLOAD: 0,75KW FOR 150% 3S,110% 57S,100% 240S AMBIENT TEMP 0 TO +40 DEG C(LO) 196 X 73 X 165 (HXWXD), FSA WITHOUT CONTROL UNIT AND PANEL APPROVED FO	0	1
6SL3210-5BE32-2CV0	SIEMENS	SINAMICS V20 3AC380-480V -15/+10% 47-63HZ RATED POWER 22KW WITH 150% OVERLOAD FOR 60SEC OUTPUT LOW OVERLOAD: 30KW WITH 110% OVERLOAD FOR 60SEC INTEGRATED FILTER C3 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION:	2	0
6SL3210-1KE11-8AF2	SIEMENS	SINAMICS G120C RATED POWER 0,55KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X17	0	1
6SL3210-1KE15-8AF2	SIEMENS	SINAMICS G120C RATED POWER 2,2KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178	0	+ 10
6SL3210-1KE13-2AF2	SIEMENS	SINAMICS G120C RATED POWER 1,1KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178	0	+ 10
6SL3210-1KE14-3AF2	SIEMENS	SINAMICS G120C RATED POWER 1,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178	0	1
6SL3210-1KE14-3UB2	SIEMENS	SINAMICS G120C RATED POWER 1,5KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: USS/ MODBUS RTU PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X155(HXWXD) EXT	0	2
6SL3210-1KE12-3UF2	SIEMENS	SINAMICS G120C RATED POWER 0,75KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178(HXWXD) EXTERN	0	1

## SINAMICS - dostępne komponenty

6SL3210-1KE15-8UF2	SIEMENS	SINAMICS G120C RATED POWER 2,2KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178(HXWXD) EXTERN	0	1
6SL3210-1KE13-2UF2	SIEMENS	SINAMICS G120C RATED POWER 1,1KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO,1AI,1AO SAFE TORQUE OFF INTEGRATED FIELD BUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSAA 173X73X178(HXWXD) EXTERNA	1	0
6SL3210-5BB17-5UV1	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,75KW / 1HP WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSAB 68X142X128(WXHXD)	0	9
6SL3210-5BB12-5UV1	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,25KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSAA 68X142X108(WXHXD)	+ 10	2
6SL3210-5BB13-7UV1	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,37KW WITH 150% OVERLOAD FOR 60SEC UNFILTERED I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSAA 68X142X108(WXHXD)	0	6
6SL3210-5BB12-5BV1	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,25KW WITH 150% OVERLOAD FOR 60SEC FILTER B I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSAA 68X142X108(WXHXD)	0	1
6SL3210-5BB13-7BV1	SIEMENS	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 0,37KW WITH 150% OVERLOAD FOR 60SEC FILTER B I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELD BUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSAA 68X142X108(WXHXD)	0	2
6SL3255-0AA00-4JC1	SIEMENS	SINAMICS G120 INTELLIGENT OPERATOR PANEL IOP OPTIONAL OPERATOR PANEL FOR SINAMICS G120, G120P, G110M, G110D, G120D, G120C, S110, ET200S FC, ET200PRO FC LANGUAGE SUPPORT: CHINESE, ENGLISH, GERMAN	0	2
6SL3210-5FB10-2UA0	SIEMENS	SINAMICS V90 INPUT: 1/3 AC200-240V -15%/+10% 3.0A/1.8A 45-66HZ OUTPUT: 0-INPUT V 1.4A 0-330H PROTECTION: IP20 MOTOR:0.2KW FRAME SIZE A, 45X170X170(WXHXD)	0	1
6SL3210-5FB10-4UA1	SIEMENS	SINAMICS V90 INPUT: 1/3 AC 200-240V -15%/+10% 5.0A/3.0A 45-66HZ OUTPUT: 0-INPUT V 2.6A 0-330HZ PROTECTION: IP20 MOTOR:0.4KW FRAME SIZE B, 55X170X170(WXHXD)	0	5
6SL3210-5FB12-0UA0	SIEMENS	SINAMICS V90 INPUT: 3AC 200-240V -15%/+10% 12.0A 45-66HZ OUTPUT: 0-INPUT V 11.6A 0-330HZ PROTECTION: IP20 MOTOR:2KW FRAME SIZE D, 95X170X195(WXHXD)	0	1
6SL3120-1TE31-3AB0	SIEMENS	SINAMICS SINGLE MOTOR MODULE INPUT: 600 V DC OUTPUT: 3AC 400V, 132A INTERNAL AIR COOLING INCL. DRIVE-CLIQ CABLE BOARD COATED	0	1
6SL3120-2TE13-0AD0	SIEMENS	SINAMICS S120 DOUBLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 3A/3A FRAME SIZE: BOOKSIZE D-TYPE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	4	3
6SL3352-1AE36-1CA0	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR 510-650 V DC, 605 A MOTOR MODULE PHASE U	1	0



## SINAMICS - dostępne komponenty

6SL3352-1AE36-1EA0	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR 510-650 V DC, 605 A MOTOR MODULE PHASES U AND V	1	0
6SL3210-5FB10-2UF0	SIEMENS	SINAMICS V90, WITH PROFINET INPUT: 1/3 AC200-240V -15%/+10% 3.0A/1.8A 45-66HZ OUTPUT: 0-INPUT V 1.4A 0-330HZ MOTOR:0.2KW PROTECTION: IP20 FRAME SIZE B, 55X170X170(WXHXD)	0	2
6SL3120-1TE23-0AD0	SIEMENS	SINAMICS S120 SINGLE MOTOR MODULE INPUT: DC 600V OUTPUT: 3AC 400V, 30A FRAME SIZE: BOOKSIZE D-TYPE INTERNAL AIR COOLING OPTIMIZED PULSE SAMPLE AND SUPPORT OF THE EXTENDED SAFETY INTEGRATED FUNCTIONS INCL. DRIVE-CLIQ CABLE	0	1
6RA8000-0MV62-0AA0-Z	SIEMENS	SINAMICS DCM CONTROL MODULE WITHOUT POWER SECTION INCL 40A CONTROLLABLE FIELD RECTIFIER; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	2
6FX8002-5DS64-1AD0	SIEMENS	POWER CABLE, PREASSEMBLED TYPE: 6FX8002-5DS64 4X10 + (2X1.5)C C CONNECTOR FULL THREAD SIZE 1.5 FOR SINAMICS S120 MOTOR MODULE BOOKSIZE RING TERMINAL END ON MOD. SIDE MOTION-CONNECT 800PLUS TRAIL. TYPE, UL/CSA DESINA, DMAX=20.1 MM LENGTH (M) = 0 + 0 +	1	0
6RA8028-6FV62-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 480V, 75A CONTROLLABLE FIELD RECTIFIER D500/90 MREQ-GEG6V62 OUTPUT: DC 500V, 90A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6FX5002-5DS01-1BF0	SIEMENS	POWER CABLE, PREASSEMBLED TYPE: 6FX5002-5DS01 (1FT/1FK/1PH TO SINAMICS) 4X1.5+(2X1.5) C, CONNECTOR SIZE 1/1.5 MM2 UL/CSA DESINA, MOTION-CONNECT 500 DMAX = 13.1 MM, LENGTH (M) = 0 + 10 + 5 + 0	1	0
6SL3162-0AN00-0AA0	SIEMENS	SINAMICS S120 BOOKSIZE SPARE FAN FOR 50MM C-/D-TYPE MOTOR MODULE	1	0
6SL3162-8AC00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT SINGLE MOTOR MODULE 50MM C-/D-TYPE	1	0
6SL3162-8AD00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT DOUBLE MOTOR MODULE 50MM C-/D-TYPE	2	0
6SL3162-8BE00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT SINGLE MOTOR MODULE 100MM C-/D-TYPE	1	0
6SL3210-1RE27-5AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240P-2 WITH BUILT IN CL. A FILTER; 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 30KW FOR 150% 60S, 100% 240S; AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 37KW FOR 135% 3S, 110% 57S,100% 240S AMBIENT TEMP	0	1
6SL3210-1RE31-1AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240P-2 WITH BUILT IN CL. A FILTER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 45KW FOR 150% 60S, 100% 240S; AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 55KW FOR 135% 3S,110% 57S,100% 240S AMBIENT TEMP -	0	1
6SL3210-1RE32-5AL0	SIEMENS	SINAMICS G120 POWER MODULE PM240P-2 WITH BUILT IN CL. A FILTER 3AC380-480V +10/-20% 47-63HZ OUTPUT HIGH OVERLOAD: 110KW FOR 150% 60S, 100% 240S; AMBIENT TEMP -20 TO +50 DEG C (HO) OUTPUT LOW OVERLOAD: 132KW FOR 135% 3S,110% 57S,100% 240S AMBIENT TEMP	0	1
6SL3210-5FB10-1UF0	SIEMENS	SINAMICS V90, WITH PROFINET INPUT: 1/3 AC 200-240V -15%/+10% 2.5A/1.5A 45-66HZ OUTPUT: 0-INPUT V 1.2A 0-330HZ MOTOR:0.1KW PROTECTION: IP20 FRAME SIZE B, 55X170X170(WXHXD)	0	2
6SL3210-5FB10-4UF1	SIEMENS	SINAMICS V90, WITH PROFINET INPUT: 1/3 AC 200-240V -15%/+10% 5.0A/3.0A 45-66HZ OUTPUT: 0-INPUT V 2.6A 0-330HZ MOTOR:0.4KW PROTECTION: IP20 FRAME SIZE B, 55X170X170(WXHXD)	0	1

## SINAMICS - dostępne komponenty

6SL3210-5FE10-4UF0	SIEMENS	SINAMICS V90, WITH PROFINET INPUT: 3AC 380-480V -15%/+10% 1.5A 45-66HZ OUTPUT: 0-INPUT V 1.2A 0-330HZ MOTOR:0.4KW PROTECTION: IP20 FRAME SIZE AA 60X180X200(WXHxD)	0	3
6SL3210-5FE10-8UF0	SIEMENS	SINAMICS V90, WITH PROFINET INPUT VOLTAGE: 380-480 V 3 A -15%/+10% 2.6 A 45-66 HZ OUTPUT VOLTAGE: 0 INPUT 2.1 A 0-330 HZ MOTOR: 0.75 KW DEGREE OF PROTECTION: IP20 SIZE A, 80X180X200 (WXHxD)	0	7
6SL3210-5FE11-0UF0	SIEMENS	SINAMICS V90, WITH PROFINET INPUT: 3AC 380-480V -15%/+10% 3.8A 45-66HZ OUTPUT: 0-INPUT V 3.0A 0-330HZ MOTOR:0.75/1.0KW PROTECTION: IP20 FRAME SIZE A, 80X180X200(WXHxD)	0	2
6SL3210-5FE11-5UF0	SIEMENS	SINAMICS V90, WITH PROFINET INPUT: 3AC 380-480V -15%/+10% 6.6A 45-66HZ OUTPUT: 0-INPUT V 5.3A 0-330HZ MOTOR:1.5/1.75KW PROTECTION: IP20 FRAME SIZE B, 100X180X220(WXHxD)	0	1
6SL3300-7TE33-8AA1	SIEMENS	SINAMICS ACTIVE INTERFACE MODULES FOR 3-PH 380-480 V, 50/60 HZ 235 KW ACTIVE LINE MODULE INTERNAL AIR COOLING PT1000	1	0
6SL3351-6GE37-5AB3	SIEMENS	SINAMICS G REPLACEMENT CONTROL INTERFACE BOARD FOR 3AC 380-480 V, 50/60HZ, 745 A POWER MODULE	0	2
6SL3210-1KE31-1UF1	SIEMENS	SINAMICS G120C RATED POWER 55.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSE 551X 275X 237(HXWXD) EX	0	1
6SL3210-1KE32-4AF1	SIEMENS	SINAMICS G120C RATED POWER 132.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSF 708X 30	0	1
6SL3352-1AH41-0FA0	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR 890-930 V DC, 1025 A MOTOR MODULE PHASE U OR V OR W	0	3
6RA8078-6DS22-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR TWO-QUADRANT DRIVES CONNECTION B6C INPUT: 3-PHASE AC 400V, 232A CONTROLLABLE FIELD RECTIFIER D485/280 MRE-GEEF6S22 OUTPUT: DC 485V, 280A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	2
6SL3710-1GF32-6AA3-Z	SIEMENS	SINAMICS G150 CONVERTER CABINET UNIT, AC/AC WITH CIM+CU320-2 3AC 500-600V, 50/60HZ NOM. POWER RATING: 160KW 6-PULSE SYSTEM WITHOUT REGENERATIVE FEEDBACK VERSION A, INKL. EMV-FILTER 2. AMB. CONDITION, CATEGORY C3	0	1
6SL3210-1KE27-0AF1	SIEMENS	SINAMICS G120C RATED POWER 37.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSD 472X 200	0	2
6SL3210-1KE28-4AF1	SIEMENS	SINAMICS G120C RATED POWER 45.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSD 472X 200	0	1
6SL3210-1KE28-4UF1	SIEMENS	SINAMICS G120C RATED POWER 45.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ UNFILTERED I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSD 472X 200X 237(HXWXD) EX	0	1

## SINAMICS - dostępne komponenty

6SL3210-1KE31-1AF1	SIEMENS	SINAMICS G120C RATED POWER 55.0KW WITH 150% OVERLOAD FOR 3 SEC 3AC380-480V +10/-20% 47-63HZ INTEGRATED FILTER CLASS A I/O-INTERFACE: 6DI, 2DO, 1AI, 1AO SAFE TORQUE OFF INTEGRATED FIELDBUS: PROFINET-PN PROTECTION: IP20/ UL OPEN TYPE SIZE: FSE 551X 275	0	1
6SL3544-0FA21-1FB0	SIEMENS	SINAMICS G120D CONTROL UNIT CU240D PN-F PROFINET AND SAFETY INTEGRATED PUSH-PULL DESIGN 6 DI, 2 DO PTC/KTY INTERFACE EM-BRAKE CONTROL, MMC INTERFACE ENCODER INTERFACE PROTECTION IP65 AMBIENT TEMP 0 TO +40 DEG C WITHOUT POWER MODULE	2	0
6SL3255-0AA00-4JA2	SIEMENS	SINAMICS G INTELLIGENT OPERATOR PANEL IOP-2 FOR SINAMICS G120, G120P, G110M, G110D, G120D, G120C, ET 200PRO FC-2 LANGUAGE SUPPORT: GERMAN, ENGLISH, FRENCH, ITALIAN, SPANISH, PORTUGUESE, DUTCH, SWEDISH, RUSSIAN, CZECH, POLISH, TURKISH, FINNISH, CHINES	1	0
6RA8087-6GV62-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 575V, 706A CONTROLLABLE FIELD RECTIFIER D600/850 MREQ-GEGF6V62 OUTPUT: DC 600V, 850A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	1	0
6SL3210-5CB13-7AA0	SIEMENS	SINAMICS V80 INPUT: 200-230V 1AC, 50/60 HZ OUTPUT: 3AC 3.7A (750W)	0	2
6RA8028-6DS22-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR TWO-QUADRANT DRIVES CONNECTION B6C INPUT: 3-PHASE AC 400V, 75A CONTROLLABLE FIELD RECTIFIER D485/90 MRE-GEE6S22 OUTPUT: DC 485V, 90A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6SL3352-6TG32-2AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 500-690V 3AC, 50/60 HZ, 215 A MOTOR MODULE	0	3
6SL3352-6TG37-4AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 500-690V 3AC, 50/60 HZ, 735A MOTOR MODULE	0	1
6SL3352-6TG28-5AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 500-690V 3AC, 50/60 HZ, 85A MOTOR MODULE	0	+ 10
6SL3352-6TG32-6AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 500-690V 3AC, 50/60 HZ, 260 A MOTOR MODULE	0	5
6SL3352-6TG31-8AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 500-690V 3AC, 50/60 HZ, 175 A MOTOR MODULE	0	2
6SL3352-6TE41-0AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 380-480V 3AC, 50/60 HZ, 985A MOTOR MODULE	0	2
6SL3352-6TH33-3AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 660-690V 3AC, 50/60 HZ, 330A MOTOR MODULE	0	1
6SL3352-6TH31-5AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 660-690V 3AC, 50/60 HZ, 145A MOTOR MODULE	0	1
6SL3352-6TG31-2AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 500-690V 3AC, 50/60 HZ, 120 A MOTOR MODULE	0	+ 10
6SL3352-6TG31-0AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 500-690V 3AC, 50/60 HZ, 100 A MOTOR MODULE	0	1
6SL3126-2TE15-0AA0	SIEMENS	SINAMICS DOUBLE MOTOR MODULE INPUT: DC 600 V OUTPUT: 3-PH. 400 V, 5 A/5 A COLD-PLATE COOLING INCL. DRIVE-CLIQ CABLE	0	1
6SL3352-1AG32-2AA1	SIEMENS	SINAMICS REPLACEMENT POWER BLOCK FOR 675-1035 DC, 215 A MOTOR MODULE 3 PHASES PAINTED MODULES AND NICKEL-PLATED BUSBARS	5	0
6RA8078-6DV62-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR FOUR-QUADRANT DRIVES CONNECTION (B6) A (B6) C INPUT: 3-PHASE AC 400V, 232A CONTROLLABLE FIELD RECTIFIER D420/280 MREQ-GEGF6V62 OUTPUT: DC 420V, 280A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1

### SINAMICS - dostępne komponenty

6RA8081-6DV62-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR 4-QUADRANT DRIVES CIRCUIT (B6) A (B6) C INPUT: 400V 3AC, 332A CONTROLLABLE: FIELD RECTIFIER D420/400 MREQ-GEGF6V62 OUTPUT: 420 V DC, 400 A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	1	3
6RA8028-6DV62-0AP0-Z	SIEMENS	SINAMICS DCM DC-PACKAGE 3AC 400V/50HZ/DC 90A/4Q 1 6RA8028-6DV62-0AA0 1 SWITCH-DISCONNECTOR-FUSE 1 CONTACTOR ARM+SNUBBER 1 COMMUTATING CHOKE ARMATURE 3 AC_SEMICONDUCTOR FUSE 1 DC_SEMICONDUCTOR FUSE+HOLDER 1 CONTACTOR EXCITATION INCL. SNUBBER CIRCUIT 1	0	1
6RA8025-6DS22-0AA0-Z	SIEMENS	SINAMICS DCM DC CONVERTER FOR TWO-QUADRANT DRIVES CONNECTION B6C INPUT: 3-PHASE AC 400V, 50A CONTROLLABLE FIELD RECTIFIER D485/60 MRE-GEE6S22 OUTPUT: DC 485V, 60A; BASE DRIVE FOR ADDITIONAL OPTIONS PLEASE CONTACT OUR SALES STAFF!	0	1
6SL3210-1SE15-9AA0	SIEMENS	6SL3210-1SE15-9AA0	0	1
6SL3210-1QE31-5AL0	SIEMENS	SINAMICS V90	0	1
6SL3210-5BE18-8UV0	SIEMENS	SINAMICS V90	0	1
6SL3350-6TK00-0DA0	SIEMENS	SINAMICS SPARE PART CONTROL INTERFACE MODULE (CIM) VERSION FPGA FOR LIQUID-COOLED DEVICES	0	+ 10
6SL3162-8BG00-0AA0	SIEMENS	SINAMICS S120 TERMINAL KIT SINGLE MOTOR MODULE 45 A/60 A C-TYPE	1	0
6FX5002-2DC00-1AC0	SIEMENS	SIGNAL CABLE PRE-ASSEMBLED TYPE: 6FX5002-2DC00 (SINAMICS DRIVE CLIQ) CONNECTOR IP20/IP20, WITH 24 V MOTION-CONNECT 500 LENGTH (M)= 0 + 0 + 2 + 0	3	0
6SL3352-6TE32-1AA3	SIEMENS	SINAMICS S REPLACEMENT CONTROL INTERFACE BOARD FOR 3PH 380-480 V, 50/60 HZ, 210 A MOTOR MODULE	0	1