

MICROMASTER 4 AC COMMUTATION CHOKE 200V-480V 3AC  
4,8A FOOTPRINT FSA - 3X1.53MH NOT FOOTPRINT FOR V20



Order number	6SE6400-3CC00-6AD3
Number of phases / of input voltage	3
Type of / input voltage	AC
Input voltage	380 ... 480
Output current / rated value	4.8 A
Effective power loss	
• at 50 Hz	7.5 W
• at 60 Hz	9 W
• Design of electrical connection / for mains supply line	Screw-type terminals
• Design of the electrical connection / for motor outgoing line	Cable
Type of connectable conductor cross-sections / for load-side outgoing feeder	3 x AWG16
Connectable conductor cross-section	
• for line supply conductor	6 mm <sup>2</sup>
• for load-side outgoing feeder	1.5 mm <sup>2</sup>
Cable length / of connecting cable / for load-side outgoing feeder	0.38 m
Design of electrical connection / for PE conductor	M5 stud bolt
Protection class IP	IP20

Width	75.5 mm
Height	201 mm
Depth	50 mm
Net weight	1.3 kg
Verification of suitability	cURus

#### Further information

##### **Information und Download Center**

[https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order\\_form.aspx](https://www.automation.siemens.com/mcms/infocenter/content/en/Pages/order_form.aspx)

##### **Technical documentation**

<http://w3.siemens.com/mcms/mc-solutions/en/motion-control/support/technical-documentation/Pages/technical-documentation.aspx>

##### **Industry Mall**

<https://eb.automation.siemens.com/mall/en/WW/Catag/Product/6SE64003CC006AD3/all>

##### **Industry Online Support**

<http://support.automation.siemens.com/WW/view/en/6SE64003CC006AD3/all>