



Figure similar

MLFB-Ordering data

6SL3210-5CC14-0UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
Input		Cooling	natural convection
Number of phases	3 AC	Installation altitude	1000 m
Line voltage	220 ... 240 V -15 % +10 %	Cooling air requirement	0.005 m³/s (0.016 ft³/s)
Line frequency	45 ... 66 Hz	Ambient temperature	
Output		Operation	0 ... 45 °C (32 ... 113 °F)
Rated power	0.80 kW	Storage	20 ... 80 °C (68 ... 176 °F)
Rated current (IN)	4.00 A	Transport	20 ... 80 °C (68 ... 176 °F)
Max. output current	8.00 A	Relative humidity	
General tech. specifications		Max. operation	95 %
Sound pressure level (1m)	45 dB	Standards	
Power loss	36.00 W	Compliance with standards	CE
Connections			
Motor end			
Conductor cross-section	2.5 mm²		
Mechanical data			
Degree of protection	IP20		
Net weight	2.63 kg (5.80 lb)		
Width	106.0 mm (4.17 in)		
Height	226.0 mm (8.90 in)		
Depth	200.0 mm (7.87 in)		