



Figure similar

MLFB-Ordering data

6FX2001-5VD13-0AA1

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

### Electrical data

Operating voltage Up	DC 24 V - 15 % + 20 %
Max. power consumption	245 mA
Interface	DRIVE-CLiQ
Data output	DRIVE-CLiQ
Short-circuit strength	Yes
Transmission rate	100 Mbit/s
Cable length up to the subsequent electronics, max.	100 m
Connection type	DRIVE-CLiQ connector, Radial
Resolution	22 bit
Incremental track	2048 S/R, 1 Vpp (encoder-internal only)
Accuracy	± 36 "

### Code type

Sampling	Gray
Transmission	DRIVE-CLiQ

### Parameterizability

Counting direction	Yes
--------------------	-----

### Ambient temperature

During operation	-20 ... 100 °C
------------------	----------------

### Standards

Compliance with standards	CE, cULus
EMC class filter	Tested to DIN EN 50081 and EN 50082

### Mechanical data

Shaft version	Hollow shaft
Shaft diameter	10 mm
Angular acceleration, max.	100000 rad/s <sup>2</sup>
Moment of inertia of rotor	0.00000280 kgm <sup>2</sup>
Vibration (55...2000 Hz), max.	100 m/s <sup>2</sup>
Friction torque (at 20°C)	≤ 0.01 Nm
Starting torque (at 20°C)	≤ 0.01 Nm
Net weight	0.4 kg

### Max. admissible speed

Electrical	14000 rpm
Mechanical	12000 rpm

### Load capacity

n = 6000 rpm	
- Axial	10 N
- Radial at shaft end	20 N
n > 6000 rpm	
- Axial	40 N
- Radial at shaft end	60 N

### Shock, max.

2 ms	2000 m/s <sup>2</sup>
6 ms	1000 m/s <sup>2</sup>

### Degree of protection

Without shaft input	IP67
With shaft input	IP64