

SIMATIC DP, ELECT. SUBMODULE FOR ET 200ISP, 4 DO, DC 23,1V/20MA, "L"-SHUT DOWN



Input current

from load voltage L+ (without load), max.	340 mA; with actuator supply
from backplane bus 3.3 V DC, max.	10 mA

Power loss

Power loss, typ.	2.5 W
------------------	-------

Address area

Address space per module

• without packing	2 byte
-------------------	--------

Digital outputs

Number of digital outputs	4; additionally 1 intrinsically-safe input for L shutdown
Short-circuit protection	Yes
No-load voltage U_{ao} (DC)	23.1 V
Internal resistor R_i	275 Ω

Trend key points E

• Voltage U_e (DC)	17.6 V
• Current I_e	20 mA

Output current

• for signal "1" rated value	0.02 A
------------------------------	--------

Output delay with resistive load	
• "0" to "1", max.	2 ms
• "1" to "0", max.	1.5 ms
Parallel switching of two outputs	
• for uprating	No; for Ex reasons not possible; nor for predecessor
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
Cable length	
• shielded, max.	500 m
• unshielded, max.	500 m
Interrupts/diagnostics/status information	
Status indicator	Yes
Diagnostic functions	Yes
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostic messages	
• Diagnostic information readable	Yes
• Wire-break	Yes; $R > 10 \text{ kohms}$, $I < 100 \mu\text{A}$
• Short-circuit	Yes; $R < 80 \text{ Ohm}$ (one output), $R < 40 \text{ Ohm}$ (outputs connected in parallel)
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
Parameter	
Remark	14 byte
Diagnostics wire break	Yes
Diagnostics short-circuit	Yes
Response to CPU/master STOP	Substitute a value/keep last value
Ex(i) characteristics	
Maximum values of output circuits (per channel)	
• T_a (permissible ambient temperature), max.	70 °C
Potential separation	
Potential separation digital outputs	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Standards, approvals, certificates	
CE mark	Yes
Highest safety class achievable in safety mode	

• SIL acc. to IEC 61508

No

Use in hazardous areas

• Type of protection acc. to EN 50020
(CENELEC)

II2 G (1) GD Ex ib[ia] IIC T4 and I M2 Ex ib[ia] I

• Type of protection acc. to KEMA

04 ATEX 1249

Dimensions

Width

30 mm

Height

129 mm

Depth

136.5 mm

Weights

Weight, approx.

255 g

last modified:

03/07/2017