

SIMATIC DP, RS485 REPEATER FOR THE CONNECTION OF PROFIBUS/MPI BUS SYSTEMS WITH MAX. 31 NODES; MAX. 12 MBIT/S, DEGREE OF PROTECTION IP20 IMPROVED USABILITY



Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	100 mA; 100 mA without loads at PG/OP socket; 130 mA load at PG/OP socket (5 V/90 mA); 200 mA load at PG/OP socket (24 V/100 mA)
Power loss	
Power loss, typ.	0.7 W
Interfaces	
PROFIBUS DP	
• Transmission rate, max.	12 Mbit/s; 9.6 kbit/s to 12 Mbit/s
Degree and class of protection	
Degree of protection acc. to EN 60529	Yes
• IP20	
Ambient conditions	

<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	-40 °C
• max.	70 °C
<b>Relative humidity</b>	
• Operation, max.	95 %; at 25 °C
<b>Connection method</b>	
Power supply	Terminal block
Bus cables	2 terminal blocks
<b>Dimensions</b>	
Width	45 mm
Height	128 mm
Depth	67 mm
<b>Weights</b>	
Weight, approx.	350 g
<b>last modified:</b>	03/24/2017